


HYSTER COMPANY PRICE LIST	BATTERY SPECIFICATIONS
--	-------------------------------

NOTICE:

AS A CONVENIENCE TO DEALERS, THE BATTERIES AND CHARGERS SHOWN ON THE FOLLOWING PAGES ILLUSTRATE SOME OF THE MODELS AVAILABLE FROM TWO MANUFACTURERS. THESE LISTINGS DO NOT IMPLY APPROVAL OR RECOMMENDATION, NOR DOES THE OMISSION OF ANY MANUFACTURERS IMPLY DISAPPROVAL.

REFER TO THE BATTERY SPECIFICATIONS SECTION IN YOUR CLASS I, II, OR III TECHNICAL GUIDES FOR APPROVED BATTERY DIMENSION AND PERFORMANCE REQUIREMENTS.

Subject to Change Without Notice		Replaces 02/15/01	PAGE E-10.1 Effective 12/01/02
---	--	------------------------------------	---



HYSTER COMPANY PRICE LIST

BATTERY SPECIFICATIONS COUNTERBALANCED ELECTRICS

TRUCK		BATTERY							
MODEL	BATTERY COMPART. WIDTH	VOLTS	CELLS/ PLATES	COVER	LEADS			CONNECTOR SB 350	T BATTERY CODE
					LENGTH	POSITION	GAUGE		
E25- 40XM2S x	27.36"	36	18/17-19	NO	30"	A	2/0	6320G1*	A
		48	24/13-15					6321G1*	B
E45XM2 E50XM2	27.32"	36	18/23					6320G1*	HH
		48	24/17					6321G1*	JJ
E45XM2 E50XM2 E55XM2 E60XM2	33.15"	36	18/27	NO	30"	B	2/0	6320G1+	KK
		48	24/21					6321G1+	LL
N30XMH E65XM2	39.76"	36	18/33					6321G1+	E
		48	24/25					6321G1+	F
E70XL3 E80XL3	39.20"	36	8/17-19+ 18/33	NO	30"	B	3/0	6320G1*	L
		48	24/27					6321G1*	Y
E100XL3 E120XL3	45.70"	36	18/19-21+	NO	30"	B	3/0	6320G1*	M
		48	24/33					6321G1*	Z
E30HSD	18.25	36	18/15	NO	30"	B	2/0	6320G1*	T
	16.25	36	18/13	NO	30"	B	2/0	6320G1*	T
E35HSD	18.25	36	18/15	NO	30"	B	2/0	6320G1*	TT
	20.75	36	18/17	NO	30"	B	2/0		
E40HSD	20.75	36	18/17	NO	30"	B	2/0		

+ Two 18 cell 36 volt batteries in one tray.

T See Battery Pages.

* All SB 350 Connectors require a disconnect handle (Anderson 919G1 or Brad Harrison Hyster Part No. 240483) for OSHA Compliance.

+ All SB 350 Connectors require a discount handle (Anderson 955G2 or Brad Harrison 66-0251).

| Trucks ordered without cover and side panels require a covered battery. Consult battery manufacturer for correct hinge alignment on battery cover.

x Optional battery compartment Opt. Code 027-02 requires 19 plate batteries.

See your Truck Specification Sheets for Minimum-Maximum Battery Sizes.

Subject to Change Without Notice

Replaces
02/15/01

PAGE E-10.2
Effective
12/01/02



HYSTER COMPANY PRICE LIST	BATTERY SPECIFICATIONS COUNTERBALANCED ELECTRICS
--	---

TRUCK		BATTERY						CONNECTOR SB 350	+ BATTERY CODE
MODEL	BATTERY COMPART WIDTH	VOLTS	CELLS/ PLATES	COVER	LEADS LENGTH	POSITION	GAUGE		
J30XMT2	16.70"	36	18/13	NO	30"	B	2/0	6320G1+	EE
		48	24/9					6321G1+	BB
J30XMT2	21.5"	36	18/17	NO	30"	B	2/0	6320G1+	K
		48	24/13					6321G1+	N
J35XMT2	25.20"	36	18/21	NO	30"	B	2/0	6320G1+	FF
J40XMT2		48	24/15					6321G1+	CC
J40- 50XM2	28.30"	36	18/23	NO	11.8"	B	2/0	6320G1	G
		48	24/17					6321G1	H
J50 -60XM2	33.9"	36	18/27	NO	11.8"	B	2/0	6320G1	J
		48	24/21					6321G1	AA

+ See Battery Pages.

+ Requires Anderson Disconnect Handle Anderson 911 for OSHA Compliance.


! Trucks ordered without cover and side panels require a covered battery. Consult battery manufacturer for correct hinge alignment on battery cover.

** Specify minimum and maximum battery specifications when ordering batteries.

See your Truck Specification Sheets for Minimum-Maximum Battery Sizes.

FOR BATTERY SPECIFICATIONS ON
NARROW AISLE, ORDER PICKER AND WALKIE PRODUCT
SEE PAGES E-10.9 AND E-10.10

Subject to Change Without Notice		Replaces 02/15/01	PAGE E-10.3 Effective 12/01/02
----------------------------------	--	----------------------	--------------------------------------



HYSTER COMPANY PRICE LIST	EXIDE BATTERIES COUNTERBALANCED ELECTRICS
--	--

BATTERIES

VOLTS	BATTERY CODE†	TYPE	(6 HOURS) A.H. CAP.	(6 HOURS) K.W.H. CAP.	WEIGHT LBS.
24	C	12-E125-19	1125	26.0	1925
	C	12-E140-19	1260	29.2	2090
	C	12-E155W-19	1395	32.3	2132
36	R	18-E85-11	425	14.8	1260
	R	18-E120-11	600	20.7	1674
	EE	18-E85-13 ♦	510	17.8	1485
	EE	18-E100-13 ♦	600	20.9	1500
	EE	18-E110W-13 ♦	660	22.9	1590
	T	18-E125-13	750	26.1	1984
	T	18-E140-13	840	29.2	2182
	T	18-E155-13	930	32.2	2226
	A-K	18-E85-17	680	23.8	1942
	A-K	18-E100-17	800	27.7	1961
	TT	18-E140-17	1120	38.9	2852
	A-K	18-E110W-17	880	30.6	2080
	TT	18-E155-17	1240	43.0	2909
	M	18-E85-19*	1530	53.2	4346
	A	18-E85-19 ‡	785	26.6	2173
	A	18-E100-19 ‡	900	31.3	2195
	M	18-E100-19*	1800	62.6	4536
	M-L	18-E110W-19 *	1980	68.8	4625
	A	18-E110W-19 ‡	990	34.4	2328
	FF	18-E85-21^	850	29.7	2404
	FF	18-E100-21^	1000	34.7	2428
	FF	18-E110W-21^	1100	38.2	2574
	GG	18-E75-21	750	26.1	2205
	GG	18-E85-21	850	29.7	2404
	M	18-E85-21 *	1700	59.4	4716
	GG	18-E100-21	1000	34.7	2428
	M	18-E100-21 *	2000	69.5	5040
	HH	18-E75-23	825	28.6	2415
	HH	18-E85-23	935	32.6	2630
	HH	18-E100-23	1100	38.2	2656
	G	18-E140-23	1540	53.3	3841
	G	18-E-155W-23	1705	59.2	3918
	J	18-E155W-27	2015	70.0	4689
	J	18-E140-27	1820	63.0	4587
	KK	18-E85-27	1105	38.5	3087
	KK	18-E100-27	1300	45.2	3118
	L-J-E	18-E85-33	1360	47.3	3774
	J	18-E75-33 **	1200	41.9	3465
	L-J-E	18-E100-33	1600	55.4	3812
	L	18-E110W-33	1760	61.2	4042

^ Requires Battery Spacer Option 201-01 on J35XMT and Battery Counterweight Option 200-02 on J40XMT

‡ Requires Battery Compartment Option Code 027-02 (E25-40XM).


† See Standard Battery Specification Pages For Truck Models.

* Two 18 cell, 36 volt batteries, in one tray.

** N/A for E100XLS.

♦ Requires Battery Counterweight Option 200-01

Subject to Change Without Notice		Replaces 02/15/01	PAGE E-10.4 Effective 12/01/02
----------------------------------	--	----------------------	--------------------------------------



HYSTER COMPANY PRICE LIST	EXIDE BATTERIES COUNTERBALANCED ELECTRICS
--	--

BATTERIES (CONT'D.)

VOLTS	BATTERY CODE†	TYPE	(6 HOURS) A.H. CAP.	(6 HOURS) K.W.H. CAP.	WEIGHT LBS.
48	BB	24-E85-9 ♦	340	15.8	1396
	BB	24-E100-9 ♦	400	18.5	1410
	BB	24-E110W-9 ♦	440	20.0	1495
	B-N	24-E110W-13	660	30.5	2159
	N-B	24-E85-13	510	23.8	2016
	N-B	24-E100-13	600	27.8	2036
	B	24-E85-15 ‡	595	27.6	2325
	B	24-E100-15 ‡	700	32.4	2348
	B	24-E110W-15 ‡	770	35.8	2490
	CC	24-E85-15 ^	595	27.6	2325
	CC	24-E100-15 ^	700	32.4	2348
	CC	24-E110W-15 ^	770	35.8	2490
	JJ	24-E85-17	680	31.7	2635
	JJ	24-E100-17	800	37.0	2661
	JJ	24-E110W-17	880	40.8	2822
	H	24-E140-17	1120	51.8	3869
	H	24-E155-17	1240	57.4	3946
	F	24-E85-19	765	35.3	2945
	F	24-E100-19	900	41.8	2975
	F	24-E110W-19	990	45.8	3154
	LL	24-E85-21	850	39.5	3255
	LL	24-E110W-21	1100	50.9	3486
	LL	24-E100-21	1000	46.3	3288
	AA	24-E140-21	1400	64.8	4775
	AA	24-E155W-21	1550	71.8	4871
	F	24-E85-25	1020	47.4	3874
	F	24-E100-25	1200	55.7	3913
	Y	24-E85-27	1105	51.4	4184
	Y	24-E100-27	1300	60.2	4226
	Y	24-E110W-27 *	1430	66.2	4481
	Z	24-E110W-33	1760	81.6	4481
	Z	24-E100-33	1600	55.4	4246

^ Requires Battery Spacer Option Code 201-01 on J35XM and Battery Counterweight Option 200-02 on J40XM.


‡ Requires Battery Compartment Option Code 027-02 (E25-40XM).

† See Standard Battery Specification Pages For Truck Models.

* N/A for E120XL.

♦ Requires Battery Counterweight Option Code 200-01

Subject to Change Without Notice		Replaces 02/15/01	PAGE E-10.5 Effective 12/01/02
---	--	------------------------------------	---




HYSTER COMPANY PRICE LIST	EXIDE CHARGERS COUNTERBALANCED ELECTRICS
---	--

CHARGERS

VOLTS	TYPE	A. H. CAP.	VOLTS	PHASE	WEIGHT LBS.
24	GE 12-1050	630/1050	208/240/480	3	350
	D3E-12-1200	720/1200	208/240/480	3	286
	D3E-12-1400	840/1400	208/240/480	3	368
36	D3 18-680	408/680	208/240/480	3	262
	D3 18-850	510/850	"	3	289
	G3 18-865	865	"	3	390
	D3 18-950	570/950	"	3	289
	G3 18-1050	1050	"	3	410
	D3 18-1050	630/1050	"	3	289
	D3 18-1200	720/1200	"	3	368
	D3 18-1400	840/1400	"	3	368
	D3 18-1600	960/1600	240/480	3	368
	D3 18-2000	1200/2000	480	3	460
	D3 24-550	330/550	208/240/480	3	280
	D3 24-680	408/680	"	3	280
	D3 24-850	510/850	"	3	369
	D3 24-1050	630/1050	"	3	369
	D3 24-1200	720/1200	240/480	3	441
	D3 24-1400	1401/1400	"	3	441
	D3 24-1600	960/1600	480	3	441
	D3 24-950	570/950	208/240/480	3	369

Subject to Change Without Notice		Replaces 02/15/01	PAGE E-10.6 Effective 12/01/02
---	--	------------------------------	---



HYSTER COMPANY PRICE LIST	GNB BATTERIES COUNTERBALANCED ELECTRICS
--	--

GNB BATTERIES

VOLTS	BATTERY CODE†	TYPE	(6 HOURS) A.H. CAP.	(6 HOURS) K.W.H. CAP.	WEIGHT LBS.
24	C	12-125C-19	1125	21.9	1971
36	R	18-85C-11	425	14.84	1287
	EE-K	18-85C-13 >	510	17.8	1433
	EE-K	18-95C-13 >	570	19.9	1506
	EE	18-100C-13	600	21.0	1698
	A	18-100A-13 ⌘			
	T	18-125C-13	750	26.3	2057
	T	18-130C-13	780	27.5	2129
	A	18-100A-15 ⌘	700	24.7	2055
	A-K	18-85C-17 >	680	23.74	2025
	L	18-85C-17‡	1360	20.06	3958
	A	18-95C-17	760	26.5	2140
	K	18-100C-17 ♦	800	27.93	2254
	TT-G	18-125C-17	1000	35.1	2679
	TT-G	18-130C-17	1040	36.7	2760
	K	18-50A-19 ⌘	450	15.9	2160
	A	18-85C-19 #	765	26.95	2241
	L-M	18-85C-19 ‡	1530	53.4	4288
	HH	18-100A-19 ⌘	900	31.8	2530
	M	18-95C-19 ‡	1710	59.7	4450
	GG-FF	18-85C-21	850	29.8	2363
	FF	18-90A-21 ⌘	900	31.8	2450
	GG-FF	18-100C-21	1000	35.2	2719
	E-L	18-100A-21 ⌘	1000	35.3	3460
	KK	18-100A-21 ⌘	1000	35.3	3150
	M	18-95C-21 *	1900	66.3	5713
	FF	18-85C-21 ^	850	29.7	2430
	FF	18-95C-21 ^	950	33.2	2462
	HH	18-85C-23	935	32.7	2660
	HH	18-95C-23	1045	36.5	2785
	J	18-100A-25 ⌘	1200	42.3	1050
	KK	18-85C-27	1105	38.5	3115
	KK	18-95C-27	1235	43.1	3300
	L-E	18-85C-33	1360	47.7	3738
	E-L	18-95C-33	1520	53.1	3914

♦ No battery counterweight required.

‡ Two batteries in one tray, requires covered battery.

† See Standard Battery Specification Pages For Truck Models.

* It is required that E100-120XL truck use two 18 cell, 36 volt batteries in one tray.

For 35.79" long optional battery compartment.

> Requires Battery Counterweight

^ Requires Battery Spacer on J35XM and Battery Counterweight on J40XM

⌘ Maintenance Free Battery

Subject to Change Without Notice		Replaces 02/15/01	PAGE E-10.7 Effective 12/01/02
---	--	------------------------------------	---



HYSTER COMPANY PRICE LIST	GNB BATTERIES COUNTERBALANCED ELECTRICS
--	--

BATTERIES (CONT'D.)

VOLTS	BATTERY CODE†	TYPE	(6 HOURS) A.H. CAP.	(6 HOURS) K.W.H. CAP.	WEIGHT LBS.
48	BB	24-85C-9 >	340	15.8	1366
	BB	24-95C-9 >	380	17.7	1402
	BB	24-100C-9	400	18.6	1950
	B	24-100A-11 ‡	500	23.5	2035
	B	24-95C-13	570	26.8	2021
	B-N	24-85C-13 >	510	23.9	1935
	N	24-100C-13 ♦	600	27.94	2457
	B	24-85C-15 #	595	27.9	2209
	N	24-50A-15 ‡	350	16.5	1965
	CC-B	24-95C-15 ^	665	31.0	2370
	CC	24-85C-15 ^	595	27.7	2320
	JJ	24-100A-15 ‡	700	32.9	2625
	F-LL	24-100A-15 ‡	700	32.9	3425
	H	24-100A-15 ‡ X	700	32.9	2975
	JJ	24-85C-17	680	31.66	2505
	JJ	24-95C-17	760	35.3	3094
	AA	24-100A-17 ‡ X	800	37.6	4000
	H	24-125C-17 X	1000	46.8	3618
	K	24-100C-19	900	38.31	3324
	LL	24-95C-21	950	44.2	3350
	LL	24-85C-21	850	39.6	3210
	Y	24-95C-25	1140	53.6	3853
	F-Y	24-85C-25	1020	47.7	3661
	Y	24-85C-27#	1105	51.4	4100
	Y	24-95C-27#	1235	57.5	4210
	Z	24-85C-33	1360	63.3	5008

‡ Maintenance Free Battery

♦ Battery counterweight not required.

> Requires Battery Counterweight for J30XM

^ Requires Battery Spacer on J35XM and Battery Counterweight on J40XM.


‡ See Standard Battery Specification Pages for Truck Models.

* Requires Covered Battery.

Truck without compact hood requires covered battery.

X Requires additional counterweight.

Subject to Change Without Notice		Replaces 02/15/01	PAGE E-10.8 Effective 12/01/02
---	--	------------------------------------	---



HYSTER COMPANY

PRICE LIST

GNB CHARGERS COUNTERBALANCED ELECTRICS

CHARGERS

VOLTS	TYPE	A. H. CAP.	VOLTS	PHASE	WEIGHT LBS.
36	FER100-18-600T	600	208/240/480	3	325
	SCR100-18-865T1	865	"	3	-
	FER100-18-750T1	750	"	3	345
	FER100-965T1	965	"	3	400
	FER100-1050T1	1050	"	3	410
	FER100-1200T1	1200	"	3	440
	FER100-1450T1	1450	"	3	480
	FER100-18-Custom	----	"	3	750
	CHP100 18-600TIU ⊕	600	"	3	-
	CHP100 18-750TIU ⊕	750	"	3	-
	CHP100 18-965TIU ⊕	965	"	3	-
	CHP100-18-1050TIU ⊕	1050	"	3	-
48	FER100-24-600T1	600	200/240/480	3	355
	CHP100-24-600TIU ⊕	600	"	3	-
	FER100-24-750T1	750	"	3	426
	CHP100-24-750TIU ⊕	750	"	3	-
	FER100-24-865T1	865	"		415
	FER100-24-965T1	965	"	3	459
	FER100-24-1050T1	1050	"	3	510
	FER100-24-1200T1	1200	"	3	550
	CHP100-24-1200TIU ⊕	1200	"	3	-
	FER100-24-1450T1	1450	"	3	600
	FER100-24-Custom	----			-

⊕ For use with Maintenance Free Batteries

Subject to Change Without Notice

Replaces
02/15/01

PAGE E-10.9
Effective
12/01/02



HYSTER COMPANY PRICE LIST	STANDARD BATTERY SPECIFICATIONS CLASS III PRODUCT
--	--

TRUCK		BATTERY						SB175* CONNECTOR	+ BATTERY CODE
MODEL	BATTERY COMPART.	VOLTS	CELLS/ PLATES	COVER	LEADS LENGTH	POSITION	GAUGE		
W40XT	7.8"	24	12/5	YES	20"	B	2	SB175	R
W45XT	8.1"	12	6/13	YES	20"	B	1/0	SB175 6328G1	L
W60XT	9.0"		6/13						A
W60XT	13.4"		6/25						B
W/B60-80XT	9.0"	24	12/7	YES	20"	B	1/0	SB 175 6329G1	P
W/B/CA 60-80XT2	13.4"		12/13						C
T5XT	13.5"	24	12/13	YES	20"	B	1/0	SB 175 6329G1	C
W20-30XTC	13.86"	12	6/21	YES	20"	B	2	6328G1	T
W20-40XTC	13.86"	24	12/24					6329G1	U
W20-30XTA	8.12"	12	6/13					6328G1	V
		24	12/7					6329G1	W
W20-30XTA	13.5"	12	6/19-21					6328G1	X
		24	12/13					6329G1	U
W20-40XTA	13.5"	24	12/13					6329G1	U
W20XTR	8.1"	12	6/13					6328G1	V
W20-30XTR	13.5"	12	6/19-21					6328G1	X
		24	12/13					6329G1	U

+ See Battery Pages.

* SB175 Battery Connector requires a disconnect handle (Anderson 995G1) for OSHA Compliance.

Subject to Change Without Notice		Replaces 02/15/01	PAGE E-10.11 Effective 12/01/02
----------------------------------	--	----------------------	---------------------------------------




HYSTER COMPANY PRICE LIST	STANDARD BATTERY SPECIFICATIONS CLASS II PRODUCT
--	---

TRUCK		BATTERY						SB* CONNECTOR	+ BATTERY CODE
MODEL	BATTERY COMPART.	VOLTS	CELLS/ PLATES	COVER	LENGTH	POSITION	GAUGE		
R30XMS2	13.5"	24	12/15	NO	16"	B	2	SB 175 6328G1	K
R30XM2/XMA2 R30XMF2	14.5"	24	12/15	NO	16"	B	1/0	SB 350 6322G1	F
R30XM2/XMA2 R30XMF2	14.5"	36	18/11	NO	16"	B	1/0	SB 350 6329G1	G
N30XMR2 N50XMA2	12.6"	24	12/15	NO	16"	B	3/0	SB350 6322G1	M
N30-40XMR2 N50XMA2 N25XMDR2	14.6"	24	12/17					SB 350 6322G1	F
	14.6"	36	18/11					SB350 6320G1	G
N40XMR2 N50XMA2 N25XMDR2	16.6"	24	12/19					SB 350 6322G1	E
N40-45XMR2 N50XMA2 N25-30XMDR2		36	18/13					SB 350 6320G1	H
N45XMR2 N30XMDR2 N45XMR N30XMXDR	16.6" 18.8" 21.1"	36	18/15 18/17					SB 350 63201G	H D J
V30XMU	21.65"	48	24/13	NO	30"	AB		SB 350	N
V35XMU	27.87"	72	36/11	NO	30"	AB		SB 350	Y
V40XMU	34.17"	72	36/13-15	NO	30"	AB		SB 350	S

+ See Battery Pages.

* SB 350 Battery Connector requires a disconnect handle (Anderson 919G1 or Brad Harrison Hyster Part No. 240483) for OSHA Compliance. The SB175 Battery Connector requires an Anderson disconnect handle 995G1.

Subject to Change Without Notice		Replaces 02/15/01	PAGE E-10.10 Effective 12/01/02
----------------------------------	--	----------------------	---------------------------------------



HYSTER COMPANY

PRICE LIST

EXIDE BATTERIES CLASS II AND III PRODUCT

EXIDE					
VOLTS	BATTERY CODE†	TYPE	(6 HOURS) A.H. CAP.	(6 HOURS) K.W.H. CAP.	WEIGHT LBS.
12	V	6E75-13 ‡	450	5.2	441
	L-V	6-E85-13 ‡	510	5.9	477
	V	6E100-13 ‡	600	7.0	482
	V	6E125-13 ‡	750	8.6	640
	A	6-E155W-13 ‡	930	10.7	718
	X	6E75-19 ‡	675	7.8	640
	X	6E75-21 ‡	750	8.7	708
	X	6E85-21 ‡	850	9.9	771
	B	6-E85-25 ‡	1020	11.9	918
	B	6-E100-25 ‡	1200	13.9	927
	B	6-E110W-25 ‡	1320	15.3	983
24	R	12-E85-5 ‡	170	4.0	348
	R	12E100-5 ‡	200	4.7	351
	W-P	12E85-7 ‡	255	5.9	528
	W-P	12E100-7 ‡	300	7.0	533
	W	12E110W-7 ‡	330	7.7	575
	P	12-E155W-7 ‡	465	10.8	928
	U	12E75-13 ‡	450	10.4	892
	U	12E85-13 ‡	510	11.9	971
	C	12E125-13 ‡	750	17.4	1302
	C	12-E140-13 ‡	840	19.4	1432
	K	12-E100-15	700	16.2	1134
	K	12-E110W-15	770	17.9	1203
	M	12-E140-15	980	22.70	1651
	M	12-E125-15	875	20.3	1501
	M	12-E155W-15	1085	25.1	1684
	F	12-E140-17	1120	25.9	1871
	F	12-E125-17	1000	23.2	1701
	F	12-E155-17	1240	28.9	1908
	E	12-E125-19	1125	26.0	1900
	E	12-E140-19	1260	29.2	2090
	E	12-E155W-19	1395	32.3	2132
36	G	18-E125-11	625	21.8	1674
	G	18-E155W-11	775	27.0	1878
	G	18-E140-11	700	24.30	1841
	D	18-E155W-15	1085	37.6	2568
	D	18-E140-15	980	34.0	2518
	J	18-E140-17	1120	38.9	2852
	J	18-E125-17	1000	34.7	2593
	H	18-E125-13	750	26.1	1984
	H	18-E140-13	840	29.2	2182
48	H	18-E155W-13	930	32.2	2226
	N	24-E125-13	750	35.0	2688
	N	24-E140-13	840	38.9	2957
	N	24-E120S-13	720	-	2957
72	N	24-E155-13	930	-	3365
	S*	36-E140-13	840	-	4364
		36-E155-13	930	-	4452
		36-E125-13	750	-	3965
	Y**	36-E125-11	625	-	3520
		36-E140-11	700	-	3682
		36-E155-11	775	-	3875
		36-E120S-11	690	-	3682

‡ Requires covered battery.


*Must include 2 fork pockets.

**Must include 2 fork pockets and rear tray curvature.

Subject to Change Without Notice

Replaces
02/15/01

PAGE E-10.12
Effective
12/01/02



HYSTER COMPANY

PRICE LIST

GNB

BATTERIES

CLASS II AND III

PRODUCT

GNB

VOLTS	BATTERY CODE†	TYPE	(6 HOURS) A.H. CAP.	(6 HOURS) K.W.H. CAP.	WEIGHT LBS.
12	L	6-100A-11 ⊕	500	5.9	530
	L-V	6-85C-13 ‡	510	5.95	507
	T-V-A	6-100A-13 ‡ ⊕	600	7.1	630
	V-A	6-125C-13 ‡	750	8.8	709
	A	6-130C-13	780	9.2	725
	X	6-100A-19 ⊕	900	10.6	865
	T-X	6-85C-21 ‡	850	10.0	830
	B	6-100C-25	1200	13.9	1128
24	R	12-85C-5	170	4.0	405
	R	12-90A-5 ⊕	180	4.2	525
	P-W	12-85C-7 ‡	255	6.0	562
	W	12-125C-7	375	8.8	801
	C	12-100A-11 ⊕	500	11.8	1050
	P	12-50A-13 ⊕	300	7.1	700
	C	12-130C-13	780	18.3	1417
	U-C	12-85C-13 ‡	510	11.9	962
	U	12-100A-13 ‡	600	14.1	1180
	C	12-125C-13 ‡	750	17.5	1378
	K	12-85C-15	595	13.85	1100
	K	12-95C-15	665	15.48	1150
	M	12-125C-15	875	20.4	1583
	F-E	12-125C-17	1000	23.4	1784
	F	12-130C-15	910	21.2	1622
	E	12-125C-19	1125	21.9	1971
	M-F	12-50A-30 ⊕	700	16.5	1600
36	G	18-125C-11	625	21.9	1711
	G	18-130C-11	650	22.9	1764
	H	18-125C-13	750	26.3	2057
	H	18-130C-13	780	27.5	2129
	D	18-125C-15	875	30.7	2250
	J	18-125C-17	1000	35.1	2679
	H	18-130C-13	780	27.5	2030
	J	18-130C-17	1040	36.7	2760
	G	18-50A-22 ⊕	500	17.6	1780
	D	18-50A-30 ⊕	700	24.7	2310
	J	18-50A-34 ⊕	800	28.2	2630
48	N	24-125C-13	750	--	?
72	Y**	36-125C-11	625	?	?
	S*	36-125C-15	875	?	?

‡ Requires covered battery.

⊕ Maintenance Free Battery


* Must include 2 fork pockets.

** Must include 2 fork pockets and rear tray curvature.

Subject to Change Without Notice

Replaces
02/15/01

PAGE E-10.13
Effective
12/01/02



HYSTER COMPANY

PRICE LIST

EXIDE/GNB CHARGERS CLASS II AND III PRODUCT

EXIDE

VOLTS	BATTERY TYPE	A. H. RATING UP TO 8 HOURS	VOLTS	PHASE	WEIGHT LBS.
12	D3-6-550B	330-550	208/240/480	3	178
	D3-6-680B	408-680	208/240/480	3	178
	D3-6-850B	510-850	"	3	206
	D3-6-1050B	630-1050	"	3	206
24	SSC12-550	550-16 Hours	-	1	73
	D3-12-550	330-550	208/240/480	3	219
	D3-12-850	510-8500	"	3	263
	D3-12-1050	630-1050	"	3	263
	D3-12-1400	840-1400	"	3	286
36	D3-18-850	510-850	208/240/480	3	289
	D3-18-950	570-950	"	3	289
	D3-18-1200	720-1200	"	3	368
	D3-18-1400	840-1400	"	3	368
48	W3-24-865	865	"	3	369
	D3E-24-850	850	"	3	
72	WH3-36-850	850	"	3	---
	D3E-36-1050	1050	480 Only	3	---


GNB

12	CHP100-6-600TIU #	600	208/240/480/600	3	
	FER100-6-600T1	600	"	3	236
	FER100-6-750T1	750	"	3	250
	CHP100-6-965TIU	965	"	3	
	FER100-6-1050T1	1050	"	3	300
	FER100-6-1200T1	1200	"	3	320
	SCR100-6-600T1 #	600	"	3	190
24	CHP100-12-475TIU #	475	"	3	
	CHP100-12-600TIU #	600	"	3	
	CHP100-12-750TIU #	750	"	3	
	FER100-12-180S1	180	"	1	110
	FER100-12-260S1	260	"	1	170
	FER100-12-380T1	380	"	3	176
	FER100-12-600T1	600	"	3	300
	FER100-12-750T	750	"	3	320
	FER100-12-865T1	865	"	3	345
	FER100-12-1050T1	1050	"	3	380
	FER100-12-1200T1	1200	"	3	410
	SCR100-12-600T1 #	600	"	3	215
36	CHP100-18-600TIU #	600	"	3	
	CHP100-18-750TIU #	750	"	3	
	CHP100-18-865TIU #	865	"	3	
	FER100-18-750T1	750	208/240/480/600	3	345
	FER100-18-865T1	865	"	3	375
	FER100-18-965T1	965	"	3	400
	FER100-18-1050T1	1050	"	3	410

Subject to Change Without Notice

Replaces
02/15/01

PAGE E-10.14
Effective
12/01/02



HYSTER COMPANY
PRICE LIST

**GNB
CHARGERS
CLASS II AND III
PRODUCT**

GNB (continued)

VOLTS	BATTERY TYPE	A. H. RATING UP TO 8 HOURS	VOLTS	PHASE	WEIGHT LBS.
48	SCR100-24-750TI	750	"	3	330
	SCR100-24-600TI	600	"	3	256
72	SCR100-36-600-TI	600	"	3	---
	SCR100-36-865-TI	865	"	3	---

⊕ For Maintenance Free Batteries