



W25ZA₂ 8" Battery Compartment High Lift Sheets



CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
EQUIPPED WITH 42" CLASS II FORKS
CAPACITIES BASED UPON 9" X 4" POLY DRIVE TIRE, SINGLE POLY LOAD WHEEL

24 Volt 8.0" Battery Compartment Minimum Battery Weight - 310 LBS.

OEC/ID	OALH	MFH	CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
			CARRIAGE	HANG-ON SS	CARRIAGE		HANG-ON SIDE SHIFTER	
			LOAD	LOAD	LIFT HEIGHT	LOAD	LIFT HEIGHT	LOAD
2-Stage								
37"	72.0	104.0	2500	2300	130.0	2500	130.0	2300
	83.0	126.0	2500	2300	130.0	2500	130.0	2300
	87.0	130.0	2500	2300	130.0	2500	130.0	2300
	92.0	144.0	2200	2000	130.0	2500	130.0	2300
	95.0	150.0	2000	1800	130.0	2500	130.0	2300
39"	72.0	104.0	2500	2300	130.0	2500	130.0	2300
	83.0	126.0	2500	2300	130.0	2500	130.0	2300
	87.0	130.0	2500	2300	130.0	2500	130.0	2300
	92.0	144.0	2200	2000	130.0	2500	130.0	2300
	95.0	150.0	2000	1800	130.0	2500	130.0	2300
42"	72.0	104.0	2500	2300	130.0	2500	130.0	2300
	83.0	126.0	2500	2300	130.0	2500	130.0	2300
	87.0	130.0	2500	2300	130.0	2500	130.0	2300
	92.0	144.0	2200	2000	130.0	2500	130.0	2300
	95.0	150.0	2000	1800	130.0	2500	130.0	2300
49"	72.0	104.0	2500	2300	130.0	2500	130.0	2300
	83.0	126.0	2500	2300	130.0	2500	130.0	2300
	87.0	130.0	2500	2300	130.0	2500	130.0	2300
	92.0	144.0	2200	2000	130.0	2500	130.0	2300
	95.0	150.0	2000	1800	130.0	2500	130.0	2300

Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration.