



E100XL3S HIGHLIFT SHEETS

HYSTER®

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER EQUIPPED WITH 42" FORKS & STANDARD TIRES

		M.F.H.	CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
			CARRIAGE	SIDESHIFT	LIFT HEIGHT	CARRIAGE	LIFT HEIGHT	SIDESHIFT
E100XL₃S 39" Battery Box	2-Stage LFL 8 Deg Back Tilt Standard Tread	112	10,000	9,800	112	10,000	112	9,800
		135	10,000	9,750	135	10,000	135	9,750
		159	10,000	9,750	159	10,000	159	9,750
		187 *	10,000	9,650	187	10,000	187	9,650
		194	9,900	9,600	187	10,000	187	9,650
	2-Stage FFL 8 Deg Back Tilt Standard Tread	112	10,000	9,750	112	10,000	112	9,750
		135	10,000	9,750	135	10,000	135	9,750
		167	10,000	9,700	167	10,000	167	9,700
		194	9,900	9,550	187	10,000	187	9,650
		218	9,600	9,250	187	10,000	187	9,600
	3-Stage FFL 6 Deg Back Tilt Wide Tread	163	10,000	9,600	163	10,000	163	9,600
		185	10,000	9,550	185	10,000	185	9,550
		196	9,850	9,450	185	10,000	185	9,550
		208	9,750	9,300	185	10,000	185	9,550
		226	9,550	9,100	185	10,000	185	9,500

RATED VERSION 0112.00

* Highest Non-highlift Mast Rated at Full Capacity

Contact appropriate Applications Engineer for capacity with load centers or configurations other than those shown above.

Actual mast dimensions may vary slightly from nominal dimensions stated in price book. The designed **Overall Lowered Height** is stated to the next higher full inch, and **Maximum Fork Height** is stated to the next lower full inch, to allow for manufacturing tolerances.

High lift masts are masts which because of their type or lift height, require capacity reduction and/or back tilt restriction. In the case of this model, any fork height greater than 187" (4 750 mm) is a high lift.

HYSTER COMPANY * 1400 SULLIVAN DRIVE * GREENVILLE, NC 27834