



E120XL3 HIGHLIFT SHEETS

HYSTER®

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER EQUIPPED WITH 42" FORKS & STANDARD TIRES

		M.F.H.	CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
			CARRIAGE	SIDESHIFT	LIFT HEIGHT	CARRIAGE	LIFT HEIGHT	SIDESHIFT
E120XL ₃	2-Stage LFL 8 Deg Back Tilt Standard Tread	112	12,000	11,700	112	12,000	112	11,700
		135	12,000	11,650	135	12,000	135	11,650
		159	12,000	11,600	159	12,000	159	11,600
		187 *	12,000	11,550	187	12,000	187	11,550
		194	11,900	11,500	187	12,000	187	11,550
	2-Stage FFL 8 Deg Back Tilt Standard Tread	112	12,000	11,700	112	12,000	112	11,700
		135	12,000	11,650	135	12,000	135	11,650
		167	12,000	11,650	167	12,000	167	11,650
		194	11,900	11,500	187	12,000	187	11,600
		218	11,650	11,200	187	12,000	187	11,550
	3-Stage FFL 6 Deg Back Tilt Wide Tread	163	12,000	11,450	163	12,000	163	11,450
		185	12,000	11,450	185	12,000	185	11,450
		196	11,850	11,300	185	12,000	185	11,400
		208	11,750	11,150	185	12,000	185	11,400
		226	11,550	10,950	185	12,000	185	11,350

RATED VERSION 0112.00

* Highest Non-highlift Mast Rated at Full Capacity

Contact appropriate Applications Engineer for capacity with load centers or configurations other than those shown above.

Actual mast dimensions may vary slightly from nominal dimensions stated in price book. The designed **Overall Lowered Height** is stated to the next higher full inch, and **Maximum Fork Height** is stated to the next lower full inch, to allow for manufacturing tolerances.

High lift masts are masts which because of their type or lift height, require capacity reduction and/or back tilt restriction. In the case of this model, any fork height greater than 187" (4 750 mm) is a high lift.

HYSTER COMPANY * 1400 SULLIVAN DRIVE * GREENVILLE, NC 27834