



E60Z HIGHLIFT SHEETS 33" Battery Compartment

HYSTER®

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
EQUIPPED WITH 42" FORKS & STANDARD TIRES
33" BATTERY COMPARTMENT

		MFH	OALH	CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
				CARRIAGE	INTEGRAL SIDESHIFT	LIFT HEIGHT	CARRIAGE	LIFT HEIGHT	INTEGRAL SIDESHIFT
E60Z-33 Standard Tread	2stg LFL 8 Deg Back Tilt	114.0	78.0	6000	6000	114.0	6000	114.0	6000
		126.0	84.0	6000	6000	126.0	6000	126.0	6000
		146.0	94.0	6000	6000	146.0	6000	146.0	6000
		165.0	108.0	6000	5800	165.0	6000	142.3	6000
		185.0	118.0	5750	5550	166.0	6000	185.0	5550
	2stg FFL 8 Deg Back Tilt	114.0	78.0	6000	5850	114.0	6000	114.0	5850
		126.0	84.0	6000	5800	126.0	6000	126.0	5800
		146.0	94.0	6000	5800	146.0	6000	146.0	5800
		165.0	106.0	6000	5800	164.0	6000	165.0	5800
		185.0	116.0	5800	5600	171.5	6000	169.6	5750
	3stg FFL 5 Deg Back Tilt	164.0	76.0	6000	5750	164.0	6000	164.0	5750
		181.0	82.0	5850	5600	169.0	6000	164.0	5750
		193.0	88.0	5750	5500	167.0	6000	169.8	5700
		211.0	94.0	5600	5350	164.0	6000	167.5	5700
		229.0	102.0	4650	4700	169.0	5950	164.0	5700
	4stg FFL 4 Deg Back Tilt	240.0	84.0	3400	3400	199.0	5000	203.7	4800
		252.0	88.0	3050	3050	200.0	4950	205.0	4800
		264.0	92.0	2700	2700	202.0	4900	204.7	4800
		276.0	96.0	2400	2400	204.0	4850	205.7	4800
		288.0	100.0	2150	2100	204.9	4850	206.7	4750
E60Z-33 Wide Tread*	3stg FFL 5 Deg Back Tilt	229.0	102.0	5400	5150	169.3	5950	164.2	5700
		240.0	84.0	4250	4300	219.5	5000	225.4	4800
	4stg FFL 4 Deg Back Tilt	252.0	88.0	3900	3900	220.7	4950	225.6	4800
		264.0	92.0	3550	3550	223.8	4900	226.4	4800
		276.0	96.0	3250	3250	225.8	4850	227.4	4800
		288.0	100.0	2950	2950	225.5	4850	228.4	4750

RATED VERSION V0112.04 (January 2003)

*Wide Tread listed for Lift Heights where capacity is dependant on Tread Width.

Contact Application Engineering if you have questions about the information above, or about a specific truck configuration.

Actual mast dimensions may vary slightly from nominal dimensions stated in price book. The Overall Lowered Height (OALH) is stated to the next higher full inch and Maximum Fork Height (MFH) is stated to the next lower full inch, to allow for manufacturing tolerances.

High Lift masts are mast which because of their type or lift height, require capacity reduction and/or back tilt restriction.

Any E60-650XM2 2-stg LFL and FFL mast with fork height greater than 165" is considered a high lift.

Any E60-650XM2 3-stg FFL mast with fork height greater than 164" is considered a high lift.

HYSTER COMPANY * 1400 SULLIVAN DRIVE * GREENVILLE, NC 27834