



E65Z HIGHLIFT SHEETS 40" Battery Compartment

HYSTER®

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
EQUIPPED WITH 42" FORKS & STANDARD TIRES
40" BATTERY COMPARTMENT

		MFH	OALH	CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
				CARRIAGE	INTEGRAL SIDESHIFT	LIFT HEIGHT	CARRIAGE	LIFT HEIGHT	INTEGRAL SIDESHIFT
E65Z-33 Standard Tread	2stg LFL 8 Deg Back Tilt	114.0	78.0	6500	6350	114.0	6500	114.0	6350
		126.0	84.0	6500	6350	126.0	6500	126.0	6350
		146.0	94.0	6500	6300	146.0	6500	146.0	6300
		165.0	108.0	6500	6250	165.0	6500	165.0	6250
		185.0	118.0	6300	6100	169.6	6500	164.2	6250
	2stg FFL 8 Deg Back Tilt	114.0	78.0	6500	6450	114.0	6500	114.0	6450
		126.0	84.0	6500	6400	126.0	6500	126.0	6400
		146.0	94.0	6500	6400	146.0	6500	146.0	6400
		165.0	106.0	6500	6400	164.0	6500	164.0	6400
		185.0	116.0	6300	6200	179.7	6500	169.6	6350
	3stg FFL 5 Deg Back Tilt	164.0	76.0	6500	6200	164.0	6500	164.0	6200
		182.0	82.0	6350	6100	167.0	6500	167.0	6200
		193.0	88.0	6250	5950	164.2	6500	164.0	6200
		211.0	94.0	5850	5750	164.2	6500	169.6	6150
		229.0	102.0	4800	4800	167.3	6450	167.3	6150
	4stg FFL 4 Deg Back Tilt	240.0	84.0	3400	3400	196.0	5000	200.8	4800
		252.0	88.0	3050	3050	197.0	4950	201.0	4800
		264.0	92.0	2750	2750	199.2	4900	201.8	4800
		276.0	96.0	2450	2450	201.2	4850	201.8	4800
		288.0	100.0	2200	2150	202.0	4850	203.8	4750
E65Z-33 Wide Tread*	3stg FFL 5 Deg Back Tilt	211.0	94.0	6050	5750	164.0	6500	169.6	6150
		229.0	102.0	5850	5550	167.3	6450	167.3	6150
	4stg FFL 4 Deg Back Tilt	240.0	84.0	4250	4250	217.5	5000	223.4	4800
		252.0	88.0	3900	3900	219.0	4950	223.6	4800
		264.0	92.0	3600	3600	221.8	4900	224.4	4800
		276.0	96.0	3300	3300	223.9	4850	225.4	4800
		288.0	100.0	3050	3000	224.6	4850	226.4	4750

RATED VERSION V0112.04 (January 2003)

*Wide Tread listed for Lift Heights where capacity is dependant on Tread Width.

Contact Application Engineering if you have questions about the information above, or about a specific truck configuration.

Actual mast dimensions may vary slightly from nominal dimensions stated in price book. The Overall Lowered Height (OALH) is stated to the next higher full inch and Maximum Fork Height (MFH) is stated to the next lower full inch, to allow for manufacturing tolerances.

High Lift masts are mast which because of their type or lift height, require capacity reduction and/or back tilt restriction.

Any E60-650XM2 2-stg LFL and FFL mast with fork height greater than 165" is considered a high lift.

Any E60-650XM2 3-stg FFL mast with fork height greater than 164" is considered a high lift.

HYSTER COMPANY * 1400 SULLIVAN DRIVE * GREENVILLE, NC 27834