



H155XL2 HIGHLIFT SHEETS

HYSTER®

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
EQUIPPED WITH 42" FORKS AND STANDARD TIRES

H155XL ₂	MAST TYPE	MFH (in.)	CAPACITY @ MFH		LIFT HEIGHT @ MAXIMUM CAPACITY			
			With Carriage (lbs.)	With Integral Sideshift (lbs.)	With Carriage		With Integral Sideshift	
					LIFT HEIGHT	CAPACITY	LIFT	CAPACITY
	2-STG LFL 10 Deg Back Tilt	212.5#	15,450	14,400	212.5	15,450	212.5	14,400
		236.0	15,000	13,950	212.5	15,300	212.5	14,600
		252.0	14,650	13,550	212.5	15,100	212.5	14,400
		264.0**	14,400	13,300	212.5	15,050	212.5	14,350
	3-STG FFL 6 Deg Back Tilt	210.6	14,350	13,650	210.6	14,350	210.6	13,650
		220.5	14,300	13,500	220.5	14,300	212.5	13,600
		240.2	14,200	13,150	240.2	14,200	212.5	13,450
		259.8	13,950	12,650	259.8	13,950	212.5	13,250
		271.7**	13,500	12,400	212.5	13,800	212.5	13,100

RATED VERSION V0005.01

Highest non-high lift mast rated at full capacity and not requiring restricted back tilt with standard carriage.

** REQUIRES SPECIAL TILT SPEED RESTRICTION

* May be available at reduced capacity; contact Applications Engineering

Maximum capacity and Lift Height at Maximum capacity with sideshifter may be influenced by channel overlap and dynamic loading factors. Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration.

High lift masts are masts which because of their type or lift height, require capacity reduction and/or back tilt restriction. In the case of this model, any fork height greater than 212.5" (5 400 mm) is a high lift.

HYSTER COMPANY * 1400 SULLIVAN DRIVE * GREENVILLE, NC 27834