



H60FT HIGHLIFT SHEETS



CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
EQUIPPED WITH 42" FORKS & STANDARD PNEUMATIC TIRES
SIDESHIFT RATINGS WITH INTEGRAL SIDESHIFTER

		MFH	OALH	CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
				CARRIAGE	SIDESHIFT	LIFT HEIGHT	CARRIAGE	LIFT HEIGHT	SIDESHIFT
H60FT Standard Tread	2stg LFL 6 Deg Back Tilt	114.0	83.0	6000	5850	114.0	6000	114.0	5850
		126.0	89.0	6000	5800	126.0	6000	126.0	5800
		150.0	105.0	6000	5800	150.0	6000	150.0	5800
		161.0	110.0	6000	5750	161.0	6000	161.0	5750
	2stg FFL 6 Deg Back Tilt	114.0	83.0	6000	5850	114.0	6000	114.0	5850
		122.0	87.0	6000	5800	122.0	6000	122.0	5800
		130.0	91.0	6000	5800	130.0	6000	130.0	5800
		142.0	97.0	6000	5800	142.0	6000	142.0	5800
	3stg FFL 6 Deg Back Tilt	170.0*	83.0	5950	5700	164.0	6000	164.0	5750
		181.0	87.0	5600	5600	164.0	6000	164.0	5750
		187.0	91.0	5300	5300	164.0	6000	164.0	5700
		193.0	93.0	4950	4950	164.0	6000	164.0	5700
		211.0	101.0	3950	3950	164.0	5950	164.0	5700
		217.0	103.0	3700	3700	164.0	5950	164.0	5650
H60FT Wide Tread	3stg FFL 6 Deg Back Tilt	170.0	83.0	5950	5700	164.0	6000	164.0	5750
		181.0	87.0	5800	5600	164.0	6000	164.0	5750
		187.0	91.0	5750	5500	164.0	6000	164.0	5700
		193.0	93.0	5650	5450	164.0	6000	164.0	5700
		211.0	101.0	5450	5200	164.0	5950	164.0	5700
		217.0	103.0	5150	5100	164.0	5950	164.0	5650
	4stg FFL	228.0	84.0	Contact Applications Engineering					
		240.0	87.0						
		252.0	91.0						
		264.0	95.0						

* Highest Non-High Lift Mast Rated at Full Capacity is 164.0/81.0 (not shown).

Wide Tread listed for Lift Heights where capacity is dependant on Tread Width.
Wide Tread is required with 4-Stage FFL Mast.

Actual mast dimensions may vary slightly from nominal dimensions stated in price book. The designed Overall Lowered Height (OALH) is stated to the next higher full inch, and Maximum Fork Height (MFH) is stated to the next lower full inch, to allow for manufacturing tolerances.

For capacity estimates for other truck configurations or for trucks with attachments, consult your copy of the Hyster HY-Rater truck rating software.
Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration.

HYSTER COMPANY * 1400 SULLIVAN DRIVE * GREENVILLE, NC 27834