



# H70XM HIGHLIFT SHEETS

**HYSTER®**

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER  
EQUIPPED WITH 48" FORKS & STANDARD BACK TILT  
USES STANDARD TREAD, SINGLE PNEUMATIC DRIVE TIRES AND PNEUMATIC STEER  
TIRES UNLESS OTHERWISE SPECIFIED

| H70XM | MAST TYPE                     | MFH<br>(in.) | CAPACITY @ MFH |              |                        |                        | LIFT HEIGHT @ MAXIMUM CAPACITY |          |              |          |                        |          |                        |          |
|-------|-------------------------------|--------------|----------------|--------------|------------------------|------------------------|--------------------------------|----------|--------------|----------|------------------------|----------|------------------------|----------|
|       |                               |              | 48" Carriage   | 60" Carriage | 48" Integral Sideshift | 60" Integral Sideshift | 48" Carriage                   |          | 60" Carriage |          | 48" Integral Sideshift |          | 60" Integral Sideshift |          |
|       |                               |              | (lbs.)         | (lbs.)       | (lbs.)                 | (lbs.)                 | LIFT                           | CAPACITY | LIFT         | CAPACITY | LIFT                   | CAPACITY | LIFT                   | CAPACITY |
|       |                               |              |                |              |                        |                        |                                |          |              |          |                        |          |                        |          |
|       | 2-STG LFL<br>12 Deg Back Tilt | 122.0        | 7,500          | 7,500        | 6,850                  | 6,700                  | 122.0                          | 7,500    | 122.0        | 7,500    | 122.0                  | 6,850    | 122.0                  | 6,700    |
|       |                               | 145.7        | 7,500          | 7,500        | 6,850                  | 6,700                  | 145.7                          | 7,500    | 145.7        | 7,500    | 145.7                  | 6,850    | 145.7                  | 6,700    |
|       |                               | 169.3        | 7,500          | 7,500        | 6,800                  | 6,650                  | 169.3                          | 7,500    | 169.3        | 7,500    | 169.3                  | 6,800    | 169.3                  | 6,650    |
|       | 2-STG FFL<br>12 Deg Back Tilt | 122.0        | 7,300          | *            | 6,600                  | 6,500                  | 122.0                          | 7,300    | 122.0        | *        | 122.0                  | 6,600    | 122.0                  | 6,500    |
|       |                               | 145.7        | 7,250          | *            | 6,550                  | 6,450                  | 145.7                          | 7,250    | 145.7        | *        | 145.7                  | 6,550    | 145.7                  | 6,450    |
|       | 3-STG FFL<br>6 Deg Back Tilt  | 173.8        | 7,000          | 7,000        | 6,450                  | 6,300                  | 173.8                          | 7,000    | 173.8        | 7,000    | 167.9                  | 7,000    | 162.0                  | 7,000    |
|       |                               | 185.6        | 6,850          | 6,850        | 6,300                  | 6,200                  | 173.8                          | 7,000    | 173.8        | 7,000    | 167.9                  | 7,000    | 162.0                  | 7,000    |
|       |                               | 194.9        | 6,750          | 6,750        | 6,200                  | 6,100                  | 173.8                          | 7,000    | 173.8        | 7,000    | 167.9                  | 7,000    | 162.0                  | 7,000    |
|       |                               | 206.7        | 6,600          | 6,600        | 6,050                  | 5,950                  | 173.8                          | 7,000    | 173.8        | 7,000    | 167.9                  | 7,000    | 162.0                  | 7,000    |
|       |                               | 218.5        | 6,500          | 6,450        | 5,900                  | 5,800                  | 173.8                          | 7,000    | 173.8        | 7,000    | 167.9                  | 7,000    | 162.0                  | 7,000    |

RATED VERSION V0005.01

\* May be available at reduced capacity; contact Applications Engineering

Maximum capacity and Lift Height at Maximum capacity with sideshifter may be influenced by channel overlap and dynamic loading factors. Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration.

High lift masts are masts which because of their type or lift height, require capacity reduction and/or back tilt restriction. In the case of this model, any fork height greater than 174" (4 420 mm) is a high lift.

HYSTER COMPANY \* 1400 SULLIVAN DRIVE \* GREENVILLE, NC 27834