



H90XMS HIGHLIFT SHEETS

HYSTER®

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
EQUIPPED WITH 48" FORKS & STANDARD BACK TILT
USES STANDARD TREAD, SINGLE PNEUMATIC DRIVE TIRES AND PNEUMATIC STEER
TIRES UNLESS OTHERWISE SPECIFIED

H90XMS	MAST TYPE	MFH	CAPACITY @ MFH				LIFT HEIGHT @ MAXIMUM CAPACITY							
			48" Carriage	60" Carriage	48" Integral Sideshift	60" Integral Sideshift	48" Carriage		60" Carriage		48" Integral Sideshift		60" Integral Sideshift	
			(in.)	(lbs.)	(lbs.)	(lbs.)	LIFT	CAPACITY	LIFT	CAPACITY	LIFT	CAPACITY	LIFT	CAPACITY
	2-STG LFL 12 Deg Back Tilt	122.0	9,000	9,000	8,250	8,100	122.0	9,000	122.0	9,000	122.0	8,250	122.0	8,100
		145.7	9,000	9,000	8,200	8,050	145.7	9,000	145.7	9,000	145.7	8,200	145.7	8,050
		169.3	9,000	9,000	8,200	8,050	169.3	9,000	169.3	9,000	169.3	8,200	169.3	8,050
	2-STG FFL 12 Deg Back Tilt	122.0	8,750	*	7,950	7,800	122.0	8,750	122.0	*	122.0	7,950	122.0	7,800
		145.7	8,750	*	7,950	7,800	145.7	8,700	145.7	*	145.7	7,950	145.7	7,800
	3-STG FFL 6 Deg Back Tilt	173.8	8,500	8,500	7,800	7,700	173.8	8,500	173.8	8,500	156.1	8,500	150.2	8,500
		185.6	8,350	8,350	7,700	7,550	173.8	8,500	173.8	8,500	156.1	8,500	150.2	8,500
		194.9	8,250	8,250	7,550	7,400	173.8	8,500	173.8	8,500	156.1	8,500	150.2	8,500
		206.7	8,100	8,050	7,400	7,250	173.8	8,500	173.8	8,500	156.1	8,500	150.2	8,500
		218.5	7,900	7,900	7,250	7,100	173.8	8,500	173.8	8,500	156.1	8,500	150.2	8,400

RATED VERSION V0005.01

* May be available at reduced capacity; contact Applications Engineering

Maximum capacity and Lift Height at Maximum capacity with sideshifter may be influenced by channel overlap and dynamic loading factors. Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration.

High lift masts are masts which because of their type or lift height, require capacity reduction and/or back tilt restriction. In the case of this model, any fork height greater than 174" (4 420 mm) is a high lift.

HYSTER COMPANY * 1400 SULLIVAN DRIVE * GREENVILLE, NC 27834