



E30XN HIGHLIFT SHEETS



**CAPACITY IN POUNDS @ 24 INCH LOAD CENTER; MINIMUM BATTERY WEIGHT=1850 LBS
EQUIPPED WITH 42" FORKS**

			OALH	M.F.H.	CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
					36" WIDE CARRIAGE	INTEGRAL SIDESHIFT	LIFT HEIGHT	36" WIDE CARRIAGE	LIFT HEIGHT	INTEGRAL SIDESHIFT
STANDARD TREAD	18 x 6 x 12.1 Smooth Rubber NM Rubber Lug	2-Stage LFL 5 ° Back Tilt	79	123	3,000	2,950	123	3000	123	2950
			82	127	3,000	2,950	127	3000	127	2950
			84	131	3,000	2,950	131	3000	131	2950
		2-Stage FFL 5 ° Back Tilt	82	126	3,000	2,950	126	3000	126	2950
			84	130	3,000	2,950	130	3000	130	2950
			88	138	3,000	2,950	138	3000	138	2950
		3-Stage FFL 5 ° Back Tilt	80	181	2,900	2,850	169	3000	169	2900
			82	187	2,800	2,800	169	3000	169	2900
			84	192	2,600	2,600	169	3000	169	2900
			88	198	2,400	2,400	169	3000	169	2900
			94	216	1,850	1,800	169	3000	169	2900
			79	123	3,000	2,950	123	3000	123	2950
INTERMEDIATE TREAD	18 x 7 x 12.1 Smooth Rubber NM Rubber Lug	2-Stage LFL 5 ° Back Tilt	82	127	3,000	2,950	127	3000	127	2950
			84	131	3,000	2,950	131	3000	131	2950
			82	126	3,000	2,950	126	3000	126	2950
		2-Stage FFL 5 ° Back Tilt	84	130	3,000	2,950	130	3000	130	2950
			88	138	3,000	2,950	138	3000	138	2950
			80	181	2,900	2,850	169	3000	169	2900
		3-Stage FFL 5 ° Back Tilt	82	187	2,850	2,800	169	3000	169	2900
			84	192	2,800	2,750	169	3000	169	2900
			88	198	2,800	2,700	169	3000	169	2900
			94	216	2,400	2,350	169	3000	169	2900
			79	123	3,000	2,950	123	3000	123	2950
			82	127	3,000	2,950	127	3000	127	2950
WIDE TREAD	18 x 6 x 12.1 Smooth Rubber NM Rubber Lug	2-Stage LFL 5 ° Back Tilt	84	131	3,000	2,950	131	3000	131	2950
			82	126	3,000	2,950	124	3000	126	2950
			84	130	3,000	2,950	130	3000	130	2950
		2-Stage FFL 5 ° Back Tilt	88	138	3,000	2,950	138	3000	138	2950
			80	181	2,900	2,850	169	3000	169	2900
			82	187	2,850	2,800	169	3000	169	2900
		3-Stage FFL 5 ° Back Tilt	84	192	2,800	2,750	169	3000	169	2900
			88	198	2,800	2,700	169	3000	169	2900
			94	216	2,650	2,550	169	3000	169	2900
			79	123	3,000	2,950	123	3000	123	2950
			82	127	3,000	2,950	127	3000	127	2950
			84	131	3,000	2,950	131	3000	131	2950
	18 x 7 x 12.1 Smooth Rubber NM Rubber Lug	2-Stage LFL 5 ° Back Tilt	82	126	3,000	2,950	126	3000	126	2950
			84	130	3,000	2,950	130	3000	130	2950
			88	138	3,000	2,950	138	3000	138	2950
		2-Stage FFL 5 ° Back Tilt	80	181	2,900	2,850	169	3000	169	2900
			82	187	2,850	2,800	169	3000	169	2900
			84	192	2,800	2,750	169	3000	169	2900
		3-Stage FFL 5 ° Back Tilt	88	198	2,800	2,700	169	3000	169	2900
			94	216	2,650	2,550	169	3000	169	2900
			79	123	3,000	2,950	123	3000	123	2950
			82	127	3,000	2,950	127	3000	127	2950
			84	131	3,000	2,950	131	3000	131	2950
			82	126	3,000	2,950	126	3000	126	2950

Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration

Actual mast dimensions may vary from the nominal dimensions stated in the price book. The Overall Lowered Height (OALH) is stated to the next higher full inch and Maximum Fork Height (MFH) is stated to the next lower full inch, to allow for manufacturing tolerances