



E35XN HIGHLIFT SHEETS



**CAPACITY IN POUNDS @ 24 INCH LOAD CENTER; MINIMUM BATTERY WEIGHT=1850 LBS
EQUIPPED WITH 42" FORKS**

			OALH	M.F.H.	CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
					36" WIDE CARRIAGE	INTEGRAL SIDESHIFT	LIFT HEIGHT	36" WIDE CARRIAGE	LIFT HEIGHT	INTEGRAL SIDESHIFT
STANDARD TREAD	18 x 6 x 12.1 Smooth Rubber NM Rubber Lug	2-Stage LFL 5 ° Back Tilt	79	123	3,500	3,400	123	3500	123	3400
			82	127	3,500	3,400	127	3500	127	3400
			84	131	3,500	3,400	131	3500	131	3400
		2-Stage FFL 5 ° Back Tilt	82	126	3,500	3,400	126	3500	126	3400
			84	130	3,500	3,400	130	3500	130	3400
			88	138	3,500	3,400	138	3500	138	3400
		3-Stage FFL 5 ° Back Tilt	80	181	3,100	3,100	157	3500	149	3350
			82	187	2,850	2,850	155	3500	149	3350
			84	192	2,600	2,600	155	3500	147	3350
			88	198	2,400	2,400	153	3500	147	3350
			94	216	1,800	1,800	149	3500	145	3300
			79	123	3,500	3,400	123	3500	123	3400
INTERMEDIATE TREAD	18 x 7 x 12.1 Smooth Rubber NM Rubber Lug	2-Stage LFL 5 ° Back Tilt	82	127	3,500	3,400	127	3500	127	3400
			84	131	3,500	3,400	131	3500	131	3400
			82	126	3,500	3,400	126	3500	126	3400
		2-Stage FFL 5 ° Back Tilt	84	130	3,500	3,400	126	3500	126	3400
			88	138	3,500	3,400	138	3500	138	3400
			80	181	3,300	3,200	157	3500	157	3350
		3-Stage FFL 5 ° Back Tilt	82	187	3,250	3,150	157	3500	157	3350
			84	192	3,250	3,100	157	3500	157	3350
			88	198	3,050	3,050	157	3500	157	3350
			94	216	2,400	2,400	157	3500	157	3300
			79	123	3,500	3,400	123	3500	123	3400
			82	127	3,500	3,400	127	3500	127	3400
WIDE TREAD	18 x 6 x 12.1 Smooth Rubber NM Rubber Lug	2-Stage LFL 5 ° Back Tilt	84	131	3,500	3,400	131	3500	131	3400
			82	126	3,500	3,400	126	3500	126	3400
			84	130	3,500	3,400	130	3500	130	3400
		2-Stage FFL 5 ° Back Tilt	88	138	3,500	3,400	138	3500	138	3400
			80	181	3,300	3,150	157	3500	149	3350
			82	187	3,250	3,150	155	3500	149	3350
		3-Stage FFL 5 ° Back Tilt	84	192	3,200	3,100	155	3500	147	3350
			88	198	3,200	3,050	153	3500	147	3350
			94	216	2,800	2,800	149	3500	145	3300
			79	123	3,500	3,400	123	3500	123	3400
			82	127	3,500	3,400	127	3500	127	3400
			84	131	3,500	3,400	131	3500	131	3400
	18 x 7 x 12.1 Smooth Rubber NM Rubber Lug	2-Stage LFL 5 ° Back Tilt	82	126	3,500	3,400	126	3500	126	3400
			84	130	3,500	3,400	130	3500	130	3400
			88	138	3,500	3,400	138	3500	138	3400
		2-Stage FFL 5 ° Back Tilt	80	181	3,300	3,200	157	3500	157	3350
			82	188	3,250	3,150	157	3500	157	3350
			84	192	3,250	3,100	157	3500	157	3350
		3-Stage FFL 5 ° Back Tilt	88	198	3,200	3,050	157	3500	157	3350
			94	216	3,000	2,900	157	3500	157	3300
			79	123	3,500	3,400	123	3500	123	3400
			82	127	3,500	3,400	127	3500	127	3400
			84	131	3,500	3,400	131	3500	131	3400
			82	126	3,500	3,400	126	3500	126	3400

Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration

Actual mast dimensions may vary from the nominal dimensions stated in the price book. The Overall Lowered Height (OALH) is stated to the next higher full inch and Maximum Fork Height (MFH) is stated to the next lower full inch, to allow for manufacturing tolerances