



H300-360HD₂ HIGHLIFT SHEETS



H300HD₂ MODEL

CAPACITY IN POUNDS @ 24, 36, & 48 INCH LOAD CENTERS
EQUIPPED WITH 72" & 96" FORKS & STANDARD TIRES

			MFH	OALH	CAPACITY @ MFH 24" L.C.					CAPACITY @ MFH 36" L.C.					CAPACITY @ MFH 48" L.C.				
					CARRIAGE	SIDESIFT	FORK POS.	APRON SSFP	DUAL SSFP	CARRIAGE	SIDESIFT	FORK POS.	APRON SSFP	DUAL SSFP	CARRIAGE	SIDESIFT	FORK POS.	APRON SSFP	DUAL SSFP
					147.0	144.0	30000	28900	30000	25000	24100	24900	24000	23400	21300	20600	21300	20500	20100
H300HD ₂	Standard	Forks 3.5x8x72"	2stg NFL 12 Deg Back Tilt	183.0	162.0	30000	28800	29900	28700	24800	23900	24800	23900	23300	21200	20500	21100	20400	20000
				212.0	176.0	29800	28600	29700	28600	24700	23800	24600	23700	23200	21100	20400	21000	20300	19900
				244.0	192.0	29600	28500	29600	28400	24600	23700	24500	23600	23100	21000	20200	20900	20200	19800
				173.0	121.0	27700	25900	27700	25800	23200	21800	23100	21700	NA	19900	18800	19800	18700	NA
				3stg FFL	196.0	129.0	27600	25700	25700	23000	21700	23000	21600	NA	19800	18700	19700	18700	NA
				10 Deg	236.0	142.0	26700	25000	26700	24900	22300	21000	22300	20900	NA	19200	18100	19100	18100
	Tread	Forks 3.5x8x96"	2stg NFL 12 Deg Back Tilt	275.0	156.0	25500	23800	25400	23700	21300	20000	21200	20000	NA	18300	17300	18200	17200	NA
				147.0	144.0	29600	28400	29500	28300	24500	23600	24400	23500	23000	20900	20200	20800	20100	19700
				183.0	162.0	29400	28200	29300	28100	24300	23400	24200	23300	22800	20800	20100	20700	20000	19600
				212.0	176.0	29200	28000	29200	28000	24200	23300	24100	23200	22700	20600	19900	20600	19900	19500
				244.0	192.0	29100	27900	29000	27800	24100	23200	24000	23100	22600	20500	19800	20500	19800	19400
				173.0	121.0	27200	25300	27100	25300	22700	21300	22600	21200	NA	19500	18400	19400	18300	NA
			3stg FFL	196.0	129.0	27000	25200	27000	25100	22600	21200	22500	21100	NA	19400	18300	19300	18200	NA
				236.0	142.0	26200	24400	26100	24300	21900	20600	21900	20500	NA	18800	17700	18700	17700	NA
				10 Deg	275.0	156.0	25000	23300	24900	22000	20800	22000	20900	NA	17900	16900	17800	16800	NA

WWRP web based revision 10.26

NOTE: DFSSFP carriage rated with 7 degree back tilt
* Highest Non-High Lift Mast Rated at Full Capacity
Wide Tread listed for Lift Heights where capacity is dependant on Tread Width.
Maximum capacity and Lift Height at Maximum capacity with sideshifter may be influenced by channel overlap and dynamic loading factors.
Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration.

H330HD₂ MODEL

CAPACITY IN POUNDS @ 24, 36, & 48 INCH LOAD CENTERS
EQUIPPED WITH 72" & 96" FORKS & STANDARD TIRES

				MFH	OALH	CAPACITY @ MFH 24" L.C.						CAPACITY @ MFH 36" L.C.						CAPACITY @ MFH 48" L.C.					
						CARRIAGE	SIDESIFT	FORK POS.	APRON SSFP	DUAL SSFP	CARRIAGE	SIDESIFT	FORK POS.	APRON SSFP	DUAL SSFP	CARRIAGE	SIDESIFT	FORK POS.	APRON SSFP	DUAL SSFP			
H330HD ₂	Standard	Forks 3.5x8x72"	2stg NFL 12 Deg Back Tilt	147.0	144.0	32700	31500	32700	31400	30500	27100	26200	27100	26100	25500	23100	22400	23100	22300	21900			
				183.0	162.0	32600	31300	32500	31200	30300	27000	26000	26900	26000	25400	23000	22300	23000	22200	21800			
				212.0	176.0	32400	31200	32300	31100	30100	26800	25900	26800	25800	25200	22900	22200	22900	22100	21700			
				244.0	192.0	32200	31000	32200	30900	29300	26700	25800	26600	25700	25100	22800	22100	22700	22000	21600			
				173.0	121.0	29800	28000	29900	27900	25000	23600	24900	23500	NA	21500	20300	21400	20300	NA				
				3stg FFL	196.0	129.0	29800	27900	27900	24900	23400	24800	23400	NA	21400	20200	21300	20200	NA				
	Tread	Forks 3.5x8x96"	2stg NFL 12 Deg Back Tilt	236.0	142.0	28900	27000	28900	27000	NA	24200	22800	24100	22700	NA	20700	19600	20700	19600	NA			
				275.0	156.0	27700	25800	27600	25800	NA	23100	21800	23100	21700	NA	19800	18800	19800	18700	NA			
				147.0	144.0	32100	30900	32100	30800	29900	26600	25700	26600	25600	25000	22700	22000	22700	21900	21500			
				183.0	162.0	32000	30700	31900	30700	29800	26500	25600	26400	25500	24900	22600	21900	22600	21800	21400			
				212.0	176.0	31800	30600	31800	30500	29600	26300	25400	26300	25400	24700	22500	21800	22400	21700	21300			
				244.0	192.0	31700	30400	31600	30300	29100	26200	25300	26200	25200	24600	22400	21600	22300	21600	21200			
			3stg FFL	173.0	121.0	29400	27400	29300	27400	NA	24500	23100	24500	23000	NA	21100	19900	21000	19900	NA			
				196.0	129.0	29200	27300	29200	27200	24400	23000	24400	22900	NA	21000	19800	20900	19800	NA				
				236.0	142.0	28400	26500	28300	26400	NA	23700	22300	23700	22200	NA	20300	19200	20300	19200	NA			
		10 Deg Back Tilt	275.0	156.0	27100	25300	27100	25300	NA	22700	21300	22600	21200	NA	19400	18400	19400	18300	NA				

WWRP web based revision 10.26

NOTE: DFSSFP carriage rated with 7 degree back tilt
* Highest Non-High Lift Mast Rated at Full Capacity
Wide Tread listed for Lift Heights where capacity is dependant on Tread Width.
Maximum capacity and Lift Height at Maximum capacity with sideshifter may be influenced by channel overlap and dynamic loading factors.
Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration.

H360HD₂ MODEL

CAPACITY IN POUNDS @ 24, 36, & 48 INCH LOAD CENTERS
EQUIPPED WITH 72" & 96" FORKS & STANDARD TIRES

			MFH	OALH	CAPACITY @ MFH 24" L.C.					CAPACITY @ MFH 36" L.C.					CAPACITY @ MFH 48" L.C.				
					CARRIAGE	SIDESIFT	FORK POS.	APRON SSFP	DUAL SSFP	CARRIAGE	SIDESIFT	FORK POS.	APRON SSFP	DUAL SSFP	CARRIAGE	SIDESIFT	FORK POS.	APRON SSFP	DUAL SSFP
					147.0	144.0	36000	34800	36000	29900	28900	29900	28900	28200	25500	24800	25500	24700	24200
H360HD ₂	Standard	Forks 3.5x8x72"	2stg NFL 12 Deg Back Tilt	183.0	162.0	36000	34600	35900	34600	29800	28800	29700	28700	28000	25400	24600	25400	24600	24100
				212.0	176.0	35800	34500	35700	34400	29700	28600	29600	28600	27900	25300	24500	25300	24500	24000
				244.0	192.0	35600	34300	35600	34300	29500	28500	29500	28500	27800	25200	24400	25100	24400	23900
				173.0	121.0	33900	31700	33800	31700	28300	26700	28200	26600	NA	23400	22100	23400	22100	NA
				3stg FFL	196.0	129.0	33700	31500	31500	28200	26600	28100	26500	NA	23400	22100	23400	22100	NA
				10 Deg	236.0	142.0	32800	30700	32800	27400	25900	27400	25800	NA	23400	21100	23400	21100	NA
	Tread	Forks 3.5x8x96"	2stg NFL 12 Deg Back Tilt	275.0	156.0	31500	29500	31400	29400	26300	24800	26300	24800	NA	22600	21200	22500	21400	NA
				147.0	144.0	35500	34200	35500	34100	29400	28500	29400	28400	27700	25100	24300	25100	24300	23800
				183.0	162.0	35400	34100	35300	34000	29300	28300	29300	28300	27600	25000	24200	25000	24200	23700
				212.0	176.0	35200	33900	35200	33800	29200	28200	29100	28100	27400	24900	24100	24800	24100	23600
				244.0	192.0	35100	33700	35000	33700	29000	28100	29000	28000	27300	24800	24000	24700	24000	23500
				173.0	121.0	33300	31200	33200	31100	27800	26200	27700	26200	NA	23000	21700	22900	21600	NA
			3stg FFL	196.0	129.0	33200	31000	33100	31000	27700	26100	27600	26100	NA	23000	21700	22800	21600	NA
				236.0	142.0	32300	30200	32200	30100	26900	25400	26900	25400	NA	23000	21700	22800	21600	NA
				10 Deg	275.0	156.0	31000	29000	30900	25900	24400	25800	24300	NA	22200	21000	22100	21000	NA

WWRP web based revision 10.26

NOTE: DFSSFP carriage rated with 7 degree back tilt
* Highest Non-High Lift Mast Rated at Full Capacity
Wide Tread listed for Lift Heights where capacity is dependant on Tread Width.
Maximum capacity and Lift Height at Maximum capacity with sideshifter may be influenced by channel overlap and dynamic loading factors.
Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration.