



E60XN - Standard Tread High Lift Sheets



CAPACITY IN POUNDS @ 24 INCH LOAD CENTER; MINIMUM BATTERY WEIGHT=2900 LBS
EQUIPPED WITH: 33" Battery Compartment & 42" FORKS

Tread Width	Tire Size	Mast	OALH	M.F.H.	CAPACITY @ MFH		LIFT HEIGHT	LIFT HEIGHT @ MAX CAPACITY		INTEGRAL SIDESHIFT
					38.5" WIDE CARRIAGE	INTEGRAL SIDESHIFT		38.5" WIDE CARRIAGE	LIFT HEIGHT	
STANDARD TREAD	21 x 8 x 15 Std cushion/Non-Marking Compound	2-Stage LFL 5 ° Back Tilt	83	118	6,000	5,850	118	6000	118	5850
			86	126	6,000	5,850	126	6000	126	5850
			88	130	6,000	5,800	130	6000	130	5800
			94	141	6,000	5,800	141	6000	141	5800
		2-Stage FFL 5 ° Back Tilt	83	118	6,000	5,850	118	6000	118	5850
			86	126	6,000	5,850	126	6000	126	5850
			88	130	6,000	5,800	130	6000	130	5800
			94	142	6,000	5,800	142	6000	142	5800
		3-Stage FFL 5 ° Back Tilt	83	175	5,900	5,700	164	6000	162	5800
			85	181	5,850	5,650	164	6000	162	5800
			88	187	5,750	5,600	164	6000	162	5750
			94	205	5,600	5,400	162	6000	160	5750
		4 stg 4 back tilt	102	223	5,400	5,200	158	6000	164	5700
			104	240	4,900	4,900	164	5900	164	5650
			84	240	3,600	3,550	210	5000	212	4800
			88	252	3,200	3,150	212	4950	214	4800
		4 stg 4 back tilt	92	264	2,800	2,750	214	4900	216	4800
			96	276	2,500	2,450	216	4900	218	4800
	21 x 9 x 15 Std cushion/Non-Marking Compound	2-Stage LFL 5 ° Back Tilt	83	118	6,000	5,850	118	6000	118	5850
			86	126	6,000	5,850	126	6000	126	5850
			88	130	6,000	5,800	130	6000	130	5800
			90	141	6,000	5,800	141	6000	141	5800
		2-Stage FFL 5 ° Back Tilt	83	118	6,000	5,850	118	6000	118	5850
			86	126	6,000	5,850	126	6000	126	5850
			88	130	6,000	5,800	130	6000	130	5800
			90	142	6,000	5,800	142	6000	142	5800
		3-Stage FFL 5 ° Back Tilt	83	175	5,900	5,700	164	6000	164	5800
			85	181	5,850	5,650	164	6000	164	5800
			88	187	5,750	5,600	164	6000	164	5750
			94	205	5,600	5,400	164	6000	164	5750
		4 stg 4 back tilt	102	223	5,400	5,200	160	6000	160	5750
			104	240	5,200	5,000	164	5900	164	5650
			84	240	4,000	3,950	218	5000	220	4800
			88	252	3,550	3,500	220	4950	222	4800
		4 stg 4 back tilt	92	264	3,150	3,150	222	4900	224	4800
			96	276	2,850	2,800	226	4900	226	4800
	21 x 7 x 15 Poly Compound	2-Stage LFL 5 ° Back Tilt	83	118	6,000	5,850	118	6000	118	5850
			86	126	6,000	5,850	126	6000	126	5850
			88	130	6,000	5,800	130	6000	130	5800
			90	141	6,000	5,800	141	6000	141	5800
		2-Stage FFL 5 ° Back Tilt	83	118	6,000	5,850	118	6000	118	5850
			86	126	6,000	5,850	126	6000	126	5850
			88	130	6,000	5,800	130	6000	130	5800
			90	142	6,000	5,800	142	6000	142	5800
		3-Stage FFL 5 ° Back Tilt	83	175	5,900	5,650	164	6000	160	5800
			85	181	5,850	5,600	164	6000	160	5800
			88	187	5,750	5,550	164	6000	160	5750
			94	205	5,600	5,400	160	6000	158	5750
		4 stg 4 back tilt	102	223	5,400	5,200	164	5900	164	5650
			104	240	5,200	5,000	164	5850	164	5650
			84	240	3,750	3,700	212	5000	214	4800
			88	252	3,350	3,300	216	4950	216	4800
		4 stg 4 back tilt	92	264	2,950	2,900	218	4900	218	4800
			96	276	2,650	2,600	220	4900	220	4800

Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration

VER 10.19

Actual mast dimensions may vary from the nominal dimensions stated in the price book. The Overall Lowered Height (OALH) is stated to the next higher full inch and Maximum Fork Height (MFH) is stated to the next lower full inch, to allow for manufacturing tolerances



E60XN - Wide Tread High Lift Sheets



CAPACITY IN POUNDS @ 24 INCH LOAD CENTER; MINIMUM BATTERY WEIGHT=2900 LBS
EQUIPPED WITH: 33" Battery Compartment & 42" FORKS

Tread Width	Tire Size	Mast	OALH	M.F.H.	CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
					38.5" WIDE CARRIAGE	INTEGRAL SIDESHIFT	LIFT HEIGHT	38.5" WIDE CARRIAGE	LIFT HEIGHT	INTEGRAL SIDESHIFT
WIDE TREAD	21 x 8 x 15 Std cushion/Non-Marking Compound	2-Stage LFL 5 ° Back Tilt	83	118	6,000	5,850	118	6000	118	5850
			86	126	6,000	5,850	126	6000	126	5850
			88	130	6,000	5,800	130	6000	130	5800
			94	141	6,000	5,800	141	6000	141	5800
		2-Stage FFL 5° Back Tilt	83	118	6,000	5,850	118	6000	118	5850
			86	126	6,000	5,850	126	6000	126	5850
			88	130	6,000	5,800	130	6000	130	5800
			94	142	6,000	5,800	142	6000	142	5800
		3-Stage FFL 5 ° Back Tilt	83	175	5,900	5,700	164	6000	162	5800
			85	181	5,850	5,650	164	6000	162	5800
			88	187	5,750	5,600	164	6000	162	5750
			94	205	5,600	5,400	162	6000	160	5750
		4 stg 4 back tilt	102	223	5,400	5,200	158	6000	164	5700
			104	240	5,200	5,000	164	5900	164	5650
			84	240	5,000	4,800	240	5000	240	4800
			88	252	4,600	4,450	240	4950	240	4800
		4 stg 4 back tilt	92	264	4,200	4,050	240	4900	240	4800
			96	276	3,800	3,650	240	4900	240	4800
	21 x 9 x 15 Std cushion/Non-Marking Compound	2-Stage LFL 5 ° Back Tilt	83	118	6,000	5,850	118	6000	118	5850
			86	126	6,000	5,850	126	6000	126	5850
			88	130	6,000	5,800	130	6000	130	5800
			90	141	6,000	5,800	141	6000	141	5800
		2-Stage FFL 5° Back Tilt	83	118	6,000	5,850	118	6000	118	5850
			86	126	6,000	5,850	126	6000	126	5850
			88	130	6,000	5,800	130	6000	130	5800
			90	142	6,000	5,800	142	6000	142	5800
		3-Stage FFL 5 ° Back Tilt	83	175	5,900	5,700	164	6000	164	5800
			85	181	5,850	5,650	164	6000	164	5800
			88	187	5,750	5,600	164	6000	164	5750
			94	205	5,600	5,400	164	6000	164	5750
		4 stg 4 back tilt	102	223	5,400	5,200	160	6000	160	5750
			104	240	5,200	5,000	164	5900	164	5650
			84	240	4,900	4,800	238	5000	240	4800
			88	252	4,450	4,400	240	4950	240	4800
		4 stg 4 back tilt	92	264	4,050	4,000	240	4900	240	4800
			96	276	3,650	3,600	240	4900	240	4800
	21 x 7 x 15 Poly Compound	2-Stage LFL 5 ° Back Tilt	83	118	6,000	5,850	118	6000	118	5850
			86	126	6,000	5,850	126	6000	126	5850
			88	130	6,000	5,800	130	6000	130	5800
			90	141	6,000	5,800	141	6000	141	5800
		2-Stage FFL 5° Back Tilt	83	118	6,000	5,850	118	6000	118	5850
			86	126	6,000	5,850	126	6000	126	5850
			88	130	6,000	5,800	130	6000	130	5800
			90	142	6,000	5,800	142	6000	142	5800
		3-Stage FFL 5 ° Back Tilt	83	175	5,900	5,650	164	6000	160	5800
			85	181	5,850	5,600	164	6000	160	5800
			88	187	5,750	5,550	164	6000	160	5750
			94	205	5,600	5,400	160	6000	158	5750
		4 stg 4 back tilt	102	223	5,400	5,200	164	5900	164	5650
			104	240	5,200	5,000	164	5850	164	5650
			84	240	5,000	4,800	240	5000	240	4800
			88	252	4,600	4,450	240	4950	240	4800
		4 stg 4 back tilt	92	264	4,200	4,050	240	4900	240	4800
			96	276	3,800	3,650	240	4900	240	4800

Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration

VER 10.19

Actual mast dimensions may vary from the nominal dimensions stated in the price book. The Overall Lowered Height (OALH) is stated to the next higher full inch and Maximum Fork Height (MFH) is stated to the next lower full inch, to allow for manufacturing tolerances