



E65XN - Standard Tread High Lift Sheets



The Safe Choice

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER; MINIMUM BATTERY WEIGHT=3100 LBS
EQUIPPED WITH: 36" Battery Compartment & 42" FORKS

Tread Width	Tire Size	Mast	OALH	M.F.H.	CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
					38.5" WIDE CARRIAGE	INTEGRAL SIDESHIFT	LIFT HEIGHT	38.5" WIDE CARRIAGE	LIFT HEIGHT	INTEGRAL SIDESHIFT
STANDARD TREAD	21 x 8 x 15 Std cushion/Non-Marking Compound	2-Stage LFL 5 ° Back Tilt	83	118	6,500	6,300	118	6500	118	6300
			86	126	6,500	6,300	126	6500	126	6300
			88	130	6,500	6,300	130	6500	130	6300
			94	141	6,500	6,300	141	6500	141	6300
		2-Stage FFL 5° Back Tilt	83	118	6,500	6,300	118	6500	118	6300
			86	126	6,500	6,300	126	6500	126	6300
			88	130	6,500	6,300	130	6500	130	6300
			94	142	6,500	6,300	142	6500	142	6300
		3-Stage FFL 5 ° Back Tilt	83	175	6,350	6,150	164	6500	162	6250
			85	181	6,300	6,100	164	6500	162	6250
			88	187	6,250	6,050	164	6500	160	6250
			94	205	6,100	5,850	160	6500	160	6250
		4 stg 4 back tilt	102	223	5,900	5,650	156	6500	156	6200
			104	240	5,050	5,000	164	6350	164	6150
			84	240	3,650	3,650	210	5000	212	4800
			88	252	3,300	3,250	212	4950	214	4800
		4 stg 4 back tilt	92	264	2,950	2,900	216	4900	216	4800
			96	276	2,650	2,550	218	4900	218	4800
	21 x 9 x 15 Std cushion/Non-Marking Compound	2-Stage LFL 5 ° Back Tilt	83	118	6,500	6,300	118	6500	118	6300
			86	126	6,500	6,300	126	6500	126	6300
			88	130	6,500	6,300	130	6500	130	6300
			90	141	6,500	6,300	141	6500	141	6300
		2-Stage FFL 5° Back Tilt	83	118	6,500	6,300	118	6500	118	6300
			86	126	6,500	6,300	126	6500	126	6300
			88	130	6,500	6,300	130	6500	130	6300
			90	142	6,500	6,300	142	6500	142	6300
		3-Stage FFL 5 ° Back Tilt	83	175	6,350	6,150	164	6500	164	6250
			85	181	6,300	6,100	164	6500	164	6250
			88	187	6,250	6,050	164	6500	164	6250
			94	205	6,100	5,850	164	6500	162	6250
		4 stg 4 back tilt	102	223	5,900	5,650	158	6500	160	6200
			104	240	5,650	5,450	164	6400	164	6150
			84	240	4,050	4,000	218	5000	220	4800
			88	252	3,700	3,600	222	4950	224	4800
		4 stg 4 back tilt	92	264	3,300	3,250	224	4900	226	4800
			96	276	2,950	2,900	226	4900	228	4800
	21 x 7 x 15 Poly Compound	2-Stage LFL 5 ° Back Tilt	83	118	6,500	6,300	118	6500	118	6300
			86	126	6,500	6,300	126	6500	126	6300
			88	130	6,500	6,300	130	6500	130	6300
			90	141	6,500	6,300	141	6500	141	6300
		2-Stage FFL 5° Back Tilt	83	118	6,500	6,300	118	6500	118	6300
			86	126	6,500	6,300	126	6500	126	6300
			88	130	6,500	6,300	130	6500	130	6300
			90	142	6,500	6,300	142	6500	142	6300
		3-Stage FFL 5 ° Back Tilt	83	175	6,350	6,100	162	6500	158	6250
			85	181	6,300	6,050	162	6500	158	6250
			88	187	6,250	6,000	162	6500	158	6250
			94	205	6,100	5,850	158	6500	156	6250
		4 stg 4 back tilt	102	223	5,900	5,650	164	6400	164	6150
			104	240	5,300	5,300	164	6350	164	6100
			84	240	3,850	3,800	214	5000	216	4800
			88	252	3,450	3,400	216	4950	218	4800
		4 stg 4 back tilt	92	264	3,100	3,050	218	4900	220	4800
			96	276	2,750	2,700	222	4900	222	4800

Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration

VER 10.19

Actual mast dimensions may vary from the nominal dimensions stated in the price book. The Overall Lowered Height (OALH) is stated to the next higher full inch and Maximum Fork Height (MFH) is stated to the next lower full inch, to allow for manufacturing tolerances



E65XN - Wide Tread High Lift Sheets



CAPACITY IN POUNDS @ 24 INCH LOAD CENTER; MINIMUM BATTERY WEIGHT=3100 LBS
EQUIPPED WITH: 36" Battery Compartment & 42" FORKS

Tread Width	Tire Size	Mast	OALH	M.F.H.	CAPACITY @ MFH		LIFT HEIGHT	LIFT HEIGHT @ MAX CAPACITY	
					38.5" WIDE CARRIAGE	INTEGRAL SIDESHIFT		38.5" WIDE CARRIAGE	INTEGRAL SIDESHIFT
WIDE TREAD	21 x 8 x 15 Std cushion/Non-Marking Compound	2-Stage LFL 5 ° Back Tilt	83	118	6,500	6,300	118	6500	6300
			86	126	6,500	6,300	126	6500	6300
			88	130	6,500	6,300	130	6500	6300
			94	141	6,500	6,300	141	6500	6300
		2-Stage FFL 5° Back Tilt	83	118	6,500	6,300	118	6500	6300
			86	126	6,500	6,300	126	6500	6300
			88	130	6,500	6,300	130	6500	6300
			94	142	6,500	6,300	142	6500	6300
		3-Stage FFL 5 ° Back Tilt	83	175	6,350	6,150	164	6500	6250
			85	181	6,300	6,100	164	6500	6250
			88	187	6,250	6,050	164	6500	6250
			94	205	6,100	5,850	160	6500	6250
		4 stg 4 back tilt	102	223	5,900	5,650	156	6500	6200
			104	240	5,700	5,450	164	6350	6150
			84	240	5,000	4,800	240	5000	4800
			88	252	4,600	4,450	240	4950	4800
		21 x 9 x 15 Std cushion/Non-Marking Compound	92	264	4,250	4,050	240	4900	4800
			96	276	3,850	3,650	240	4900	4800
			83	118	6,500	6,300	118	6500	6300
			86	126	6,500	6,300	126	6500	6300
			88	130	6,500	6,300	130	6500	6300
			90	141	6,500	6,300	141	6500	6300
		2-Stage FFL 5° Back Tilt	83	118	6,500	6,300	118	6500	6300
			86	126	6,500	6,300	126	6500	6300
			88	130	6,500	6,300	130	6500	6300
			90	142	6,500	6,300	142	6500	6300
		3-Stage FFL 5 ° Back Tilt	83	175	6,350	6,150	164	6500	6250
			85	181	6,300	6,100	164	6500	6250
			88	187	6,250	6,050	164	6500	6250
			94	205	6,100	5,850	164	6500	6250
		4 stg 4 back tilt	102	223	5,900	5,650	158	6500	6200
			104	240	5,700	5,450	164	6400	6150
			84	240	4,950	4,800	238	5000	4800
			88	252	4,550	4,450	240	4950	4800
		21 x 7 x 15 Poly Compound	92	264	4,150	4,100	240	4900	4800
			96	276	3,750	3,700	240	4900	4800
			83	118	6,500	6,300	118	6500	6300
			86	126	6,500	6,300	126	6500	6300
			88	130	6,500	6,300	130	6500	6300
			90	141	6,500	6,300	141	6500	6300
		2-Stage FFL 5° Back Tilt	83	118	6,500	6,300	118	6500	6300
			86	126	6,500	6,300	126	6500	6300
			88	130	6,500	6,300	130	6500	6300
			90	142	6,500	6,300	142	6500	6300
		3-Stage FFL 5 ° Back Tilt	83	175	6,350	6,100	162	6500	6250
			85	181	6,300	6,050	162	6500	6250
			88	187	6,250	6,000	162	6500	6250
			94	205	6,100	5,850	158	6500	6250
		4 stg 4 back tilt	102	223	5,900	5,650	164	6400	6150
			104	240	5,650	5,450	164	6350	6100
			84	240	5,000	4,800	240	5000	4800
			88	252	4,600	4,450	240	4950	4800
			92	264	4,200	4,050	240	4900	4800
			96	276	3,800	3,650	240	4900	4800

Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration

VER 10.19

Actual mast dimensions may vary from the nominal dimensions stated in the price book. The Overall Lowered Height (OALH) is stated to the next higher full inch and Maximum Fork Height (MFH) is stated to the next lower full inch, to allow for manufacturing tolerances