



E70XN - Standard Tread High Lift Sheets



The Safe Choice

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER; MINIMUM BATTERY WEIGHT=3400 LBS
EQUIPPED WITH: 40" Battery Compartment & 42" FORKS

Tread Width	Tire Size	Mast	OALH	M.F.H.	CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY		
					38.5" WIDE CARRIAGE	INTEGRAL SIDESHIFT	LIFT HEIGHT	38.5" WIDE CARRIAGE	INTEGRAL SIDESHIFT
STANDARD TREAD	21 x 9 x 15 Std cushion/Non-Marking Compound	2-Stage LFL	83	118	7,000	6,800	118	7000	6800
		5 ° Back Tilt	86	126	7,000	6,800	126	7000	6800
			88	130	7,000	6,800	130	7000	6800
			94	141	7,000	6,800	141	7000	6800
		2-Stage FFL	83	118	7,000	6,800	118	7000	6800
		5 ° Back Tilt	86	126	7,000	6,800	126	7000	6800
			88	130	7,000	6,800	130	7000	6800
			94	142	7,000	6,800	142	7000	6800
		3-Stage FFL	83	175	6,850	6,650	164	7000	6750
		5 ° Back Tilt	85	181	6,800	6,600	164	7000	6750
			88	187	6,750	6,550	164	7000	6750
			94	205	6,550	6,350	164	7000	6700
			102	223	6,350	6,100	164	7000	6700
			104	240	5,750	5,700	164	7000	6700
		4 stg	84	240	4,150	4,050	220	5000	4800
		4 back tilt	88	252	3,750	3,700	222	4950	4800
	21 x 8 x 15 Poly Compound		92	264	3,400	3,350	226	4900	4800
			96	276	3,100	3,000	228	4900	4800
		2-Stage LFL	83	118	7,000	6,800	118	7000	6800
		5 ° Back Tilt	86	126	7,000	6,800	126	7000	6800
			88	130	7,000	6,800	130	7000	6800
			90	141	7,000	6,800	141	7000	6800
		2-Stage FFL	83	118	7,000	6,800	118	7000	6800
		5 ° Back Tilt	86	126	7,000	6,800	126	7000	6800
			88	130	7,000	6,800	130	7000	6800
			90	142	7,000	6,800	142	7000	6800
		3-Stage FFL	83	175	6,850	6,650	164	7000	6750
		5 ° Back Tilt	85	181	6,800	6,600	164	7000	6750
			88	187	6,750	6,550	164	7000	6750
			94	205	6,550	6,350	164	7000	6700
			102	223	6,350	6,100	164	7000	6700
			104	240	5,750	5,700	164	7000	6700
		4 stg	84	240	4,200	4,100	220	5000	4800
		4 back tilt	88	252	3,850	3,750	222	4950	4800
			92	264	3,500	3,400	226	4900	4800
			96	276	3,150	3,100	228	4900	4800

Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration

VER 10.19

Actual mast dimensions may vary from the nominal dimensions stated in the price book. The Overall Lowered Height (OALH) is stated to the next higher full inch and Maximum Fork Height (MFH) is stated to the next lower full inch, to allow for manufacturing tolerances



E70XN - Wide Tread High Lift Sheets



The Safe Choice

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER; MINIMUM BATTERY WEIGHT=3400 LBS
EQUIPPED WITH: 40" Battery Compartment & 42" FORKS

Tread Width	Tire Size	Mast	OALH	M.F.H.	CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
					38.5" WIDE CARRIAGE	INTEGRAL SIDESHIFT	LIFT HEIGHT	38.5" WIDE CARRIAGE	LIFT HEIGHT	INTEGRAL SIDESHIFT
WIDE TREAD	21 x 9 x 15 Std cushion/Non-Marking Compound	2-Stage LFL	83	118	7,000	6,800	118	7000	118	6800
		5 ° Back Tilt	86	126	7,000	6,800	126	7000	126	6800
			88	130	7,000	6,800	130	7000	130	6800
			94	141	7,000	6,800	141	7000	141	6800
		2-Stage FFL	83	118	7,000	6,800	118	7000	118	6800
		5 ° Back Tilt	86	126	7,000	6,800	126	7000	126	6800
			88	130	7,000	6,800	130	7000	130	6800
			94	142	7,000	6,800	142	7000	142	6800
		3-Stage FFL	83	175	6,850	6,650	164	7000	164	6750
		5 ° Back Tilt	85	181	6,800	6,600	164	7000	164	6750
			88	187	6,750	6,550	164	7000	164	6750
			94	205	6,550	6,350	164	7000	164	6700
			102	223	6,350	6,100	164	7000	164	6700
			104	240	6,150	5,900	164	7000	164	6700
		4 stg	84	240	5,000	4,800	240	5000	240	4800
		4 back tilt	88	252	4,600	4,450	240	4950	240	4800
			92	264	4,200	4,100	240	4900	240	4800
			96	276	3,900	3,700	240	4900	240	4800
	21 x 8 x 15 Poly Compound	2-Stage LFL	83	118	7,000	6,800	118	7000	118	6800
		5 ° Back Tilt	86	126	7,000	6,800	126	7000	126	6800
			88	130	7,000	6,800	130	7000	130	6800
			90	141	7,000	6,800	141	7000	141	6800
		2-Stage FFL	83	118	7,000	6,800	118	7000	118	6800
		5 ° Back Tilt	86	126	7,000	6,800	126	7000	126	6800
			88	130	7,000	6,800	130	7000	130	6800
			90	142	7,000	6,800	142	7000	142	6800
		3-Stage FFL	83	175	6,850	6,650	164	7000	164	6750
		5 ° Back Tilt	85	181	6,800	6,600	164	7000	164	6750
			88	187	6,750	6,550	164	7000	164	6750
			94	205	6,550	6,350	164	7000	164	6700
			102	223	6,350	6,100	164	7000	164	6700
			104	240	6,150	5,900	164	7000	164	6700
		4 stg	84	240	5,000	4,800	240	5000	240	4800
		4 back tilt	88	252	4,600	4,450	240	4950	240	4800
			92	264	4,250	4,100	240	4900	240	4800
			96	276	3,850	3,700	240	4900	240	4800

Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration

VER 10.19

Actual mast dimensions may vary from the nominal dimensions stated in the price book. The Overall Lowered Height (OALH) is stated to the next higher full inch and Maximum Fork Height (MFH) is stated to the next lower full inch, to allow for manufacturing tolerances