



J35XNT HIGHLIFT SHEETS



The Safe Choice

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
EQUIPPED WITH 42" FORKS

				OALH	M.F.H.	MAX BACK TILT (DEG)	CAPACITY @ MFH (LBS)		LIFT HEIGHT @ MAX CAPACITY		
				(IN)	(IN)		38.5" WIDE CARRIAGE	INTEGRAL SIDESHIFT	LIFT HEIGHT(IN)	38.5" WIDE CARRIAGE (LBS)	INTEGRAL SIDESHIFT (LBS)
25.3" (642 mm) BATTERY COMPARTMENT:	Without Aux Counterweight spacer. Min Battery Weight= 2500 lbs	18 x 7 x 12.1 Cushion Drive 15 x 4 x 11.25 Cushion Steer	2-Stage LFL	78	119	5	3,500	3,500	119	3500	3500
				82	127	5	3,500	3,500	127	3500	3500
				88	150	5	3,500	3,500	150	3500	3500
				110	170	5	3,500	3,450	170	3500	3450
			2-Stage FFL	78	118	5	3,500	3,500	118	3500	3500
				82	126	5	3,500	3,500	126	3500	3500
				88	138	5	3,500	3,500	138	3500	3500
				94	150	5	3,500	3,500	150	3500	3500
			3-Stage FFL	78	175	5	3,500	3,450	175	3500	3450
				82	187	5	3,500	3,450	187	3500	3450
				84	192	5	3,500	3,450	192	3500	3450
				88	198	5	3,450	3,400	192	3500	3450
			Lift-Tek 4-Stage FFL	94	216	5	3,300	3,250	192	3500	3450
				98	222	5	3,250	3,200	192	3500	3450
				84	241	4	2,500	2,450	212	2700	2650
				90	259	4	2,350	2,300	212	2700	2600
	Aux Counterweight spacer. Min Battery Weight= 2100 lbs	18 x 7 x 12.1 Solid Pneumatic Drive Tires 15 x 4 x 11.25 Solid Pneumatic Steer Tires	2-Stage LFL	78	119	5	3,500	3,500	119	3500	3500
				82	127	5	3,500	3,500	127	3500	3500
				88	150	5	3,500	3,500	150	3500	3500
				110	170	5	3,500	3,450	170	3500	3450
			2-Stage FFL	78	118	5	3,500	3,500	118	3500	3500
				82	126	5	3,500	3,500	126	3500	3500
				88	138	5	3,500	3,500	138	3500	3500
				94	150	5	3,500	3,500	150	3500	3500
			3-Stage FFL	78	175	5	3,500	3,500	175	3500	3500
				82	187	5	3,500	3,450	187	3500	3450
				84	192	5	3,500	3,450	192	3500	3450
			Lift-Tek 4-Stage FFL	88	198	5	3,400	3,350	192	3500	3450
				94	216	5	2,950	2,900	192	3500	3450
				98	222	5	2,850	2,750	192	3500	3450
				84	241	4	2,250	2,250	212	2700	2650
				90	259	4	1,900	1,900	212	2700	2600
		18 x 7 x 12.1 Cushion Drive 15 x 4 x 11.25 Cushion Steer	2-Stage LFL	78	119	5	3,500	3,500	119	3500	3500
				82	127	5	3,500	3,500	127	3500	3500
				88	150	5	3,500	3,500	150	3500	3500
				110	170	5	3,500	3,450	170	3500	3450
			2-Stage FFL	78	118	5	3,500	3,500	118	3500	3500
				82	126	5	3,500	3,500	126	3500	3500
				88	138	5	3,500	3,500	138	3500	3500
				94	150	5	3,500	3,500	150	3500	3500
			3-Stage FFL	78	175	5	3,500	3,500	175	3500	3500
				82	187	5	3,500	3,450	187	3500	3450
				84	192	5	3,500	3,450	192	3500	3450
			Lift-Tek 4-Stage FFL	88	198	5	3,450	3,400	192	3500	3450
				94	216	5	3,300	3,250	192	3500	3450
				98	222	5	3,250	3,200	192	3500	3450
				84	241	4	2,500	2,450	212	2700	2650
		18 x 7 x 12.1 Solid Pneumatic Drive Tires 15 x 4 x 11.25 Solid Pneumatic Steer Tires	2-Stage LFL	84	241	4	2,200	2,200	212	2700	2650
				90	259	4	1,900	1,850	212	2700	2600

Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration

Actual mast dimensions may vary from the nominal dimensions stated in the price book. The Overall Lowered Height (OALH) is stated to the next higher full inch and Maximum Fork Height (MFH) is stated to the next lower full inch, to allow for manufacturing tolerances