



J60XN HIGHLIFT SHEETS



CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
34" BATTERY COMPARTMENT - LIFT OUT BATTERY EXTRACTION
EQUIPPED WITH 2.0" x 4.9" x 42" FORKS

			OALH	M.F.H.	MAX	CAPACITY @ MFH (LBS)		LIFT HEIGHT @ MAX CAPACITY			
			(IN)	(IN)	BACK TILT (DEG)	42" WIDE CARRIAGE	INTEGRAL SIDESHIFT	LIFT HEIGHT(IN)	42" WIDE CARRIAGE (LBS)	LIFT HEIGHT(IN)	INTEGRAL SIDESHIFT (LBS)
J60XN - 34" BATTERY COMPARTMENT. MINIMUM BATTERY WEIGHT = 4460 LBS	Std Tread (47") 23 x 10-12 16PR Pneumatic Drive Tires	2-Stage LFL	87	126	5	6,000	5,850	126	6000	126	5850
			91	134	5	6,000	5,850	134	6000	134	5850
			95	142	5	6,000	5,850	142	6000	142	5850
			109	161	5	6,000	5,800	161	6000	161	5800
		2-Stage FFL	87	126	5	6,000	5,850	126	6000	126	5850
			91	134	5	6,000	5,850	134	6000	134	5850
			95	142	5	6,000	5,800	142	6000	142	5800
			107	161	5	6,000	5,800	161	6000	161	5800
		3-Stage FFL	85	181	5	6,000	5,750	181	6000	181	5750
			89	187	5	6,000	5,750	187	6000	187	5750
			91	193	5	5,750	5,650	187	6000	187	5750
			95	205	5	5,150	5,050	187	6000	187	5750
			101	217	5	4,650	4,550	187	6000	187	5700
			103	223	5	4,400	4,300	187	6000	187	5700
			105	229	5	4,200	4,100	187	6000	187	5700
			109	235	5	4,000	3,950	187	6000	187	5700
	Std Tread (47") 23 x 10-12 16PR Pneumatic Solid Drive Tires	2-Stage LFL	87	126	5	6,000	5,850	126	6000	126	5850
			91	134	5	6,000	5,850	134	6000	134	5850
			95	142	5	6,000	5,850	142	6000	142	5850
			109	161	5	6,000	5,800	161	6000	161	5800
		2-Stage FFL	87	126	5	6,000	5,850	126	6000	126	5850
			91	134	5	6,000	5,850	134	6000	134	5850
			95	142	5	6,000	5,800	142	6000	142	5800
			107	161	5	6,000	5,800	161	6000	161	5800
		3-Stage FFL	85	181	5	6,000	5,750	181	6000	181	5750
			89	187	5	6,000	5,750	187	6000	187	5750
			91	193	5	5,900	5,700	187	6000	187	5750
			95	205	5	5,800	5,550	187	6000	187	5750
			101	217	5	5,650	5,400	187	6000	187	5700
			103	223	5	5,600	5,350	187	6000	187	5700
			105	229	5	5,500	5,250	187	6000	187	5700
			109	235	5	5,400	5,200	187	6000	187	5700
	Wide Tread (52") 23 x 10-12 16PR Pneumatic Drive Tires	2-Stage LFL	87	126	5	6,000	5,850	126	6000	126	5850
			91	134	5	6,000	5,850	134	6000	134	5850
			95	142	5	6,000	5,850	142	6000	142	5850
			109	161	5	6,000	5,800	161	6000	161	5800
		2-Stage FFL	87	126	5	6,000	5,850	126	6000	126	5850
			91	134	5	6,000	5,850	134	6000	134	5850
			95	142	5	6,000	5,800	142	6000	142	5800
			107	161	5	6,000	5,800	161	6000	161	5800
		3-Stage FFL	85	181	5	6,000	5,750	181	6000	181	5750
			89	187	5	6,000	5,750	187	6000	187	5750
			91	193	5	5,900	5,700	187	6000	187	5750
			95	205	5	5,800	5,550	187	6000	187	5750
			101	217	5	5,650	5,400	187	6000	187	5700
			103	223	5	5,600	5,350	187	6000	187	5700
			105	229	5	5,500	5,250	187	6000	187	5700
			109	235	5	5,450	5,200	187	6000	187	5700
	Wide Tread (52") 23 x 10-12 16PR Pneumatic Solid Drive Tires	2-Stage LFL	87	126	5	6,000	5,850	126	6000	126	5850
			91	134	5	6,000	5,850	134	6000	134	5850
			95	142	5	6,000	5,850	142	6000	142	5850
			109	161	5	6,000	5,800	161	6000	161	5800
		2-Stage FFL	87	126	5	6,000	5,850	126	6000	126	5850
			91	134	5	6,000	5,850	134	6000	134	5850
			95	142	5	6,000	5,800	142	6000	142	5800
			107	161	5	6,000	5,800	161	6000	161	5800
		3-Stage FFL	85	181	5	6,000	5,750	181	6000	181	5750
			89	187	5	6,000	5,750	187	6000	187	5750
			91	193	5	5,900	5,700	187	6000	187	5750
			95	205	5	5,800	5,550	187	6000	187	5750
			101	217	5	5,650	5,400	187	6000	187	5700
			103	223	5	5,600	5,350	187	6000	187	5700
			105	229	5	5,500	5,250	187	6000	187	5700
			109	235	5	5,450	5,200	187	6000	187	5700

Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration

Actual mast dimensions may vary from the nominal dimensions stated in the price book. The Overall Lowered Height (OALH) is stated to the next higher full inch and Maximum Fork Height (MFH) is stated to the next lower full inch, to allow for manufacturing tolerances