



J30ZT HIGHLIFT SHEETS

HYSTER®

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
EQUIPPED WITH 42" FORKS & 21.5" BATTERY COMPARTMENT

		MFH	OALH	CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
				CARRIAGE	INTEGRAL SIDESHIFT	LIFT HEIGHT	CARRIAGE	LIFT HEIGHT	INTEGRAL SIDESHIFT
J30ZT 18x7x12.1 Cush Std Tread	2-Stage (LFL) 7 Deg Back Tilt	119.0	78.0	3000	3000	119.0	3000	119.0	3000
		127.0	82.0	3000	3000	127.0	3000	127.0	3000
		151.0	94.0	3000	3000	151.0	3000	151.0	3000
	2-Stage (FFL) 5 Deg Back Tilt	109.0	72.0	3000	3000	109.0	3000	109.0	3000
		120.0	78.0	3000	3000	120.0	3000	120.0	3000
		128.0	82.0	3000	3000	128.0	3000	128.0	3000
	3-Stage (FFL) 5 Deg Back Tilt	152.0	94.0	3000	3000	152.0	3000	152.0	3000
		159.0	72.0	3000	3000	159.0	3000	159.0	3000
		177.0	78.0	3000	3000	177.0	3000	177.0	3000
	5 Deg Back Tilt	189.0*	82.0	3000	3000	189.0	3000	189.0	3000
		218.0	94.0	2800	2800	206.7	3000	206.7	3000
J30ZT 18x7x12.1 Solid Std Tread	2-Stage (LFL) 7 Deg Back Tilt	119.0	78.0	3000	3000	119.0	3000	119.0	3000
		127.0	82.0	3000	3000	127.0	3000	127.0	3000
		151.0	94.0	3000	3000	151.0	3000	151.0	3000
	2-Stage (FFL) 5 Deg Back Tilt	109.0	72.0	3000	3000	109.0	3000	109.0	3000
		120.0	78.0	3000	3000	120.0	3000	120.0	3000
		128.0	82.0	3000	3000	128.0	3000	128.0	3000
	3-Stage (FFL) 5 Deg Back Tilt	152.0	94.0	3000	3000	152.0	3000	152.0	3000
		159.0	72.0	3000	3000	159.0	3000	159.0	3000
		177.0	78.0	3000	3000	177.0	3000	177.0	3000
	5 Deg Back Tilt	189.0	82.0	3000	3000	189.0	3000	189.0	3000
		218.0	94.0	2450	2450	197.8	3000	197.8	3000

RATED VERSION V0307.01 (3.24.04)

* Highest Non-High Lift Mast Rated at Full Capacity

Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration.

Contact Applications Engineering for 4-Stage FFL (Quad) Mast ratings.

Actual mast dimensions may vary from nominal dimensions stated in price book. The Overall Lowered Height (OALH) is stated to the next higher full inch and Maximum Fork height (MFH) is stated to the next lower full inch, to allow for manufacturing tolerances.