



J35ZT HIGHLIFT SHEETS

HYSTER®

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
EQUIPPED WITH 42" FORKS & 25" BATTERY COMPARTMENT

		MFH	OALH	CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
				CARRIAGE	INTEGRAL SIDESHIFT	LIFT HEIGHT	CARRIAGE	LIFT HEIGHT	INTEGRAL SIDESHIFT
J35ZT 18x7x12.1 Cush Std Tread	2-Stage (LFL) 7 Deg Back Tilt	119.0	78.0	3500	3500	119.0	3500	119.0	3500
		127.0	82.0	3500	3500	127.0	3500	127.0	3500
		151.0	94.0	3500	3500	151.0	3500	151.0	3500
	2-Stage (FFL) 5 Deg Back Tilt	109.0	72.0	3500	3500	109.0	3500	109.0	3500
		120.0	78.0	3500	3500	120.0	3500	120.0	3500
		128.0	82.0	3500	3500	128.0	3500	128.0	3500
	3-Stage (FFL) 5 Deg Back Tilt	152.0	94.0	3500	3500	152.0	3500	152.0	3500
		159.0	72.0	3500	3500	159.0	3500	159.0	3500
		177.0	78.0	3500	3500	177.0	3500	177.0	3500
	3-Stage (FFL) 5 Deg Back Tilt	189.0*	82.0	3500	3500	189.0	3500	189.0	3500
		218.0	94.0	3100	3100	189.0	3500	189.0	3500
J35ZT 18x7x12.1 Solid Std Tread	2-Stage (LFL) 7 Deg Back Tilt	119.0	78.0	3500	3500	119.0	3500	119.0	3500
		127.0	82.0	3500	3500	127.0	3500	127.0	3500
		151.0	94.0	3500	3500	151.0	3500	151.0	3500
	2-Stage (FFL) 5 Deg Back Tilt	109.0	72.0	3500	3500	109.0	3500	109.0	3500
		120.0	78.0	3500	3500	120.0	3500	120.0	3500
		128.0	82.0	3500	3500	128.0	3500	128.0	3500
	3-Stage (FFL) 5 Deg Back Tilt	152.0	94.0	3500	3500	152.0	3500	152.0	3500
		159.0	72.0	3500	3500	159.0	3500	159.0	3500
		177.0	78.0	3500	3500	177.0	3500	177.0	3500
	3-Stage (FFL) 5 Deg Back Tilt	189.0	82.0	3500	3450	189.0	3500	188.0	3500
		218.0	94.0	2700	2650	189.0	3500	180.1	3500

RATED VERSION V0307.01 (3.24.04)

* Highest Non-High Lift Mast Rated at Full Capacity

Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration.

Contact Applications Engineering for 4-Stage FFL (Quad) Mast ratings.

Actual mast dimensions may vary from nominal dimensions stated in price book. The Overall Lowered Height (OALH) is stated to the next higher full inch and Maximum Fork height (MFH) is stated to the next lower full inch, to allow for manufacturing tolerances.