



J40Z HIGHLIFT SHEETS

HYSTER

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
EQUIPPED WITH 42" FORKS

			MFH	OALH	CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
					CARRIAGE	INTEGRAL SIDESHIFT	LIFT HEIGHT	CARRIAGE	LIFT HEIGHT	INTEGRAL SIDESHIFT
J40Z 28" Battery Compartment (Std.)	Pneumatic Drive Tires Standard Tread	2 Stg LFL	119.0	79.0	4000	3950	119.0	4000	119.0	3950
			131.0	85.0	4000	3950	131.0	4000	131.0	3950
			150.0	95.0	4000	3900	150.0	4000	150.0	3900
		2 Stg FFL	118.0	79.0	4000	3950	118.0	4000	118.0	3950
			129.0	85.0	4000	3950	129.0	4000	129.0	3950
			171.0	77.0	4000	3850	171.0	4000	171.0	3850
	Pneumatic Drive Tires Wide	3 Stg FFL	189.0	83.0	4000	3850	189.0	4000	189.0	3850
			218.5	95.0	3300	3300	189.0	4000	189.0	3850
			171.0	77.0	4000	3850	171.0	4000	171.0	3850
		3 Stg FFL	189.0	83.0	4000	3850	189.0	4000	189.0	3850
			218.5	95.0	3750	3600	189.0	4000	189.0	3850
			171.0	77.0	4000	3850	171.0	4000	171.0	3850
	Solid Pneumatic Shaped	3 Stg FFL	189.0	83.0	4000	3850	189.0	4000	189.0	3850
			218.5	95.0	3750	3650	189.0	4000	189.0	3850
			171.0	77.0	4000	3850	171.0	4000	171.0	3850
		3 Stg FFL	189.0	83.0	4000	3850	189.0	4000	189.0	3850
			218.5	95.0	3750	3650	189.0	4000	189.0	3850
			171.0	77.0	4000	3850	171.0	4000	171.0	3850

RATED VERSION V0307.00 (10/23/03)

Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration.

Actual mast dimensions may vary from nominal dimensions stated in price book. The Overall Lowered Height (**OALH**) is stated to the next higher full inch and Maximum Fork height (**MFH**) is stated to the next lower full inch, to allow for manufacturing tolerances.

High lift masts are masts which because of their type or lift height, require capacity reduction and/or back tilt restriction. In the the case of this model, any fork height greater than 189" (4800mm) is a high lift.

HYSTER COMPANY * 1400 SULLIVAN DRIVE * GREENVILLE, NC 27834