



J50Z-34" HIGHLIFT SHEETS

HYSTER®

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
EQUIPPED WITH 42" FORKS
BATTERY WEIGHT RANGE: 4450 lbs-4950 lbs

			MFH	OALH	CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
					CARRIAGE	INTEGRAL SIDESHIFT	LIFT HEIGHT	CARRIAGE	LIFT HEIGHT	INTEGRAL SIDESHIFT
J50Z 34" Battery Compartment (Opt.)	Pneumatic Drive Tires Standard Tread	2 Stg LFL	119.0	79.0	5000	4900	119.0	5000	119.0	4900
			131.0	85.0	5000	4900	131.0	5000	131.0	4900
			150.0	95.0	5000	4900	150.0	5000	150.0	4900
		2 Stg FFL	118.0	79.0	5000	4900	118.0	5000	118.0	4900
			129.0	85.0	5000	4900	129.0	5000	129.0	4900
			171.0	77.0	5000	4850	171.0	5000	171.0	4850
	Pneumatic Drive Tires Wide Tread	3 Stg FFL	189.0	83.0	4900	4800	187.0	5000	189.0	4800
			218.0	95.0	3750	3700	186.0	5000	190.0	4800
			171.0	77.0	5000	4850	171.0	5000	171.0	4850
		3 Stg FFL	189.0	83.0	5000	4800	189.0	5000	189.0	4800
			218.0	95.0	4600	4600	200.8	5000	200.8	4800
			171.0	77.0	5000	4850	171.0	5000	171.0	4850
	Solid Pneumatic Shaped Drive Tires Standard Tread	3 Stg FFL	189.0	83.0	5000	4800	189.0	5000	189.0	4800
			218.0	95.0	4850	4650	200.8	5000	200.8	4800
			171.0	77.0	5000	4850	171.0	5000	171.0	4850
	Solid Pneumatic Shaped Drive Tires Wide Tread	3 Stg FFL	189.0	83.0	5000	4800	189.0	5000	189.0	4800
			218.0	95.0	4850	4650	200.8	5000	200.8	4800
			171.0	77.0	5000	4850	171.0	5000	171.0	4850

RATED VERSION V0307.02 (07/08/04)

Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration.

Actual mast dimensions may vary from nominal dimensions stated in price book. The Overall Lowered Height (**OALH**) is stated to the next higher full inch and Maximum Fork height (**MFH**) is stated to the next lower full inch, to allow for manufacturing tolerances.

High lift masts are masts which because of their type or lift height, require capacity reduction and/or back tilt restriction. In the the case of this model, any fork height greater than 177" (4500mm) is a high lift.