



J60-65Z-34" HIGHLIFT SHEETS

HYSTER®

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
EQUIPPED WITH 42" FORKS
BATTERY WEIGHT RANGE: 4450 lbs-4950 lbs

			MFH	OALH	CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
					CARRIAGE	INTEGRAL SIDESHIFT	LIFT HEIGHT	CARRIAGE	LIFT HEIGHT	INTEGRAL SIDESHIFT
J60Z 34" Battery Compartment (Std.)	Pneumatic Drive Tires Standard Tread	2 Stg LFL	126.0	85.0	6000	5800	126.0	6000	126.0	5800
			146.0	95.0	6000	5800	146.0	6000	146.0	5800
		2 Stg FFL	126.0	85.0	6000	5800	126.0	6000	126.0	5800
			164.0	77.0	6000	5750	164.0	6000	164.0	5750
			181.0	83.0	5200	5150	167.0	6000	170.0	5750
			193.0	89.0	4600	4600	167.0	6000	171.0	5700
	Pneumatic Drive Tires Wide Tread	3 Stg FFL	211.0	95.0	3900	3850	166.0	6000	171.0	5700
			164.0	77.0	6000	5750	164.0	6000	164.0	5750
			181.0	83.0	6000	5750	182.0	6000	182.0	5750
			193.0	89.0	5650	5650	188.0	6000	188.0	5700
		211.0	95.0	4850	4850	188.0	6000	188.0	5700	
		Solid Pneumatic Shaped Drive Tires Standard Tread	3 Stg FFL	164.0	77.0	6000	5750	164.0	6000	164.0
	181.0			83.0	6000	5750	182.0	6000	182.0	5750
	193.0			89.0	5950	5700	188.0	6000	193.0	5700
	211.0			95.0	5300	5300	188.0	6000	188.0	5700
	Solid Pneumatic Shaped Drive Tires Wide Tread	3 Stg FFL	164.0	77.0	6000	5750	164.0	6000	164.0	5750
181.0			83.0	6000	5750	182.0	6000	182.0	5750	
193.0			89.0	5950	5700	188.0	6000	193.0	5700	
211.0			95.0	5750	5500	188.0	6000	188.0	5700	

RATED VERSION V0307.02 (07/08/04)

			MFH	OALH	CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY				
					CARRIAGE	INTEGRAL SIDESHIFT	LIFT HEIGHT	CARRIAGE	LIFT HEIGHT	INTEGRAL SIDESHIFT	
J65Z 34" Battery Compartment (Std.)	Pneumatic Drive Tires Standard Tread	2 Stg LFL	126.0	85.0	6500	6350	126.0	6500	126.0	6350	
			146.0	95.0	6500	6300	146.0	6500	139.2	6300	
		2 Stg FFL	126.0	85.0	6500	6300	126.0	6500	126.0	6300	
			3 Stg FFL	164.0	77.0	6250	6200	160.0	6500	163.0	6250
				181.0	83.0	5250	5200	160.0	6500	164.0	6200
				193.0	89.0	4700	4650	160.0	6500	164.0	6200
	211.0	95.0		3950	3900	160.0	6500	164.0	6200		
	Pneumatic Drive Tires Wide Tread	3 Stg FFL	164.0	77.0	6500	6250	164.0	6500	164.0	6250	
			181.0	83.0	6450	6200	181.0	6500	181.0	6200	
			193.0	89.0	5800	5750	181.0	6500	186.0	6200	
			211.0	95.0	4950	4950	179.0	6500	184.0	6200	
	Solid Pneumatic Shaped Drive Tires Standard Tread	3 Stg FFL	164.0	77.0	6500	6250	164.0	6500	164.0	6250	
			181.0	83.0	6500	6200	182.0	6500	182.0	6200	
			193.0	89.0	6400	6150	186.0	6500	188.0	6200	
			211.0	95.0	5450	5400	184.0	6500	188.0	6200	
	Solid Pneumatic Shaped Drive Tires Wide Tread	3 Stg FFL	164.0	77.0	6500	6250	164.0	6500	164.0	6250	
181.0			83.0	6500	6200	182.0	6500	182.0	6200		
193.0			89.0	6400	6150	186.8	6500	188.0	6200		
211.0			95.0	6250	5950	184.0	6500	187.8	6200		

RATED VERSION V0307.02 (07/08/04)

Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration.

Actual mast dimensions may vary from nominal dimensions stated in price book. The Overall Lowered Height (OALH) is stated to the next higher full inch and Maximum Fork height (MFH) is stated to the next lower full inch, to allow for manufacturing tolerances.

High lift masts are masts which because of their type or lift height, require capacity reduction and/or back tilt restriction. In the the case of the J60Z model, any fork height greater than 170" (4320mm) is a high lift. In the case of the J65Z model, any fork height greater than 158" (4020mm) is a high lift.