



J60-65Z HIGHLIFT SHEETS

HYSTER

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
EQUIPPED WITH 42" FORKS

			MFH	OALH	CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY					
					CARRIAGE	INTEGRAL SIDESHIFT	LIFT HEIGHT	CARRIAGE	LIFT HEIGHT	INTEGRAL SIDESHIFT		
J60Z	34" Battery Compartment (Std.)	2 Stg LFL	126.0	85.0	6000	5800	126.0	6000	126.0	5800		
			146.0	95.0	6000	5800	146.0	6000	146.0	5800		
		2 Stg FFL	126.0	85.0	6000	5800	126.0	6000	126.0	5800		
			3 Stg FFL	164.0	77.0	6000	5750	164.0	6000	164.0	5750	
				181.0	83.0	5150	5100	166.1	6000	169.1	5750	
				193.0	89.0	4600	4550	166.1	6000	170.1	5700	
		211.0	95.0	3850	3800	166.1	6000	170.1	5700			
		3 Stg FFL	164.0	77.0	6000	5750	164.0	6000	164.0	5750		
			181.0	83.0	5950	5700	178.0	6000	178.9	5750		
			193.0	89.0	5650	5600	176.0	6000	183.9	5700		
			211.0	95.0	4800	4800	177.0	6000	180.9	5700		
		3 Stg FFL	164.0	77.0	6000	5750	164.0	6000	164.0	5750		
	181.0		83.0	6000	5750	181.0	6000	181.0	5750			
	193.0		89.0	5900	5700	184.8	6000	193.0	5700			
	211.0		95.0	5200	5200	182.9	6000	187.8	5700			
	3 Stg FFL	164.0	77.0	6000	5750	164.0	6000	164.0	5750			
		181.0	83.0	6000	5750	181.0	6000	181.0	5750			
		193.0	89.0	5900	5700	184.8	6000	193.0	5700			
		211.0	95.0	5700	5500	182.9	6000	187.8	5700			
	J65Z	34" Battery Compartment (Std.)	2 Stg LFL	126.0	85.0	6500	6300	126.0	6500	126.0	6300	
				146.0	95.0	6450	6200	146.0	6500	139.2	6300	
			2 Stg FFL	126.0	85.0	6500	6250	126.0	6500	126.0	6300	
				3 Stg FFL	164.0	77.0	6200	6050	146.5	6500	145.5	6250
					181.0	83.0	5250	5200	143.5	6500	148.4	6200
193.0					89.0	4650	4600	142.5	6500	146.5	6200	
211.0			95.0	3900	3850	139.6	6500	144.5	6200			
3 Stg FFL			164.0	77.0	6300	6050	146.5	6500	145.5	6250		
			181.0	83.0	6100	5900	143.5	6500	148.4	6200		
			193.0	89.0	5700	5700	142.5	6500	146.5	6200		
			211.0	95.0	4850	4850	139.6	6500	144.5	6200		
3 Stg FFL			164.0	77.0	6350	6100	151.4	6500	150.4	6250		
		181.0	83.0	6200	5950	149.4	6500	154.3	6200			
		193.0	89.0	6050	5800	147.4	6500	152.4	6200			
		211.0	95.0	5350	5300	145.5	6500	150.4	6200			
3 Stg FFL		164.0	77.0	6350	6100	151.4	6500	150.4	6250			
		181.0	83.0	6200	5950	149.4	6500	154.3	6200			
		193.0	89.0	6050	5800	147.4	6500	152.4	6200			
		211.0	95.0	5900	5650	145.5	6500	150.4	6200			

RATED VERSION V0307.00 (10/23/03)

Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration.

Actual mast dimensions may vary from nominal dimensions stated in price book. The Overall Lowered Height (OALH) is stated to the next higher full inch and Maximum Fork height (MFH) is stated to the next lower full inch, to allow for manufacturing tolerances.

High lift masts are masts which because of their type or lift height, require capacity reduction and/or back tilt restriction. In the the case of the J60Z model, any fork height greater than 170" (4320mm) is a high lift. In the case of the J65Z model, any fork height greater than 158" (4020mm) is a high lift.

HYSTER COMPANY * 1400 SULLIVAN DRIVE * GREENVILLE, NC 27834