



N25XMDR3 HIGHLIFT SHEETS **16.6" Battery Compartment** **36 Volt**

HYSTER

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
 EQUIPPED WITH 42" FORKS & DOUBLE REACH CARRIAGE
 RATINGS WITH BOTH STANDARD CARRIAGE AND WITH INTEGRAL SIDESHIFTER

36 Volt 16.6" Battery Compartment Minimum Battery Weight - 1850 LBS.

3STG FFL VISTA MAST			CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
OEC/ID	OALH	MFH	CARRIAGE	INTEGRAL SS	CARRIAGE		INTEGRAL SIDESHIFTER	
			LOAD	LOAD CENTERED	LIFT HEIGHT	LOAD	LIFT HEIGHT	LOAD CENTERED
34"	89.0	197.0	2500	2500	197.0	2500	197.0	2500
	95.0	212.0	2500	2500	212.0	2500	212.0	2500
	107.0	242.0	2500	2500	242.0	2500	242.0	2500
	110.0	251.0	2350	2300	247.0	2500	245.0	2500
	119.0	272.0	1850	1800	247.0	2500	245.0	2500
35"	89.0	197.0	2500	2500	197.0	2500	197.0	2500
	95.0	212.0	2500	2500	212.0	2500	212.0	2500
	107.0	242.0	2500	2500	242.0	2500	242.0	2500
	110.0	251.0	2500	2450	251.0	2500	249.0	2500
	119.0	272.0	1950	1900	251.0	2500	249.0	2500
36"	89.0	197.0	2500	2500	197.0	2500	197.0	2500
	95.0	212.0	2500	2500	212.0	2500	212.0	2500
	107.0	242.0	2500	2500	242.0	2500	242.0	2500
	110.0	251.0	2500	2500	251.0	2500	251.0	2500
	119.0	272.0	2050	2000	256.0	2500	254.0	2500
38"	89.0	197.0	2500	2500	197.0	2500	197.0	2500
	95.0	212.0	2500	2500	212.0	2500	212.0	2500
	107.0	242.0	2500	2500	242.0	2500	242.0	2500
	110.0	251.0	2500	2500	251.0	2500	251.0	2500
	119.0	272.0	2300	2250	265.0	2500	263.0	2500
41"	89.0	197.0	2500	2500	197.0	2500	197.0	2500
	95.0	212.0	2500	2500	212.0	2500	212.0	2500
	107.0	242.0	2500	2500	242.0	2500	242.0	2500
	110.0	251.0	2500	2500	251.0	2500	251.0	2500
	119.0	272.0	2500	2500	272.0	2500	272.0	2500
42"	89.0	197.0	2500	2500	197.0	2500	197.0	2500
	95.0	212.0	2500	2500	212.0	2500	212.0	2500
	107.0	242.0	2500	2500	242.0	2500	242.0	2500
	110.0	251.0	2500	2500	251.0	2500	251.0	2500
	119.0	272.0	2500	2500	272.0	2500	272.0	2500
43"	89.0	197.0	2500	2500	197.0	2500	197.0	2500
	95.0	212.0	2500	2500	212.0	2500	212.0	2500
	107.0	242.0	2500	2500	242.0	2500	242.0	2500
	110.0	251.0	2500	2500	251.0	2500	251.0	2500
	119.0	272.0	2500	2500	272.0	2500	272.0	2500
44"	89.0	197.0	2500	2500	197.0	2500	197.0	2500
	95.0	212.0	2500	2500	212.0	2500	212.0	2500
	107.0	242.0	2500	2500	242.0	2500	242.0	2500
	110.0	251.0	2500	2500	251.0	2500	251.0	2500
	119.0	272.0	2500	2500	272.0	2500	272.0	2500
48"	89.0	197.0	2500	2500	197.0	2500	197.0	2500
	95.0	212.0	2500	2500	212.0	2500	212.0	2500
	107.0	242.0	2500	2500	242.0	2500	242.0	2500
	110.0	251.0	2500	2500	251.0	2500	251.0	2500
	119.0	272.0	2500	2500	272.0	2500	272.0	2500

NOTE: Above Capacities are with Standard 5"x3" Load Wheels.

RATED VERSION V0112.00

Actual mast dimensions may vary slightly from nominal dimensions stated in price book. The Overall Lowered Height (OALH) is stated to the next higher full inch and Maximum Fork Height (MFH) is stated to the next lower full inch, to allow for manufacturing tolerances.

Contact Application Engineering if you have questions about the information above, or about a specific truck configuration.

High Lift masts are mast which because of their type or lift height, require capacity reduction and/or back tilt restriction. In the case of this model configuration, ant fork height greater than 245" is a high lift.

HYSTER COMPANY * 1400 SULLIVAN DRIVE * GREENVILLE, NC 27834