



N30XMR3 HIGHLIFT SHEETS **14.6" Battery Compartment** **24 Volt**

HYSTER

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
 EQUIPPED WITH 42" FORKS & SINGLE REACH CARRIAGE
 RATINGS WITH BOTH STANDARD CARRIAGE AND WITH INTEGRAL SIDESHIFTER

24 Volt 14.6" Battery Compartment Minimum Battery Weight - 1500 LBS.

3STG FFL VISTA MAST			CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
OEC/ID	OALH	MFH	CARRIAGE	INTEGRAL SS	CARRIAGE		INTEGRAL SIDESHIFTER	
			LOAD	LOAD CENTERED	LIFT HEIGHT	LOAD	LIFT HEIGHT	LOAD CENTERED
34"	89.0	197.0	3000	3000	197.0	3000	197.0	3000
	95.0	212.0	3000	3000	212.0	3000	212.0	3000
	107.0	242.0	2850	2800	237.0	3000	234.0	3000
	110.0	251.0	2600	2550	237.0	3000	234.0	3000
35"	89.0	197.0	3000	3000	197.0	3000	197.0	3000
	95.0	212.0	3000	3000	212.0	3000	212.0	3000
	107.0	242.0	2950	2900	240.0	3000	237.0	3000
	110.0	251.0	2750	2700	240.0	3000	238.0	3000
36"	89.0	197.0	3000	3000	197.0	3000	197.0	3000
	95.0	212.0	3000	3000	212.0	3000	212.0	3000
	107.0	242.0	3000	3000	242.0	3000	242.0	3000
	110.0	251.0	2850	2800	245.0	3000	242.0	3000
38"	89.0	197.0	3000	3000	197.0	3000	197.0	3000
	95.0	212.0	3000	3000	212.0	3000	212.0	3000
	107.0	242.0	3000	3000	242.0	3000	242.0	3000
	110.0	251.0	3000	2950	251.0	3000	250.0	3000
41"	89.0	197.0	3000	3000	197.0	3000	197.0	3000
	95.0	212.0	3000	3000	212.0	3000	212.0	3000
	107.0	242.0	3000	3000	242.0	3000	242.0	3000
	110.0	251.0	3000	3000	251.0	3000	251.0	3000
42"	89.0	197.0	3000	3000	197.0	3000	197.0	3000
	95.0	212.0	3000	3000	212.0	3000	212.0	3000
	107.0	242.0	3000	3000	242.0	3000	242.0	3000
	110.0	251.0	3000	3000	251.0	3000	251.0	3000
43"	89.0	197.0	3000	3000	197.0	3000	197.0	3000
	95.0	212.0	3000	3000	212.0	3000	212.0	3000
	107.0	242.0	3000	3000	242.0	3000	242.0	3000
	110.0	251.0	3000	3000	251.0	3000	251.0	3000
44"	89.0	197.0	3000	3000	197.0	3000	197.0	3000
	95.0	212.0	3000	3000	212.0	3000	212.0	3000
	107.0	242.0	3000	3000	242.0	3000	242.0	3000
	110.0	251.0	3000	3000	251.0	3000	251.0	3000
48"	89.0	197.0	3000	3000	197.0	3000	197.0	3000
	95.0	212.0	3000	3000	212.0	3000	212.0	3000
	107.0	242.0	3000	3000	242.0	3000	242.0	3000
	110.0	251.0	3000	3000	251.0	3000	251.0	3000

NOTE: Above Capacities are with Standard 5"x3" Load Wheels.

RATED VERSION V0112.00

Actual mast dimensions may vary slightly from nominal dimensions stated in price book. The Overall Lowered Height (OALH) is stated to the next higher full inch and Maximum Fork Height (MFH) is stated to the next lower full inch, to allow for manufacturing tolerances.

Contact Application Engineering if you have questions about the information above, or about a specific truck configuration.

High Lift masts are mast which because of their type or lift height, require capacity reduction and/or back tilt restriction. In the case of this model configuration, ant fork height greater than 221" is a high lift.

HYSTER COMPANY * 1400 SULLIVAN DRIVE * GREENVILLE, NC 27834