



N30MXDR3 HIGHLIFT SHEETS **18.8" Battery Compartment** **36 Volt**

HYSTER

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
 EQUIPPED WITH 42" FORKS & DOUBLE REACH CARRIAGE
 RATINGS WITH BOTH STANDARD CARRIAGE AND WITH INTEGRAL SIDESHIFTER

36 Volt 18.8" Battery Compartment Minimum Battery Weight - 2200 LBS.

3STG FFL VISTA MAST			CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
OEC/ID	OALH	MFH	CARRIAGE	INTEGRAL SS	CARRIAGE		INTEGRAL SIDESHIFTER	
			LOAD	LOAD CENTERED	LIFT HEIGHT	LOAD	LIFT HEIGHT	LOAD CENTERED
35"	119.0	272.0	3000	3000	272.0	3000	272.0	3000
	125.0	287.0	3000	3000	287.0	3000	287.0	3000
	131.0	302.0	2950	2900	300.0	3000	297.0	3000
	138.0	320.0	2450	2400	300.0	3000	298.0	3000
	143.0	332.0	2200	2150	300.0	3000	298.0	3000
38"	119.0	272.0	3000	3000	272.0	3000	272.0	3000
	125.0	287.0	3000	3000	287.0	3000	287.0	3000
	131.0	302.0	3000	3000	302.0	3000	302.0	3000
	138.0	320.0	2850	2800	316.0	3000	314.0	3000
	143.0	332.0	2550	2500	316.0	3000	314.0	3000
41"	119.0	272.0	3000	3000	272.0	3000	272.0	3000
	125.0	287.0	3000	3000	287.0	3000	287.0	3000
	131.0	302.0	3000	3000	302.0	3000	302.0	3000
	138.0	320.0	3000	3000	320.0	3000	320.0	3000
	143.0	332.0	2950	2900	330.0	3000	328.0	3000
42"	119.0	272.0	3000	3000	272.0	3000	272.0	3000
	125.0	287.0	3000	3000	287.0	3000	287.0	3000
	131.0	302.0	3000	3000	302.0	3000	302.0	3000
	138.0	320.0	3000	3000	320.0	3000	320.0	3000
	143.0	332.0	3000	3000	332.0	3000	332.0	3000
43"	119.0	272.0	3000	3000	272.0	3000	272.0	3000
	125.0	287.0	3000	3000	287.0	3000	287.0	3000
	131.0	302.0	3000	3000	302.0	3000	302.0	3000
	138.0	320.0	3000	3000	320.0	3000	320.0	3000
	143.0	332.0	3000	3000	332.0	3000	332.0	3000
48"	119.0	272.0	3000	3000	272.0	3000	272.0	3000
	125.0	287.0	3000	3000	287.0	3000	287.0	3000
	131.0	302.0	3000	3000	302.0	3000	302.0	3000
	138.0	320.0	3000	3000	320.0	3000	320.0	3000
	143.0	332.0	3000	3000	332.0	3000	332.0	3000
49"	119.0	272.0	3000	3000	272.0	3000	272.0	3000
	125.0	287.0	3000	3000	287.0	3000	287.0	3000
	131.0	302.0	3000	3000	302.0	3000	302.0	3000
	138.0	320.0	3000	3000	320.0	3000	320.0	3000
	143.0	332.0	3000	3000	332.0	3000	332.0	3000

RATED VERSION V0112.00

Note: Above Capacities are shown with Standard 5"x4" Load Wheels.

Note: 18.8" Battery Compartment NOT Available with MFH >332".

Actual mast dimensions may vary slightly from nominal dimensions stated in price book. The Overall Lowered Height (OALH) is stated to the next higher full inch and Maximum Fork Height (MFH) is stated to the next lower full inch, to allow for manufacturing tolerances.

Contact Application Engineering if you have questions about the information above, or about a specific truck configuration.

High lift masts are masts which because of their type or lift height require capacity reduction. In the case of this model configuration, any fork height greater than 299" is a high lift.

HYSTER COMPANY * 1400 SULLIVAN DRIVE * GREENVILLE, NC 27834