



N40XMR3 HIGHLIFT SHEETS **14.6" Battery Compartment** **24/36 Volt**

HYSTER

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
 EQUIPPED WITH 42" FORKS & SINGLE REACH CARRIAGE
 RATINGS WITH BOTH STANDARD CARRIAGE AND WITH INTEGRAL SIDESHIFTER

24/36 Volt 14.6" Battery Compartment Minimum Battery Weight - 1500 LBS.

3STG FFL VISTA MAST			CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
OEC/ID	OALH	MFH	CARRIAGE	INTEGRAL SS	CARRIAGE		INTEGRAL SIDESHIFTER	
			LOAD	LOAD CENTERED	LIFT HEIGHT	LOAD	LIFT HEIGHT	LOAD CENTERED
34"	89.0	197.0	4000	3900	197.0	4000	190.0	4000
	95.0	212.0	3650	3600	206.0	4000	196.0	4000
	107.0	242.0	3000	2900	206.0	4000	206.0	4000
	110.0	251.0	2700	2650	206.0	4000	206.0	4000
	119.0	272.0	2150	2100	205.0	4000	205.0	4000
35"	89.0	197.0	4000	3900	197.0	4000	190.0	4000
	95.0	212.0	3900	3850	206.0	4000	196.0	4000
	107.0	242.0	3000	2950	210.0	4000	206.0	4000
	110.0	251.0	2850	2800	210.0	4000	209.0	4000
	119.0	272.0	2250	2200	210.0	4000	210.0	4000
36"	89.0	197.0	4000	3900	197.0	4000	190.0	4000
	95.0	212.0	3950	3850	206.0	4000	196.0	4000
	107.0	242.0	3150	3100	215.0	4000	206.0	4000
	110.0	251.0	2950	2850	216.0	4000	209.0	4000
	119.0	272.0	2350	2300	216.0	4000	216.0	4000
38"	89.0	197.0	4000	3900	197.0	4000	190.0	4000
	95.0	212.0	3900	3850	206.0	4000	196.0	4000
	107.0	242.0	3350	3300	215.0	4000	206.0	4000
	110.0	251.0	3150	3050	218.0	4000	209.0	4000
	119.0	272.0	2650	2600	226.0	4000	218.0	4000
41"	89.0	197.0	4000	3900	197.0	4000	190.0	4000
	95.0	212.0	3900	3850	206.0	4000	196.0	4000
	107.0	242.0	3750	3700	215.0	4000	206.0	4000
	110.0	251.0	3400	3300	218.0	4000	209.0	4000
	119.0	272.0	2950	2900	227.0	4000	218.0	4000
42"	89.0	197.0	4000	3900	197.0	4000	190.0	4000
	95.0	212.0	3900	3850	206.0	4000	196.0	4000
	107.0	242.0	3750	3700	215.0	4000	206.0	4000
	110.0	251.0	3600	3600	218.0	4000	209.0	4000
	119.0	272.0	3000	2950	227.0	4000	218.0	4000
43"	89.0	197.0	4000	3900	197.0	4000	190.0	4000
	95.0	212.0	3900	3850	206.0	4000	196.0	4000
	107.0	242.0	3750	3700	215.0	4000	206.0	4000
	110.0	251.0	3700	3650	218.0	4000	209.0	4000
	119.0	272.0	3100	3050	227.0	4000	218.0	4000
44"	89.0	197.0	4000	3900	197.0	4000	190.0	4000
	95.0	212.0	3900	3850	206.0	4000	196.0	4000
	107.0	242.0	3750	3700	215.0	4000	206.0	4000
	110.0	251.0	3700	3650	218.0	4000	209.0	4000
	119.0	272.0	3150	3100	227.0	4000	218.0	4000
48"	89.0	197.0	4000	3900	197.0	4000	190.0	4000
	95.0	212.0	3900	3850	206.0	4000	196.0	4000
	107.0	242.0	3750	3700	215.0	4000	206.0	4000
	110.0	251.0	3700	3650	218.0	4000	209.0	4000
	119.0	272.0	3600	3550	227.0	4000	218.0	4000

NOTE: Above Capacities are with Standard 5"x3" Load Wheels.

RATED VERSION V0112.00

Actual mast dimensions may vary slightly from nominal dimensions stated in price book. The Overall Lowered Height (OALH) is stated to the next higher full inch and Maximum Fork Height (MFH) is stated to the next lower full inch, to allow for manufacturing tolerances.

Contact Application Engineering if you have questions about the information above, or about a specific truck configuration.

High Lift masts are mast which because of their type or lift height, require capacity reduction and/or back tilt restriction. In the case of this model configuration, ant fork height greater than 200" is a high lift.

HYSTER COMPANY * 1400 SULLIVAN DRIVE * GREENVILLE, NC 27834