



N40XMR3 HIGHLIFT SHEETS **16.6" Battery Compartment** **24 Volt**

HYSTER

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
 EQUIPPED WITH 42" FORKS & SINGLE REACH CARRIAGE
 RATINGS WITH BOTH STANDARD CARRIAGE AND WITH INTEGRAL SIDESHIFTER

24 Volt 16.6" Battery Compartment Minimum Battery Weight - 1600 LBS.

3STG FFL VISTA MAST			CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
OEC/ID	OALH	MFH	CARRIAGE	INTEGRAL SS	CARRIAGE		INTEGRAL SIDESHIFTER	
			LOAD	LOAD CENTERED	LIFT HEIGHT	LOAD	LIFT HEIGHT	LOAD CENTERED
34"	89.0	197.0	4000	4000	197.0	4000	197.0	4000
	95.0	212.0	3650	3600	208.0	4000	207.0	4000
	107.0	242.0	2900	2850	207.0	4000	207.0	4000
	110.0	251.0	2700	2650	207.0	4000	207.0	4000
	119.0	272.0	2100	2050	206.0	4000	206.0	4000
35"	89.0	197.0	4000	4000	197.0	4000	197.0	4000
	95.0	212.0	4000	3950	212.0	4000	207.0	4000
	107.0	242.0	3000	2950	212.0	4000	212.0	4000
	110.0	251.0	2800	2750	212.0	4000	212.0	4000
	119.0	272.0	2250	2200	211.0	4000	211.0	4000
36"	89.0	197.0	4000	4000	197.0	4000	197.0	4000
	95.0	212.0	4000	3950	212.0	4000	207.0	4000
	107.0	242.0	3100	3050	217.0	4000	217.0	4000
	110.0	251.0	2900	2850	217.0	4000	216.0	4000
	119.0	272.0	2350	2350	217.0	4000	216.0	4000
38"	89.0	197.0	4000	4000	197.0	4000	197.0	4000
	95.0	212.0	4000	3950	212.0	4000	207.0	4000
	107.0	242.0	3300	3200	227.0	4000	219.0	4000
	110.0	251.0	3050	3000	227.0	4000	223.0	4000
	119.0	272.0	2650	2550	226.0	4000	226.0	4000
41"	89.0	197.0	4000	4000	197.0	4000	197.0	4000
	95.0	212.0	4000	3950	212.0	4000	207.0	4000
	107.0	242.0	3850	3750	229.0	4000	219.0	4000
	110.0	251.0	3350	3350	232.0	4000	223.0	4000
	119.0	272.0	2850	2850	240.0	4000	231.0	4000
42"	89.0	197.0	4000	4000	197.0	4000	197.0	4000
	95.0	212.0	4000	3950	212.0	4000	207.0	4000
	107.0	242.0	3850	3750	229.0	4000	219.0	4000
	110.0	251.0	3750	3700	232.0	4000	223.0	4000
	119.0	272.0	2950	2900	240.0	4000	231.0	4000
43"	89.0	197.0	4000	4000	197.0	4000	197.0	4000
	95.0	212.0	4000	3950	212.0	4000	207.0	4000
	107.0	242.0	3850	3750	229.0	4000	219.0	4000
	110.0	251.0	3800	3700	232.0	4000	223.0	4000
	119.0	272.0	3050	3000	238.0	4000	227.0	4000
44"	89.0	197.0	4000	4000	197.0	4000	197.0	4000
	95.0	212.0	4000	3950	212.0	4000	207.0	4000
	107.0	242.0	3850	3750	229.0	4000	219.0	4000
	110.0	251.0	3800	3750	232.0	4000	223.0	4000
	119.0	272.0	3150	3100	240.0	4000	231.0	4000
48"	89.0	197.0	4000	4000	197.0	4000	197.0	4000
	95.0	212.0	4000	3950	212.0	4000	207.0	4000
	107.0	242.0	3850	3750	229.0	4000	219.0	4000
	110.0	251.0	3800	3700	232.0	4000	223.0	4000
	119.0	272.0	3700	3600	240.0	4000	231.0	4000

NOTE: Above Capacities are with Standard 5"x3" Load Wheels.

RATED VERSION V0112.00

Actual mast dimensions may vary slightly from nominal dimensions stated in price book. The Overall Lowered Height (OALH) is stated to the next higher full inch and Maximum Fork Height (MFH) is stated to the next lower full inch, to allow for manufacturing tolerances.

Contact Application Engineering if you have questions about the information above, or about a specific truck configuration.

High Lift masts are mast which because of their type or lift height, require capacity reduction and/or back tilt restriction. In the case of this model configuration, any fork height greater than 206" is a high lift.