



N40XMR3 HIGHLIFT SHEETS **16.6" Battery Compartment** **36 Volt**

HYSTER

CAPACITY IN POUNDS @24 INCH LOAD CENTER
 EQUIPPED WITH 42" FORKS & SINGLE REACH CARRIAGE
 RATINGS WITH BOTH STANDARD CARRIAGE AND WITH INTEGRAL SIDESHIFTER

36 Volt 16.6" Battery Compartment Minimum Battery Weight - 1850 LBS.

3STG FFL VISTA MAST			CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
OEC/ID	OALH	MFH	CARRIAGE	INTEGRAL SS	CARRIAGE		INTEGRAL SIDESHIFTER	
			LOAD	LOAD CENTERED	LIFT HEIGHT	LOAD	LIFT HEIGHT	LOAD CENTERED
34"	89.0	197.0	4000	4000	197.0	4000	197.0	4000
	95.0	212.0	3800	3750	208.0	4000	208.0	4000
	107.0	242.0	3050	3000	207.0	4000	207.0	4000
	110.0	251.0	2850	2800	207.0	4000	207.0	4000
	119.0	272.0	2250	2200	208.0	4000	206.0	4000
35"	89.0	197.0	4000	4000	197.0	4000	197.0	4000
	95.0	212.0	4000	4000	212.0	4000	208.0	4000
	107.0	242.0	3150	3100	213.0	4000	213.0	4000
	110.0	251.0	2950	2900	213.0	4000	213.0	4000
	119.0	272.0	2350	2350	213.0	4000	213.0	4000
36"	89.0	197.0	4000	4000	197.0	4000	197.0	4000
	95.0	212.0	4000	4000	212.0	4000	212.0	4000
	107.0	242.0	3250	3200	218.0	4000	218.0	4000
	110.0	251.0	3000	2950	218.0	4000	218.0	4000
	119.0	272.0	2500	2450	217.0	4000	217.0	4000
38"	89.0	197.0	4000	4000	197.0	4000	197.0	4000
	95.0	212.0	4000	4000	212.0	4000	212.0	4000
	107.0	242.0	3450	3400	229.0	4000	228.0	4000
	110.0	251.0	3200	3150	228.0	4000	228.0	4000
	119.0	272.0	2800	2700	228.0	4000	228.0	4000
41"	89.0	197.0	4000	4000	197.0	4000	197.0	4000
	95.0	212.0	4000	4000	212.0	4000	212.0	4000
	107.0	242.0	4000	3950	242.0	4000	237.0	4000
	110.0	251.0	3500	3500	245.0	4000	240.0	4000
	119.0	272.0	3000	2950	244.0	4000	244.0	4000
42"	89.0	197.0	4000	4000	197.0	4000	197.0	4000
	95.0	212.0	4000	4000	212.0	4000	212.0	4000
	107.0	242.0	4000	3950	242.0	4000	237.0	4000
	110.0	251.0	3850	3850	249.0	4000	240.0	4000
	119.0	272.0	3100	3000	248.0	4000	245.0	4000
43"	89.0	197.0	4000	4000	197.0	4000	197.0	4000
	95.0	212.0	4000	4000	212.0	4000	212.0	4000
	107.0	242.0	4000	3950	242.0	4000	237.0	4000
	110.0	251.0	3950	3900	249.0	4000	240.0	4000
	119.0	272.0	3200	3100	254.0	4000	245.0	4000
44"	89.0	197.0	4000	4000	197.0	4000	197.0	4000
	95.0	212.0	4000	4000	212.0	4000	212.0	4000
	107.0	242.0	4000	3950	242.0	4000	237.0	4000
	110.0	251.0	3950	3900	249.0	4000	240.0	4000
	119.0	272.0	3250	3200	254.0	4000	245.0	4000
48"	89.0	197.0	4000	4000	197.0	4000	197.0	4000
	95.0	212.0	4000	4000	212.0	4000	212.0	4000
	107.0	242.0	4000	3950	242.0	4000	237.0	4000
	110.0	251.0	3950	3900	249.0	4000	240.0	4000
	119.0	272.0	3850	3750	254.0	4000	245.0	4000

NOTE: Above Capacities are with Standard 5"x3" Load Wheels.

RATED VERSION V0112.00

Actual mast dimensions may vary slightly from nominal dimensions stated in price book. The Overall Lowered Height (OALH) is stated to the next higher full inch and Maximum Fork Height (MFH) is stated to the next lower full inch, to allow for manufacturing tolerances.

Contact Application Engineering if you have questions about the information above, or about a specific truck configuration.

High Lift masts are mast which because of their type or lift height, require capacity reduction and/or back tilt restriction. In the case of this model, ant fork height greater than 200" is a high lift.

HYSTER COMPANY * 1400 SULLIVAN DRIVE * GREENVILLE, NC 27834