



N45MXR3 HIGHLIFT SHEETS **18.8" Battery Compartment** **36 Volt**

HYSTER

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
 EQUIPPED WITH 42" FORKS & SINGLE REACH CARRIAGE
 RATINGS WITH BOTH STANDARD CARRIAGE AND WITH INTEGRAL SIDESHIFTER

36 Volt 18.8" Battery Compartment Minimum Battery Weight - 2200 LBS.

3STG FFL VISTA MAST			CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
OEC/ID	OALH	MFH	CARRIAGE	INTEGRAL SS	CARRIAGE		INTEGRAL SIDESHIFTER	
			LOAD	LOAD CENTERED	LIFT HEIGHT	LOAD	LIFT HEIGHT	LOAD CENTERED
35"	119.0	272.0	4400	4300	269.0	4500	258.0	4500
	125.0	287.0	3900	3800	270.0	4500	265.0	4500
	131.0	302.0	3400	3350	270.0	4500	269.0	4500
	138.0	320.0	2950	2900	270.0	4500	269.0	4500
	143.0	332.0	2600	2550	271.0	4500	269.0	4500
38"	119.0	272.0	4450	4350	269.0	4500	258.0	4500
	125.0	287.0	4250	4250	272.0	4500	272.0	4500
	131.0	302.0	3950	3900	272.0	4500	272.0	4500
	138.0	320.0	3400	3350	272.0	4500	272.0	4500
	143.0	332.0	3050	3000	272.0	4500	272.0	4500
41"	119.0	272.0	4450	4350	269.0	4500	258.0	4500
	125.0	287.0	4250	4250	272.0	4500	265.0	4500
	131.0	302.0	4050	4050	272.0	4500	271.0	4500
	138.0	320.0	3800	3800	272.0	4500	272.0	4500
	143.0	332.0	3500	3450	272.0	4500	272.0	4500
42"	119.0	272.0	4450	4350	269.0	4500	258.0	4500
	125.0	287.0	4250	4250	272.0	4500	265.0	4500
	131.0	302.0	4050	4050	272.0	4500	271.0	4500
	138.0	320.0	3800	3800	272.0	4500	272.0	4500
	143.0	332.0	3650	3600	272.0	4500	272.0	4500
43"	119.0	272.0	4450	4350	269.0	4500	258.0	4500
	125.0	287.0	4250	4250	272.0	4500	265.0	4500
	131.0	302.0	4050	4050	272.0	4500	271.0	4500
	138.0	320.0	3800	3800	272.0	4500	272.0	4500
	143.0	332.0	3650	3650	272.0	4500	272.0	4500
48"	119.0	272.0	4450	4350	269.0	4500	258.0	4500
	125.0	287.0	4250	4250	272.0	4500	265.0	4500
	131.0	302.0	4050	4050	272.0	4500	271.0	4500
	138.0	320.0	3800	3800	272.0	4500	272.0	4500
	143.0	332.0	3650	3650	272.0	4500	272.0	4500
49"	119.0	272.0	4450	4350	269.0	4500	258.0	4500
	125.0	287.0	4250	4250	272.0	4500	265.0	4500
	131.0	302.0	4050	4050	272.0	4500	271.0	4500
	138.0	320.0	3800	3800	272.0	4500	272.0	4500
	143.0	332.0	3650	3650	272.0	4500	272.0	4500

RATED VERSION V0112.00

Note: Above Capacities are shown with Standard 5"x4" Load Wheels.

Note: 18.8" Battery Compartment NOT Available with MFH >332".

Actual mast dimensions may vary slightly from nominal dimensions stated in price book. The Overall Lowered Height (OALH) is stated to the next higher full inch and Maximum Fork Height (MFH) is stated to the next lower full inch, to allow for manufacturing tolerances.

Contact Application Engineering if you have questions about the information above, or about a specific truck configuration.

High lift masts are masts which because of their type or lift height require capacity reduction. In the case of this model configuration, any fork height greater than 299" is a high lift.

HYSTER COMPANY * 1400 SULLIVAN DRIVE * GREENVILLE, NC 27834