



R30XMA2 Straddle OrderPicker High Lift Sheets



R30XMA2

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
STANDARD 40" WIDE X 27.5" DEEP OPERATOR PLATFORM
42" FORKS, STANDARD 6" X 3" LOAD WHEEL AND 85.5" WHEELBASE

CAPACITIES ARE WITH OR WITHOUT TRAVEL ABOVE 272 MFH
NOTE: 10 DEG STEER LIMIT WITH TRAVEL ABOVE 272" (105-03)

42" O.E.C. (BASE ARM "OPEN END CLEARANCE") Min. Batt. Wt. 1500 lbs.					
		CAPACITY @ MFH		RATED CAPACITY	
VISTA MAST TYPE	M.F.H.	CAPACITY	LIFT HEIGHT	CAPACITY	LIFT HEIGHT
3 STAGE NO FREELIFT	195	3000	195	3000	195
	213	3000	213	3000	213
	240	3000	240	3000	240
	270	2500	270	3000	240
	300	2000	300	3000	240
	315	1750	315	3000	240
	330	1500	330	3000	240
	345	N/A	N/A	N/A	N/A
	360	N/A	N/A	N/A	N/A

44" O.E.C. (BASE ARM "OPEN END CLEARANCE") Min. Batt. Wt. 1500 lbs.					
		CAPACITY @ MFH		RATED CAPACITY	
VISTA MAST TYPE	M.F.H.	CAPACITY	LIFT HEIGHT	CAPACITY	LIFT HEIGHT
3 STAGE NO FREELIFT	195	3000	195	3000	195
	213	3000	213	3000	213
	240	3000	240	3000	240
	270	3000	270	3000	270
	300	2500	300	3000	270
	315	1750	315	3000	270
	330	1500	330	3000	270
	345	N/A	N/A	N/A	N/A
	360	N/A	N/A	N/A	N/A

46" O.E.C. (BASE ARM "OPEN END CLEARANCE") Min. Batt. Wt. 1500 lbs.					
		CAPACITY @ MFH		RATED CAPACITY	
VISTA MAST TYPE	M.F.H.	CAPACITY	LIFT HEIGHT	CAPACITY	LIFT HEIGHT
3 STAGE NO FREELIFT	195	3000	195	3000	195
	213	3000	213	3000	213
	240	3000	240	3000	240
	270	3000	270	3000	270
	300	2700	300	3000	272
	315	2000	315	3000	272
	330	1750	330	3000	272
	345	1500	345	3000	272
	360	1000	360	3000	272

48" O.E.C. (BASE ARM "OPEN END CLEARANCE") Min. Batt. Wt. 1500 lbs.					
		CAPACITY @ MFH		RATED CAPACITY	
VISTA MAST TYPE	M.F.H.	CAPACITY	LIFT HEIGHT	CAPACITY	LIFT HEIGHT
3 STAGE NO FREELIFT	195	3000	195	3000	195
	213	3000	213	3000	213
	240	3000	240	3000	240
	270	3000	270	3000	270
	300	2700	300	3000	272
	315	2500	315	3000	272
	330	2000	330	3000	272
	345	1750	345	3000	272
	360	1500	360	3000	272

Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration.

Revised: 5/1/02