



R30XMF2 Furniture OrderPicker High Lift Sheets



R30XMF2

CAPACITY IN POUNDS @ 48 INCH LOAD CENTER
STANDARD 40" WIDE X 27.5" DEEP OPERATOR PLATFORM
2" X 5" X 78" FORKS, STANDARD 6" X 3" LOAD WHEEL AND 139.6" WHEELBASE

CAPACITIES ARE WITH OR WITHOUT TRAVEL ABOVE 272 MFH
NOTE: 10 DEG STEER LIMIT WITH TRAVEL ABOVE 272" (105-03)

42" O.E.C. (BASE ARM OPEN END CLEARANCE) Min. Batt. Wt. 1500 lbs.					
		CAPACITY @ MFH		RATED CAPACITY	
VISTA MAST TYPE	M.F.H.	CAPACITY	LIFT HEIGHT	CAPACITY	LIFT HEIGHT
3 STAGE NO FREELIFT	240	1500	240	1500	240
	270	1500	270	1500	270
	300	1500	300	1500	300
	330	1300	330	1500	300
	360	1100	360	1500	300

44" O.E.C. (BASE ARM OPEN END CLEARANCE) Min. Batt. Wt. 1500 lbs.					
		CAPACITY @ MFH		RATED CAPACITY	
VISTA MAST TYPE	M.F.H.	CAPACITY	LIFT HEIGHT	CAPACITY	LIFT HEIGHT
3 STAGE NO FREELIFT	240	1500	240	1500	240
	270	1500	270	1500	270
	300	1500	300	1500	300
	330	1300	330	1500	300
	360	1100	360	1500	300

46" O.E.C. (BASE ARM OPEN END CLEARANCE) Min. Batt. Wt. 1500 lbs.					
		CAPACITY @ MFH		RATED CAPACITY	
VISTA MAST TYPE	M.F.H.	CAPACITY	LIFT HEIGHT	CAPACITY	LIFT HEIGHT
3 STAGE NO FREELIFT	240	1500	240	1500	240
	270	1500	270	1500	270
	300	1500	300	1500	300
	330	1500	330	1500	330
	360	1300	360	1500	330

48" O.E.C. (BASE ARM OPEN END CLEARANCE) Min. Batt. Wt. 1500 lbs.					
		CAPACITY @ MFH		RATED CAPACITY	
VISTA MAST TYPE	M.F.H.	CAPACITY	LIFT HEIGHT	CAPACITY	LIFT HEIGHT
3 STAGE NO FREELIFT	240	1500	240	1500	240
	270	1500	270	1500	270
	300	1500	300	1500	300
	330	1500	330	1500	330
	360	1300	360	1500	330

Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration.

Revised: 5/1/02