



R30XMS2 41" Base OrderPicker High Lift Sheets



R30XMS2

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
STANDARD 40" WIDE X 27.5" DEEP OPERATOR PLATFORM
42" FORKS, STANDARD 4" X 3" LOAD WHEELS AND 55" WHEELBASE

41" BASE WIDTH Min. Batt. Wt. 900 lbs.

<i>WITHOUT TRAVEL ABOVE 150"</i>		CAPACITY @ MFH		RATED CAPACITY	
VISTA MAST TYPE	M.F.H.	CAPACITY	LIFT HEIGHT	CAPACITY	LIFT HEIGHT
2 STAGE NO FREELIFT	135	3000	135	3000	135
	147	3000	147	3000	147
	157	3000	157	3000	157
	165	3000	165	3000	165
3 STAGE NO FREELIFT	195	3000	195	3000	195
	213	3000	213	3000	213
	228	2500	228	3000	213
	240	2000	240	3000	213

41" BASE WIDTH Min. Batt. Wt. 900 lbs.

<i>WITH TRAVEL ABOVE 150"</i> <i>10 DEG STEER LIMIT (105-01)</i>		CAPACITY @ MFH		RATED CAPACITY	
VISTA MAST TYPE	M.F.H.	CAPACITY	LIFT HEIGHT	CAPACITY	LIFT HEIGHT
2 STAGE NO FREELIFT	135	3000	135	3000	135
	147	3000	147	3000	147
	157	3000	157	3000	157
	165	3000	165	3000	165
3 STAGE NO FREELIFT	195	3000	195	3000	195
	213	2800	213	3000	195
	228	2500	228	3000	195
	240	2000	240	3000	195

Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration.

Revised: 5/1/02