



S100FT HIGHLIFT SHEETS



CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
EQUIPPED WITH 42 INCH FORKS

	MFH	CAPACITY @ MFH			LIFT HEIGHT AT MAXIMUM CAPACITY				
		CARRIAGE		SIDESHIFT	MFH	CARRIAGE		MFH	SIDESHIFT
	(IN)	42" WIDE	48" WIDE	48" WIDE	(IN)	42" WIDE	48" WIDE	(IN)	48" WIDE
2 STAGE LFL 6 DEG BACKTILT STD TREAD	110.2	10650	-----	10550	110.2	10650	-----	110.2	10550
	133.9	10650	-----	10500	133.9	10650	-----	133.9	10500
	157.5	10650	-----	10450	157.5	10650	-----	157.5	10450
	185.0	10650	-----	10400	185.0	10650	-----	185.0	10400
	204.7	10400	-----	10150	204.7	10650	-----	185.0	10350
	228.3	10100	-----	9850	228.3	10650	-----	185.0	10300
	252.0	9800	-----	9450	252.0	10650	-----	185.0	10250
	271.7	7450	-----	7600	271.7	10650	-----	185.0	10250
2 STAGE FFL 6 DEG BACKTILT STD TREAD	111.2	10400	-----	10200	111.2	10400	-----	111.2	10200
	134.8	10400	-----	10200	134.8	10400	-----	134.8	10200
	158.5	10400	-----	10200	158.5	10400	-----	158.5	10200
	182.1	10400	-----	10200	182.1	10400	-----	182.1	10200
	193.9	10250	-----	10050	182.1	10400	-----	182.1	10150
	205.7	10150	-----	9900	182.1	10400	-----	182.1	10150
	225.4	9900	-----	9650	182.1	10400	-----	182.1	10100
	3-STAGE FFL 6 DEG BACKTILT WIDE TREAD	163.2	10000	10000	9700	163.2	10000	10000	163.2
185.0		10000	10000	9650	185.0	10000	10000	185.0	9650
196.9		9850	9850	9650	185.0	10000	10000	185.0	9650
208.7		9750	9750	9400	185.0	10000	10000	185.0	9650
220.5		9600	9600	9400	185.0	10000	10000	185.0	9650
3 STAGE FFL 5 DEG WIDE TREAD	244.1	9300	9300	8900	185.0	10000	10000	185.0	9550
	255.9	9150	9150	8750	185.0	10000	10000	185.0	9550
	276.6	8750	8700	8400	185.0	10000	10000	185.0	9500

RELEASE VERSION V9.01 BETA

Wide Tread listed for Lift Heights where capacity or mast physical limitations are dependent on Tread Width

Maximum capacity and Lift Height at Maximum capacity with sideshifter may be influenced by channel overlap and dynamic loading factors.

Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration.

*High lift masts are masts which because of their type or lift height, require capacity reduction and/or back tilt restrictions. In the case of this model, any fork height greater than 185" (4700 mm) is a high lift.