



S120FT PRS HIGHLIFT SHEETS



ROLL CLAMP CAPACITY IN POUNDS EQUIPPED WITH 42 INCH CARRIAGE

	MFH (IN)	CAPACITY @ MFH		CAPACITY @ MFH		
		CASCADE	CASCADE	CASCADE	CASCADE	CASCADE
		90F-RCP-01C	90F-RCS-21C	100F-RCP-01C	120F-RCP-01C	100F-RCS-21C
2 STAGE LFL	185.0	9000	9000	9500	9100	9050
6 DEG	204.7	9000	9000	9350	8950	8850
BACKTILT	228.3	9000	9000	9050	8700	8600
STD TREAD	252.0	9000	9000	8750	8400	8300
	271.7	9000	9000	6300	5950	5950
2 STAGE FFL	182.1	9000	9000	9400	9000	8950
6 DEG	193.9	9000	9000	9400	9000	8950
BACKTILT	205.7	9000	9000	9300	8900	8800
STD TREAD	225.4	9000	9000	9000	8600	8550
3 STAGE FFL	163.2	9000	9000	9550	9150	9100
6 DEG	185.0	9000	9000	9500	9100	9050
BACKTILT	196.9	9000	9000	9450	9050	8950
WIDE TREAD	208.7	9000	9000	9300	8900	8800
	220.5	9000	9000	9100	8700	8650
	244.1	8900	8750	8700	8300	8250

RELEASE VERSION V9.01 BETA

Wide Tread listed for Lift Heights where capacity or mast physical limitations are dependent on Tread Width
Maximum capacity and Lift Height at Maximum capacity with sideshifter may be influenced by channel overlap and dynamic loading factors.
Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration.