



S135XL2 HIGHLIFT SHEETS

HYSTER®

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
EQUIPPED WITH 48" CARRIAGE & STANDARD TIRES

		MFH	OALH	CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
				48" FORKS	72" FORKS	LIFT HEIGHT	48" FORKS	LIFT HEIGHT	72" FORKS
S135XL2	2stg LFL 10 Deg Back Tilt	94.0	87.0	13500	13300	94.5	13500	94.5	13300
		133.0	107.0	13500	13200	134.0	13500	134.0	13200
		173.0	126.0	13400	13050	173.5	13400	173.5	13050
		212.0	146.0	12950	12650	181.0	13300	181.0	13000
	3stg FFL 6 Deg Back Tilt	143.0	86.0	13450	13150	144.0	13450	144.0	13150
		181.0	99.0	13350	13050	181.0	13350	181.0	13050
		220.0	112.0	12750	12450	181.0	13300	181.0	13000
		241.0	121.0	12400	12100	181.0	13250	181.0	12950

RATED VERSION V0112.00

Contact Application Engineering if you have questions about the information above, or about a specific truck configuration.

Actual mast dimensions may vary slightly from nominal dimensions stated in price book. The Overall Lowered Height (OALH) is stated to the next higher full inch and Maximum Fork Height (MFH) is stated to the next lower full inch, to allow for manufacturing tolerances.

High Lift masts are mast which because of their type or lift height, require capacity reduction and/or back tilt restriction.

Any S135XL2 mast with fork height greater than 147" is considered a high lift. All 3-stg masts are considered high lifts.

HYSTER COMPANY * 1400 SULLIVAN DRIVE * GREENVILLE, NC 27834