



CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
EQUIPPED WITH 48" CARRIAGE & STANDARD TIRES

		MFH	OALH	CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
				48" FORKS	72" FORKS	LIFT HEIGHT	48" FORKS	LIFT HEIGHT	72" FORKS
S155XL2	2stg LFL 10 Deg Back Tilt	94.0	87.0	15500	15300	94.5	15500	94.5	15300
		133.0	107.0	15500	15200	134.0	15500	134.0	15200
		173.0	126.0	15400	15100	173.5	15400	173.5	15100
		212.0	146.0	14950	14650	181.0	15300	181.0	15000
	3stg FFL 6 Deg Back Tilt	143.0	86.0	15200	15000	144.0	15200	144.0	15000
		181.0	99.0	15000	14800	181.0	15000	181.0	14800
		220.0	112.0	14300	14050	181.0	14800	181.0	14600
		241.0	121.0	13900	13650	181.0	14700	181.0	14500

RATED VERSION V0112.00

Contact Application Engineering if you have questions about the information above, or about a specific truck configuration.

Actual mast dimensions may vary slightly from nominal dimensions stated in price book. The Overall Lowered Height (OALH) is stated to the next higher full inch and Maximum Fork Height (MFH) is stated to the next lower full inch, to allow for manufacturing

High Lift masts are mast which because of their type or lift height, require capacity reduction and/or back tilt restriction.

Any S155XL2 mast with fork height greater than 147" is considered a high lift. All 3-stg masts are considered high lifts.

HYSTER COMPANY * 1400 SULLIVAN DRIVE * GREENVILLE, NC 27834