



S25XM HIGHLIFT SHEETS

HYSTER

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER EQUIPPED WITH 42" FORKS & STANDARD CUSHION TIRES

		MFH (in)	OALH (in)	CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
				CARRIAGE	INTEGRAL SIDESHIFT	LIFT HEIGHT	CARRIAGE	LIFT HEIGHT	INTEGRAL SIDESHIFT
S25XM Standard Tread	2 Stage LFL 5 Deg Back Tilt	84.0	60	2500	2450	84.0	2500	84.0	2450
		107.0	72	2500	2450	107.0	2500	107.0	2450
		115.0	76	2500	2450	115.0	2500	115.0	2450
		127.0	82	2500	2450	127.0	2500	127.0	2450
		131.0	84	2500	2450	131.0	2500	131.0	2450
		146.0	92	2500	2450	146.0	2500	146.0	2450
		162.0	104	2500	2350	162.0	2500	154.7	2400
		174.0	110	2400	2300	160.4	2500	151.6	2400
		190.0	118	2300	2200	156.5	2500	165.0	2300
	2 Stage FFL 5 Deg Back Tilt	105.0	71	2500	2450	105.0	2500	106.0	2450
		116.0	76	2500	2450	116.0	2500	116.0	2450
		128.0	82	2500	2450	128.0	2500	128.0	2450
		144.0	90	2500	2400	144.0	2500	144.0	2400
		168.0	104	2400	2300	154.5	2500	145.7	2400
		180.0	110	2350	2250	151.6	2500	165.0	2300
	3 Stage FFL 5 Deg Back Tilt	192.0	116	2250	2150	147.6	2500	151.6	2350
		159.0*	72	2500	2350	159.0*	2500	157.5	2400
		171.0	76	2450	2300	165.4	2500	154.5	2400
		189.0#	82	2300	2200	161.4	2500	150.6	2400
		200.0#	88	2100	2100	157.5	2500	160.4	2350
		212.0#	92	1750	1750	152.6	2500	155.5	2350

S25XM Wide Tread	2 Stage LFL 5 Deg Back Tilt	84.0	60	Same Capacity as Standard Tread		Same Capacity as Standard Tread			
		107.0	72						
		115.0	76						
		127.0	82						
		131.0	84						
		146.0	92						
	2 Stage FFL 5 Deg Back Tilt	162.0	104	Same Capacity as Standard Tread		Same Capacity as Standard Tread			
		174.0	110						
		190.0	118						
		105.0	71						
		116.0	76						
		128.0	82						
	3 Stage FFL 5 Deg Back Tilt	144.0	90	2500		2350		159.0	
		168.0	104						
		180.0	110						
		192.0	116						
		159.0	72						
	3 Stage FFL 5 Deg Back Tilt	171.0	76	2450		2300		165.4	
		189.0	82						
		200.0	89						
		212.0	92						
		159.0	72	2100		2000		152.6	
		171.0	76						
		189.0	82						
		200.0	89						
		212.0	92						

RATED VERSION V0112.00

* Highest Non-High Lift Mast Rated at Full Capacity

- Requires option Q206-98 on order - "Standard Tread with Hi-Lift Mast and Reduced Capacity Acceptance"

Wide Tread listed for Lift Heights where capacity is dependant on Tread Width

Contact appropriate Application Engineer for capacity with load centers or configurations other than those shown above.

Actual mast dimensions may vary slightly from nominal dimensions stated in price book. The designed **Overall Lowered Height (OALH)** is stated to the next higher full inch, and **Maximum Fork Height (MFH)** is stated to the next lower full inch, to allow for manufacturing tolerances.