



S30FT HIGHLIFT SHEETS



CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
EQUIPPED WITH 42" FORKS & STANDARD CUSHION TIRES
SIDESHIFT RATINGS WITH INTEGRAL SIDESHIFTER

		MFH	OALH	CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY				
				CARRIAGE	SIDESHIFT	LIFT HEIGHT	CARRIAGE	LIFT HEIGHT	SIDESHIFT	
S30FT Standard Tread	2stg LFL 5 Deg Back Tilt	83.0	61.0	3000	2900	83.0	3000	83.0	2900	
		111.0	74.0	3000	2900	111.0	3000	111.0	2900	
		115.0	76.0	3000	2900	114.0	3000	114.0	2900	
		119.0	78.0	3000	2900	119.0	3000	119.0	2900	
		123.0	80.0	3000	2900	123.0	3000	123.0	2900	
		127.0	82.0	3000	2850	127.0	3000	127.0	2850	
		190.0	118.0	2800	2700	166.0	3000	166.0	2800	
	2stg FFL 5 Deg Back Tilt	99.0	68.0	3000	2900	99.0	3000	99.0	2900	
		103.0	70.0	3000	2900	103.0	3000	103.0	2900	
		111.0	74.0	3000	2900	111.0	3000	111.0	2900	
		114.0	76.0	3000	2900	114.0	3000	114.0	2900	
		122.0	80.0	3000	2900	122.0	3000	122.0	2900	
		126.0	82.0	3000*	2850	126.0	3000	126.0	2850	
		190.0	116.0	2800	2650	164.0	3000	166.0	2800	
	3stg FFL 5 Deg Back Tilt	151.0	71.0	2950	2750	151.0	2950	151.0	2750	
		175.0	78.0	2850	2700	164.0	2950	164.0	2750	
		187.0	82.0	2750	2600	164.0	2900	164.0	2750	
		192.0	84.0	2500	2500	164.0	2900	164.0	2750	
		198.0	88.0	2300	2300	164.0	2900	164.0	2750	
		216.0	94.0	1750	1750	164.0	2900	164.0	2700	
		234.0	102.0	1300	1250	164.0	2850	164.0	2700	
		252.0	110.0	900	900	164.0	2850	164.0	2700	
	S30FT Wide Tread	3stg FFL 5 Deg Back Tilt	175.0	78.0	2850	2700	164.0	2950	164.0	2750
			187.0	82.0	2750	2600	164.0	2900	164.0	2750
			192.0	84.0	2700	2550	164.0	2900	164.0	2750
			198.0	88.0	2650	2500	164.0	2900	164.0	2750
			216.0	94.0	2450	2350	164.0	2900	164.0	2700
			234.0	102.0	1950	2000	164.0	2850	164.0	2700
252.0			110.0	1550	1550	164.0	2850	164.0	2700	

*Highest Non-High Lift Mast Rated at Full Capacity
Wide Tread listed for Lift Heights where capacity is dependant on Tread Width.

Actual mast dimensions may vary slightly from nominal dimensions stated in price book. The designed Overall Lowered Height (OALH) is stated to the next higher full inch, and Maximum Fork Height (MFH) is stated to the next lower full inch, to allow for manufacturing tolerances.

For capacity estimates for other truck configurations or for trucks with attachments, consult your copy of the Hyster HY-Rater truck rating software. Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration.

HYSTER COMPANY * 1400 SULLIVAN DRIVE * GREENVILLE, NC 27834