



S30XM HIGHLIFT SHEETS

HYSTER

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
EQUIPPED WITH 42" FORKS STANDARD CUSHION TIRES

		MFH (in)	OALH (in)	CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
				CARRIAGE	INTEGRAL SIDESHIFT	LIFT HEIGHT	CARRIAGE	LIFT HEIGHT	INTEGRAL SIDESHIFT
S30XM Standard Tread	2 Stage LFL 5 Deg Back Tilt	84.0	60	3000	2950	84.0	3000	84.0	2950
		107.0	72	3000	2950	107.0	3000	107.0	2950
		115.0	76	3000	2950	115.0	3000	115.0	2950
		127.0	82	3000	2950	127.0	3000	127.0	2950
		131.0	84	3000	2950	131.0	3000	131.0	2950
		146.0	92	3000	2900	146.0	3000	146.0	2900
		162.0	104	2950	2800	162.0	3000	144.9	2900
		174.0	110	2850	2700	153.5	3000	141.7	2900
		190.0	118	2750	2650	149.6	3000	190.0	2650
	2 Stage FFL 5 Deg Back Tilt	105.0	71	3000	2950	105.0	3000	106.0	2950
		116.0	76	3000	2900	116.0	3000	116.0	2900
		128.0	82	3000	2900	128.0	3000	128.0	2900
		144.0	90	3000	2900	144.0	3000	144.0	2900
		168.0	104	2850	2750	148.6	3000	148.6	2850
		180.0	110	2800	2650	145.7	3000	145.7	2850
	3 Stage FFL 5 Deg Back Tilt	192.0	116	2750	2600	142.7	3000	142.7	2850
		159.0*	72	3000	2850	159.0*	3000	147.6	2900
		171.0	76	2950	2750	159.4	3000	157.5	2850
		189.0#	82	2450	2500	155.5	3000	153.5	2850
		200.0#	88	2050	2100	151.6	3000	150.6	2850
		212.0#	92	1650	1650	148.6	3000	146.7	2850
S30XM Wide Tread	2 Stage LFL 5 Deg Back Tilt	84.0	60	Same Capacity as Standard Tread		Same Capacity as Standard Tread			
		107.0	72						
		115.0	76						
		127.0	82						
		131.0	84						
		146.0	92						
		162.0	104						
		174.0	110						
		190.0	118						
	2 Stage FFL 5 Deg Back Tilt	105.0	71	Same Capacity as Standard Tread		Same Capacity as Standard Tread			
		116.0	76						
		128.0	82						
		144.0	90						
		168.0	104						
		180.0	110						
	3 Stage FFL 5 Deg Back Tilt	192.0	116						
		159.0	72	3000	2850	159.0	3000	147.6	2900
		171.0	76	2950	2750	159.4	3000	157.5	2850
		189.0	82	2800	2650	155.5	3000	153.5	2850
		200.0	89	2700	2550	151.6	3000	149.6	2850
		212.0	92	2450	2450	147.6	3000	146.7	2850

RATED VERSION V0112.00

* Highest Non-High Lift Mast Rated at Full Capacity

- Requires option Q206-98 on order - "Standard Tread with Hi-Lift Mast and Reduced Capacity Acceptance"

Wide Tread listed for Lift Heights where capacity is dependant on Tread Width

Contact appropriate Application Engineer for capacity with load centers or configurations other than those shown above.

Actual mast dimensions may vary slightly from nominal dimensions stated in price book. The designed **Overall Lowered Height (OALH)** is stated to the next higher full inch, and **Maximum Fork Height (MFH)** is stated to the next lower full inch, to allow for manufacturing tolerances.