



S35FT HIGHLIFT SHEETS



CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
EQUIPPED WITH 42" FORKS & STANDARD CUSHION TIRES
SIDESHIFT RATINGS WITH INTEGRAL SIDESHIFTER

		MFH	OALH	CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY				
				CARRIAGE	SIDESHIFT	LIFT HEIGHT	CARRIAGE	LIFT HEIGHT	SIDESHIFT	
S35FT Standard Tread	2stg LFL 6 Deg Back Tilt	84.0	60.0	3500	3400	83.0	3500	83.0	3400	
		111.0	74.0	3500	3400	111.0	3500	111.0	3400	
		115.0	76.0	3500	3400	114.0	3500	114.0	3400	
		119.0	78.0	3500	3400	119.0	3500	119.0	3400	
		123.0	80.0	3500	3400	123.0	3500	123.0	3400	
		127.0	82.0	3500	3350	127.0	3500	127.0	3350	
		190.0	118.0	3300	3200	166.0	3500	166.0	3350	
	2stg FFL 6 Deg Back Tilt	99.0	68.0	3000	2900	99.0	3000	99.0	2900	
		103.0	70.0	3000	2900	103.0	3000	103.0	2900	
		111.0	74.0	3000	2900	111.0	3000	111.0	2900	
		114.0	76.0	3000	2900	114.0	3000	114.0	2900	
		122.0	80.0	3000	2900	122.0	3000	122.0	2900	
		126.0	82.0	3000	2850	126.0	3000	126.0	2850	
		190.0	116.0	2800	2650	164.0	3000	164.0	2800	
	3stg FFL 6 Deg Back Tilt	151.0	71.0	3500*	3300	151.0	3500	151.0	3300	
		175.0	78.0	3400	3200	164.0	3400	175.0	3200	
		187.0	82.0	3200	3100	164.0	3450	164.0	3250	
		192.0	86.0	2900	2950	164.0	3450	164.0	3250	
		198.0	88.0	2700	2700	164.0	3450	164.0	3250	
		216.0	94.0	2050	2050	164.0	3450	164.0	3250	
		234.0	102.0	1550	1500	164.0	3400	164.0	3200	
		252.0	110.0	1100	1050	164.0	3400	164.0	3200	
	S35FT Wide Tread	3stg FFL 6 Deg Back Tilt	175.0	78.0	3400	3200	164.0	3450	164.0	3250
			187.0	82.0	3300	3100	164.0	3450	164.0	3250
			192.0	84.0	3250	3050	164.0	3450	164.0	3250
			198.0	88.0	3000	3000	164.0	3450	164.0	3250
			216.0	94.0	2400	2400	164.0	3450	164.0	3250
			234.0	102.0	1850	1850	164.0	3400	164.0	3200
252.0			110.0	1400	1400	164.0	3400	164.0	3200	

*Highest Non-High Lift Mast Rated at Full Capacity
Wide Tread listed for Lift Heights where capacity is dependant on Tread Width.

Actual mast dimensions may vary slightly from nominal dimensions stated in price book. The designed Overall Lowered Height (OALH) is stated to the next higher full inch, and Maximum Fork Height (MFH) is stated to the next lower full inch, to allow for manufacturing tolerances.

For capacity estimates for other truck configurations or for trucks with attachments, consult your copy of the Hyster HY-Rater truck rating software. Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration.

HYSTER COMPANY * 1400 SULLIVAN DRIVE * GREENVILLE, NC 27834