



S35XM HIGHLIFT SHEETS

HYSTER®

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
EQUIPPED WITH 42" FORKS & STANDARD CUSHION TIRES

		MFH (in)	OALH (in)	CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
				CARRIAGE	INTEGRAL SIDESHIFT	LIFT HEIGHT	CARRIAGE	LIFT HEIGHT	INTEGRAL SIDESHIFT
S35XM Standard Tread	2 Stage LFL 5 Deg Back Tilt	84.0	60	3500	3400	84.0	3500	84.0	3400
		107.0	72	3500	3400	107.0	3500	107.0	3400
		115.0	76	3500	3400	115.0	3500	115.0	3400
		127.0	82	3500	3400	127.0	3500	127.0	3400
		131.0	84	3500	3400	131.0	3500	131.0	3400
		146.0	92	3500	3400	146.0	3500	146.0	3400
		162.0	104	3450	3250	162.0	3500	145.9	3400
		174.0	110	3350	3200	152.6	3500	149.6	3350
		190.0	118	3250	3100	149.6	3500	145.7	3350
	2 Stage FFL 5 Deg Back Tilt	105.0	71	3500	3400	105.0	3500	106.0	3400
		116.0	76	3500	3400	116.0	3500	116.0	3400
		128.0	82	3500	3400	128.0	3500	128.0	3400
		144.0	90	3500	3350	144.0	3500	144.0	3350
		168.0	104	3350	3200	148.6	3500	148.6	3350
		180.0	110	3300	3150	146.7	3500	145.7	3350
	3 Stage FFL 5 Deg Back Tilt	192.0	116	3200	3050	143.7	3500	143.7	3350
		159.0*	72	3500	3300	159.0*	3500	157.5	3350
		171.0	76	3400	3250	159.4	3500	158.5	3350
		189.0#	82	2900	2950	156.5	3500	155.5	3350
		200.0#	88	2400	2450	153.5	3500	158.5	3300
		212.0#	92	1950	1950	153.5	3500	155.5	3300
S35XM Wide Tread	2 Stage LFL 5 Deg Back Tilt	84.0	60	Same Capacity as Standard Tread		Same Capacity as Standard Tread			
		107.0	72						
		115.0	76						
		127.0	82						
		131.0	84						
		146.0	92						
		162.0	104						
		174.0	110						
		190.0	118						
	2 Stage FFL 5 Deg Back Tilt	105.0	71	Same Capacity as Standard Tread		Same Capacity as Standard Tread			
		116.0	76						
		128.0	82						
		144.0	90						
		168.0	104						
		180.0	110						
	3 Stage FFL 5 Deg Back Tilt	192.0	116						
		159.0	72	3500	3300	159.0	3500	157.5	3350
		171.0	76	3400	3250	159.4	3500	158.5	3350
		189.0	82	3250	3150	156.5	3500	155.5	3350
		200.0	88	2850	2900	153.5	3500	158.5	3300
		212.0	92	2400	2450	153.5	3500	155.5	3300

RATED VERSION V0112.00

* Highest Non-High Lift Mast Rated at Full Capacity

- Requires option Q206-98 on order - "Standard Tread with Highlift Mast and Reduced Capacity Acceptance"

Wide Tread listed for Lift Heights where capacity is dependant on Tread Width

Contact appropriate Application Engineer for capacity with load centers or configurations other than those shown above.

Actual mast dimensions may vary slightly from nominal dimensions stated in price book. The designed **Overall Lowered Height (OALH)** is stated to the next higher full inch, and **Maximum Fork Height (MFH)** is stated to the next lower full inch, to allow for man

HYSTER COMPANY * 1400 SULLIVAN DRIVE * GREENVILLE, NC 27834