



S40FTS HIGHLIFT SHEETS



CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
EQUIPPED WITH 42" FORKS & STANDARD CUSHION TIRES
SIDESHIFT RATINGS WITH INTEGRAL SIDESHIFTER

		MFH	OALH	CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
				CARRIAGE	SIDESHIFT	LIFT HEIGHT	CARRIAGE	LIFT HEIGHT	SIDESHIFT
S40FTS Standard Tread	2stg LFL 6 Deg Back Tilt	84.0	60.0	4000	3900	83.0	4000	83.0	3900
		111.0	74.0	4000	3900	111.0	4000	111.0	3900
		115.0	76.0	4000	3900	114.0	4000	114.0	3900
		119.0	78.0	4000	3900	119.0	4000	119.0	3900
		123.0	80.0	4000	3900	123.0	4000	123.0	3900
		127.0	82.0	4000	3850	127.0	4000	127.0	3850
		190.0	118.0	3800	3650	166.0	4000	166.0	3800
	2stg FFL 6 Deg Back Tilt	99.0	68.0	4000	3900	99.0	4000	99.0	3900
		103.0	70.0	4000	3900	103.0	4000	103.0	3900
		111.0	74.0	4000	3900	111.0	4000	111.0	3900
		114.0	76.0	4000	3900	114.0	4000	114.0	3900
		122.0	80.0	4000	3900	122.0	4000	122.0	3900
		126.0	82.0	4000	3850	126.0	4000	126.0	3850
		190.0	116.0	3750	3600	164.0	4000	164.0	3800
	3stg FFL 6 Deg Back Tilt	151.0	71.0	4000*	3750	151.0	4000	151.0	3750
		175.0	78.0	3800	3700	164.0	3950	175.0	3750
		187.0	82.0	3150	3200	164.0	3950	164.0	3750
		192.0	86.0	2900	2950	164.0	3950	164.0	3750
		198.0	88.0	2600	2650	164.0	3950	164.0	3750
		216.0	94.0	1900	1900	164.0	3950	164.0	3700
		234.0	102.0	1300	1350	164.0	3900	164.0	3700
		252.0	110.0	850	800	164.0	3900	164.0	3700
	S40FTS Wide Tread	175.0	78.0	3900	3700	164.0	3950	164.0	3750
		187.0	82.0	3600	3600	164.0	3950	164.0	3750
		192.0	84.0	3350	3400	164.0	3950	164.0	3750
		198.0	88.0	3050	3100	164.0	3950	164.0	3750
		216.0	94.0	2350	2400	164.0	3950	164.0	3700
		234.0	102.0	1750	1750	164.0	3900	164.0	3700
		252.0	110.0	1250	1200	164.0	3900	164.0	3700

*Highest Non-High Lift Mast Rated at Full Capacity

Wide Tread listed for Lift Heights where capacity is dependant on Tread Width.

Actual mast dimensions may vary slightly from nominal dimensions stated in price book. The designed Overall Lowered Height (OALH) is stated to the next higher full inch, and Maximum Fork Height (MFH) is stated to the next lower full inch, to allow for manufacturing tolerances.

For capacity estimates for other truck configurations or for trucks with attachments, consult your copy of the Hyster HY-Rater truck rating software. Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration.

HYSTER COMPANY * 1400 SULLIVAN DRIVE * GREENVILLE, NC 27834