



S60XM HIGHLIFT SHEET

HYSTER®

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
EQUIPPED WITH 42" FORKS & STANDARD TIRES

		MFH	OALH	CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
				CARRIAGE	INTEGRAL SIDESHIFT	LIFT HEIGHT	CARRIAGE	LIFT HEIGHT	INTEGRAL SIDESHIFT
Standard Tread	2stg LFL 8 Deg Back Tilt	114.0	79.0	6000	5850	114.5	6000	114.5	5850
		126.0	85.0	6000	5850	126.5	6000	126.4	5850
		146.0	94.0	6000	5800	146.0	6000	146.0	5800
		165.0	108.0	5950	5750	164.0	6000	164.0	6000
		185.0	118.0	5800	5550	164.0	6000	164.0	6000
	2stg FFL 8 Deg Back Tilt	114.0	79.0	6000	5800	114.5	6000	114.5	5800
		126.0	85.0	6000	5800	126.5	6000	126.5	5800
		146.0	94.0	6000	5800	146.0	6000	146.0	5800
		165.0	106.0	5950	5750	164.0	6000	164.0	6000
		185.0	116.0	5800	5550	164.0	6000	164.0	6000
	3stg FFL 5 Deg Back Tilt	164.0	77.0	6000	5750	164.0	6000	164.0	5750
		181.0	83.0	5800	5550	164.0	6000	164.0	6000
		193.0	88.0	5700	5450	164.0	6000	164.0	6000
		211.0	94.0	5500	5250	164.0	6000	164.0	6000
		229.0	102.0	4100	4300	164.0	6000	164.0	6000
	4stg FFL 4 Deg Back Tilt	240.0	84.0	3300	3300	209.0	5000	210.0	4950
		252.0	88.0	2800	2800	210.0	4950	211.0	4900
		264.0	92.0	2350	2350	212.0	4900	213.0	4850
		276.0	96.0	1950	1950	213.0	4850	214.0	4800
		288.0	100.0	1600	1550	214.0	4850	216.0	4750
Wide Tread	3stg FFL 5 Deg Back Tilt	229.0	102.0	5300	5050	164.0	6000	164.0	6000
		240.0	84.0	4600	4650	232.0	5000	234.0	4950
	4stg FFL 4 Deg Back Tilt	252.0	88.0	4100	4150	234.0	4950	236.0	4900
		264.0	92.0	3650	3650	236.0	4900	237.0	4850
		276.0	96.0	3150	3200	237.0	4850	239.0	4800
		288.0	100.0	2750	2750	238.0	4850	240.0	4750

RATED VERSION V0005.02

*Wide Tread listed for Lift Heights where capacity is dependant on Tread Width.

Contact Application Engineering if you have questions about the information above, or about a specific truck configuration.

Actual mast dimensions may vary slightly from nominal dimensions stated in price book. The Overall Lowered Height (OALH) is stated to the next higher full inch and Maximum Fork Height (MFH) is stated to the next lower full inch, to allow for manufacturing tolerances.

High Lift masts are mast which because of their type or lift height, require capacity reduction and/or back tilt restriction.

Any S60-65XM mast with fork height greater than 164" is considered a high lift.

HYSTER COMPANY * 1400 SULLIVAN DRIVE * GREENVILLE, NC 27834