



S65XM HIGHLIFT SHEET

HYSTER®

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
EQUIPPED WITH 42" FORKS & STANDARD TIRES

		MFH	OALH	CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
				CARRIAGE	INTEGRAL SIDESHIFT	LIFT HEIGHT	CARRIAGE	LIFT HEIGHT	INTEGRAL SIDESHIFT
Standard Tread	2stg LFL 8 Deg Back Tilt	114.0	79.0	6500	6300	114.5	6500	114.5	6300
		126.0	85.0	6500	6300	126.5	6500	126.4	6300
		146.0	94.0	6500	6300	146.0	6500	146.0	6300
		165.0	108.0	6450	6250	164.0	6500	164.0	6500
		185.0	118.0	6250	6000	164.0	6500	164.0	6500
	2stg FFL 8 Deg Back Tilt	114.0	79.0	6500	6300	114.5	6500	114.5	6300
		126.0	85.0	6500	6300	126.5	6500	126.5	6300
		146.0	94.0	6500	6300	146.0	6500	146.0	6300
		165.0	106.0	6450	6250	164.0	6500	164.0	6500
		185.0	116.0	6250	6050	164.0	6500	164.0	6500
	3stg FFL 5 Deg Back Tilt	164.0	77.0	6500	6250	164.0	6500	164.0	6250
		181.0	83.0	6300	6050	164.0	6500	164.0	6500
		193.0	88.0	5100	5300	164.0	6500	164.0	6500
		211.0	94.0	3200	3300	164.0	6500	164.0	6500
		229.0	102.0	1800	1850	164.0	6500	164.0	6500
	4stg FFL 4 Deg Back Tilt	240.0	84.0	3300	1750	209.0	6500	184.0	4950
		252.0	88.0	2800	1250	210.0	4950	185.0	4900
		264.0	92.0	2350	750	212.0	4900	187.0	4850
		276.0	96.0	1950	350	213.0	4850	187.0	4800
	Wide Tread	193.0	88.0	6200	5950	164.0	6500	164.0	6500
		211.0	94.0	5800	5750	164.0	6500	164.0	6500
		229.0	102.0	4200	4350	164.0	6500	164.0	6500
		240.0	84.0	3150	3200	206.0	5000	207.0	4950
		252.0	88.0	2700	2700	207.0	4950	209.0	4900
	4stg FFL 4 Deg Back Tilt	264.0	92.0	2250	2250	209.0	4900	210.0	4850
		276.0	96.0	1800	1850	210.0	4850	212.0	4800

RATED VERSION V0005.02

*Wide Tread listed for Lift Heights where capacity is dependant on Tread Width.

Contact Application Engineering if you have questions about the information above, or about a specific truck configuration.

Actual mast dimensions may vary slightly from nominal dimensions stated in price book. The Overall Lowered Height (OALH) is stated to the next higher full inch and Maximum Fork Height (MFH) is stated to the next lower full inch, to allow for manufacturing tolerances.

High Lift masts are mast which because of their type or lift height, require capacity reduction and/or back tilt restriction.

Any S60-65XM mast with fork height greater than 164" is considered a high lift.

HYSTER COMPANY * 1400 SULLIVAN DRIVE * GREENVILLE, NC 27834