



S70XM HIGHLIFT SHEETS

HYSTER®

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
EQUIPPED WITH 42 INCH FORKS
SIDESHIFT RATINGS WITH INTEGRAL SIDESHIFTER

	CAPACITY @ MFH					LIFT HEIGHT AT MAXIMUM CAPACITY					
	MFH	OAH				42" CARRIAGE		42" SIDESHIFT		48" SIDESHIFT	
			42" CARRIAGE	42" SIDESHIFT	48" SIDESHIFT	LIFT HEIGHT	CAPACITY	LIFT HEIGHT	CAPACITY	LIFT HEIGHT	CAPACITY
2-STAGE LFL 6 DEG BACKTILT STD TREAD	122.0	84.0	7500	7250	7250	122.0	7500	122.0	7250	122.0	7250
	146.0	96.0	7450	7200	7200	146.0	7450	146.0	7200	146.0	7200
	170.0	107.5	7350	7150	7150	161.4	7450	166.3	7200	169.5	7150
	185.0	115.5	7100	6900	6900	174.6	7200	166.8	7150	174.6	7050
	197.0	125.0	6950	6750	6750	174.6	7150	174.6	7000	174.6	6950
	209.0	131.0	6800	6650	6600	174.6	7150	174.6	6950	174.6	7000
	221.0	141.0	6650	6450	6450	174.6	7100	174.6	6900	174.6	6900
	236.0	149.0	6450	6300	6250	174.6	7050	174.6	6850	174.6	6850
2-STAGE FFL 6 DEG BACKTILT STD TREAD	122.0	84.0	7200	6950	6950	122.0	7200	122.0	6950	122.0	6950
	170.0	107.5	7100	6900	6900	167.3	7150	169.5	6900	169.5	6900
	185.0	115.5	6900	6700	6650	167.8	7100	167.7	6900	170.7	6850
	197.0	125.0	6750	6550	6500	174.6	7000	170.6	6850	174.6	6750
	209.0	131.0	6600	6400	6400	174.6	6950	174.6	6750	174.6	6750
	221.0	141.0	6450	6250	6250	174.6	6900	174.6	6700	174.6	6650
	236.0	149.0	6250	6100	6050	174.6	6800	174.6	6600	174.6	6600

	CAPACITY @ MFH					LIFT HEIGHT AT MAXIMUM CAPACITY					
	MFH	OAH				42" CARRIAGE		42" SIDESHIFT		48" SIDESHIFT	
			42" CARRIAGE	48" CARRIAGE	48" SIDESHIFT	LIFT HEIGHT	CAPACITY	LIFT HEIGHT	CAPACITY	LIFT HEIGHT	CAPACITY
3-STAGE FFL 6 DEG BACKTILT WIDE TREAD	174.0*	84.0	7000	7000	6700	174.0	7000	174.0	7000	174.0	6700
	186.0	88.0	6850	6850	6600	174.6	7000	174.6	7000	174.6	6700
	195.0	92.0	6750	6750	6500	174.6	7000	174.6	6950	174.6	6650
	207.0	95.5	6600	6600	6350	174.6	6950	174.6	6950	174.6	6650
	219.0	99.5	6500	6450	6250	174.6	6950	174.6	6900	174.6	6650
	237.0	107.5	6300	6250	6000	174.6	6850	174.6	6850	174.6	6550
	253.5	113.5	6050	6050	5750	174.6	6800	174.6	6800	174.6	6500
	277.5	123.5	5700	5700	5450	174.6	6650	174.6	6650	174.6	6350

RATED VERSION V0112.04

Wide Tread listed for Lift Heights where capacity is dependant on Tread Width.

Maximum capacity and Lift Height at Maximum capacity with sideshifter may be influenced by channel overlap and dynamic loading factors.

Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration.

*High lift masts are masts which because of their type or lift height, require capacity reduction and/or back tilt restriction. In the case of this model, any fork height greater than 173" (4 394 mm) is a high lift.

HYSTER COMPANY * 1400 SULLIVAN DRIVE * GREENVILLE, NC 27834