



# W20ZR (2 STAGE MAST) HIGH LIFT SHEETS

**HYSTER**

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER  
EQUIPPED WITH 42 INCH CLASS II FORKS  
CAPACITIES BASED UPON 10.0" x 5.0" POLY DRIVE TIRE & 3.4" x 2.8" POLY LOAD WHEELS

24 Volt

13.5" Battery Compartment

Minimum Battery Weight - 600lbs

| ID/OEC  | MFH  | OALH  | CAPACITY @ MFH |            | LIFT HEIGHT @ MAX CAPACITY |      |             |      |
|---------|------|-------|----------------|------------|----------------------------|------|-------------|------|
|         |      |       | STD. CRG.      | SIDE SHIFT | CARRIAGE                   |      | SIDE SHIFT  |      |
|         |      |       | LOAD           | LOAD       | LIFT HEIGHT                | LOAD | LIFT HEIGHT | LOAD |
| 2-Stage |      |       |                |            |                            |      |             |      |
| 35"     | 72.0 | 101.0 | 2000           | 2000       | 101.0                      | 2000 | 101.0       | 2000 |
|         | 77.0 | 111.0 | 2000           | 2000       | 111.0                      | 2000 | 111.0       | 2000 |
|         | 83.0 | 123.0 | 2000           | 2000       | 123.0                      | 2000 | 123.0       | 2000 |
|         | 92.0 | 141.0 | 2000           | 2000       | 141.0                      | 2000 | 141.0       | 2000 |
| 37"     | 72.0 | 101.0 | 2000           | 2000       | 101.0                      | 2000 | 101.0       | 2000 |
|         | 77.0 | 111.0 | 2000           | 2000       | 111.0                      | 2000 | 111.0       | 2000 |
|         | 83.0 | 123.0 | 2000           | 2000       | 123.0                      | 2000 | 123.0       | 2000 |
|         | 92.0 | 141.0 | 2000           | 2000       | 141.0                      | 2000 | 141.0       | 2000 |
| 41"     | 72.0 | 101.0 | 2000           | 2000       | 101.0                      | 2000 | 101.0       | 2000 |
|         | 77.0 | 111.0 | 2000           | 2000       | 111.0                      | 2000 | 111.0       | 2000 |
|         | 83.0 | 123.0 | 2000           | 2000       | 123.0                      | 2000 | 123.0       | 2000 |
|         | 92.0 | 141.0 | 2000           | 2000       | 141.0                      | 2000 | 141.0       | 2000 |
| 43"     | 72.0 | 101.0 | 2000           | 2000       | 101.0                      | 2000 | 101.0       | 2000 |
|         | 77.0 | 111.0 | 2000           | 2000       | 111.0                      | 2000 | 111.0       | 2000 |
|         | 83.0 | 123.0 | 2000           | 2000       | 123.0                      | 2000 | 123.0       | 2000 |
|         | 92.0 | 141.0 | 2000           | 2000       | 141.0                      | 2000 | 141.0       | 2000 |
| 49"     | 72.0 | 101.0 | 2000           | 2000       | 101.0                      | 2000 | 101.0       | 2000 |
|         | 77.0 | 111.0 | 2000           | 2000       | 111.0                      | 2000 | 111.0       | 2000 |
|         | 83.0 | 123.0 | 2000           | 2000       | 123.0                      | 2000 | 123.0       | 2000 |
|         | 92.0 | 141.0 | 2000           | 2000       | 141.0                      | 2000 | 141.0       | 2000 |

Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration.

HYSTER COMPANY \* 1400 SULLIVAN DRIVE \* GREENVILLE, NC 27834