



W20ZR (3 STAGE MAST) HIGH LIFT SHEETS

HYSTER®

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
EQUIPPED WITH 42 INCH CLASS II FORKS
CAPACITIES BASED UPON 10.0" x 5.0" POLY DRIVE TIRE & 3.4" x 2.8" POLY LOAD WHEELS

24 Volt

13.5" Battery Compartment

Minimum Battery Weight - 600lbs

ID/OEC	OALH	MFH	CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
			STD. CRG.	SIDE SHIFT	CARRIAGE		SIDE SHIFT	
			LOAD	LOAD	LIFT HEIGHT	LOAD	LIFT HEIGHT	LOAD
3-Stage								
35"	73.0	149.0	2000	2000	149.0	2000	149.0	2000
	78.0	164.0	2000	2000	164.0	2000	164.0	2000
	83.0	179.0	2000	2000	179.0	2000	179.0	2000
37"	73.0	149.0	2000	2000	149.0	2000	149.0	2000
	78.0	164.0	2000	2000	164.0	2000	164.0	2000
	83.0	179.0	2000	2000	179.0	2000	179.0	2000
41"	73.0	149.0	2000	2000	149.0	2000	149.0	2000
	78.0	164.0	2000	2000	164.0	2000	164.0	2000
	83.0	179.0	2000	2000	179.0	2000	179.0	2000
43"	73.0	149.0	2000	2000	149.0	2000	149.0	2000
	78.0	164.0	2000	2000	164.0	2000	164.0	2000
	83.0	179.0	2000	2000	179.0	2000	179.0	2000
49"	73.0	149.0	2000	2000	149.0	2000	149.0	2000
	78.0	164.0	2000	2000	164.0	2000	164.0	2000
	83.0	179.0	2000	2000	179.0	2000	179.0	2000

Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration.

HYSTER COMPANY * 1400 SULLIVAN DRIVE * GREENVILLE, NC 27834