



W25ZC HIGH LIFT SHEETS

HYSTER®

CAPACITY IN POUNDS @ 24 INCH LOAD CENTER
EQUIPPED WITH 42 INCH CLASS II FORKS
CAPACITIES BASED UPON 10.0" x 5.0" POLY DRIVE TIRE & 10.0" x 6.0" POLY LOAD WHEELS

24 Volt

13.4" Battery Compartment

Minimum Battery Weight - 900lbs

OALH	MFH	CAPACITY @ MFH		LIFT HEIGHT @ MAX CAPACITY			
		STD CRG	SIDE SHIFT	STD CRG		SIDE SHIFT	
		LOAD	LOAD	LIFT HEIGHT	LOAD	LIFT HEIGHT	LOAD
2-Stage							
72.0	104.0	2500	2300	104.0	2500	104.0	2300
77.0	114.0	2500	2300	114.0	2500	114.0	2300
83.0	126.0	2500	2300	126.0	2500	126.0	2300
92.0	144.0	2500	2300	144.0	2500	144.0	2300
96.0	152.0	2500	2300	152.0	2500	152.0	2300
3-Stage							
72.0*	157.0	2500	2300	157.0	2500	157.0	2300
77.0	172.0	2400	2200	157.0	2500	157.0	2300
83.0	190.0	2200	2000	144.0	2500	144.0	2300
92.0	217.0	2000	1800	144.0	2500	144.0	2300
96.0	229.0	1500	1300	144.0	2500	144.0	2300

Contact Applications Engineering if you have questions about the information above, or about a specific truck configuration.

*High lift masts are masts which because of their type or lift height, require capacity reduction and/or back tilt restriction. In the case of this model, any fork height greater than 157" (3 988 mm) is a high lift.

HYSTER COMPANY * 1400 SULLIVAN DRIVE * GREENVILLE, NC 27834